

## EUROLITE Set 2x LED KLS-180 + 2x LED WF-40 + DMX LED Color Chief Controller

2x Compact Light Set, 2x Projection effect for water reflections including DMX lighting desk

GTIN: 4026397578058



### Features:

- Crossbar with integrated DMX control unit and stand sleeve
- Compact lightweight
- Color blend stepless; color change adjustable; colors preset; Dimmer electronic
- Strobe effect
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; IR remote control; sound to light via microphone; master/slave function; QuickDMX via 5-pin XLR (M) mounting version (optional)
- Flicker-free
- With a beam angle of 9°
- With mounting bracket
- Monochrome 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; decoration; mobile djs / entertainer; party room; restaurants, bars and hotels
- Silent operation
- Application possibility: On stand
- spotlight**
- 4 LEDs 8 W SMD 9080 4in1 RGBW (homogenous color mix)<BR>4 spots controlled separately
- bar**
- 4 LEDs 1 W SMD 8072 cold white (CW)<BR> LEDs controlled separately
- <p>EUROLITE LED WF-40 Water Effect
- <h2 class="featureSatz">Projection effect for water reflections, with RGBW color mixing & DMX</h2>Static and moving water effects with a 3D look in vibrant colors
- 1 LED 40 W COB (chip-on-board) 4in1 RGBW
- Focus manual
- Dimmer electronic; color blend stepless; Rotation speed stepless; color change adjustable

### Logistic

EAN / GTIN: 4026397578058  
 Weight: 37,10 kg  
 Length: 1.26 m  
 Width: 0.52 m  
 Height: 0.67 m

- Beam effect; strobe effect
- Integrated show programs
- Direct color selection for 18 preset colors
- The device is cooled by passive convection cooling
- Control via DMX; sound to light via microphone; stand-alone; master/slave function
- With mounting bracket
- Monochrome 4 digit 7-segment LED display
- For application areas such as: Clubs/dancing school; decoration; restaurants, bars and hotels; mobile djs / entertainer
- Application possibility: Suspended; on stand
- <p>EUROLITE DMX LED Color Chief Controller
- <h2 class="featureSatz">DMX lighting desk with innovative control concept for LED spotlights</h2>Easy control of LED spotlights with up to 6 colors, light bars as well as simple lighting effects
- For 8 devices or device groups, each with up to 4 segments
- Quick and easy programming
- Additional fixtures can be configured manually
- 8 color effects directly selectable
- 3 additional channels available per fixture (e.g. for rotations)
- Color wheel selection and simulation
- 24 memory spaces for scenes and chases
- Several chases and scenes can be run simultaneously
- USB port for storing program data
- Sound control via audio signal or TAP button
- Master dimming, fade time and run time easily adjustable
- Can transmit up to 240 DMX channels
- (19") 48.3 cm rack installation 3 U
- Programmable 24 scenes/chases distributed over 1 page/s
- Control via DMX; sound to light via RCA (F) mounting version; sound to light via microphone
- Firmware can be updated
- Desktop console housing
- For application areas such as: Clubs/dancing school; party room; Trade fair and shop fitting; mobile djs / entertainer; restaurants, bars and hotels
- Silent operation

## Technical specifications:

---

Weight: 32.50 kg

---

### EUROLITE LED KLS-180 Compact Light Set

|                    |  |
|--------------------|--|
| Power supply:      | 100-240 V AC, 50/60 Hz   |
| Power consumption: | 80 W   |
| Power connection:  | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided) |
| Power output:      | 1 x IEC connector (F) mounting version   |
| Fuse:              | 5 x 20 mm, T 1 A fuse replaceable  |
| Lamp type:         | LED lamp   |
| Flash rate:        | 0.5 - 20 Hz  |
| DMX channels:      | 3; 4; 8; 21  |
| DMX input:         | 3-pin XLR (M) mounting version   |
| DMX output:        | 3-pin XLR (F) mounting version   |
| Cooling:           | Passive convection cooling   |

|                          |   |
|--------------------------|---|
| Control:                 | Stand-alone; DMX; IR remote control; sound to light via microphone; master/slave function; QuickDMX via 5-pin XLR (M) mounting version (optional) |
| Fixtures available for:  | LED PC-Control 512; Light Captain; Light J; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Colorchief   |
| Projection:              | Flicker-free  |
| PWM frequency:           | 9000 Hz   |
| Beam angle (1/2 peak):   | 9°  |
| Beam angle (1/10 peak):  | 18°   |
| Housing color:           | Black   |
| Attachment system:       | Ø 35mm<br>1x mounting bracket   |
| Display type:            | Monochrome 4 digit 7-segment LED display  |
| Material:                | Metal; plastic  |
| Dimensions:              | Width: 60.5 cm<br>Depth: 14 cm<br>Height: 23 cm   |
| Weight:                  | 4.85 kg   |
| Noise classification:    | Class 0 (no noise at all)   |
| Photobiological safety:  | Risk Group 0  |
| LED type:                | 4 x 8 W SMD 9080 4in1 RGBW (homogenous color mix)   |
| LED type:                | 4 x 1 W SMD 8072 cold white (CW)  |
| Diameter mounting holes: | 3 x Ø11mm; 2 x Ø3mm   |
| Material:                | Metal, 2 mm   |
| Cable construction:      | 3 x 0.75 mm <sup>2</sup> H05VV-F  |
| Battery:                 | 1 x button cell 3.0 V CR2025 lithium manganese built-in   |
| Special product:         | Not designed for household room illumination  |
| Intended use:            | Show effect lighting  |

#### **EUROLITE LED WF-40 Water Effect**

|                    |  |
|--------------------|--|
| Power supply:      | 100-240 V AC, 50/60 Hz   |
| Power consumption: | 25 W   |
| Protection class:  | Protection class I   |
| Power connection:  | Mains input via IEC connector (M) mounting version power supply cord with safety plug included |
| Device fuse:       | 5 x 20 mm, T 1 A fuse replaceable  |
| Lamp type:         | LED lamp   |
| LED type:          | 1 x 40 W COB (chip-on-board) 4in1 RGBW   |
| Flash rate:        | 2.5 - 19 Hz  |
| Equipment:         | Focus manual   |
| DMX channels:      | 9  |
| DMX input:         | 1 x 3-pin XLR (M) mounting version   |

|                          |  |
|--------------------------|--|
| DMX output:              | 1 x 3-pin XLR (F) mounting version   |
| Cooling:                 | Passive convection cooling   |
| Control:                 | DMX; sound to light via microphone; stand-alone; master/slave function           |
| Fixtures available for:  | Light J; LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2; Colorchief |
| Beam angle (1/2 peak):   | 30°  |
| Housing color:           | Black matte  |
| Attachment system:       | Mounting bracket   |
| Display type:            | Monochrome 4 digit 7-segment LED display   |
| Material:                | Metal  |
| Dimensions:              | Width: 27.7 cm<br>Depth: 25.2 cm<br>Height: 18.7 cm                              |
| Weight:                  | 3.32 kg  |
| Noise classification:    | Class 2 (slight noise)   |
| Cable construction:      | 3 x 0.75 mm <sup>2</sup> H05VV-F   |
| Diameter mounting holes: | 3 x Ø10mm  |
| Material:                | Metal, 2 mm  |
| Special product:         | Not designed for household room illumination                                     |
| Intended use:            | Show effect lighting   |

#### **EUROLITE DMX LED Color Chief Controller**

|                          |   |
|--------------------------|---|
| Power supply:            | 100-240 V AC, 50/60 Hz<br>9V DC 800 mA  |
| Power consumption:       | 7.2 W   |
| Protection class:        | Protection class III  |
| Power connection:        | Mains input via coaxial power connector (M) mounting version power supply cord with AC adapter (provided) |
| Programs:                | Programmable 24 scenes/chases distributed over 1 page/s   |
| DMX channels:            | Output 240  |
| DMX output:              | 1 x 3-pin XLR (F) mounting version  |
| Control:                 | DMX; sound to light via RCA (F) mounting version; sound to light via microphone                           |
| Housing color:           | Black   |
| Available storage media: | USB devices (FAT 32)  |
| USB port:                | Type A  |
| Color:                   | Black   |
| PC connect:              | , firmware can be updated   |
| Housing design:          | (19") 48.3 cm rack installation 3 U<br>Desktop console housing  |
| Dimensions:              | Width: 48.3 cm<br>Depth: 13.35 cm<br>Height: 8.5 cm   |

|                       |                           |
|-----------------------|---------------------------|
| Weight:               | 2.25 kg                   |
| Noise classification: | Class 0 (no noise at all) |

---

**Scope of delivery:**

---

**2 x EUROLITE LED KLS-180 Compact Light Set**

- 1 x spotlight
- 1 x power cord
- 1 x bag
- 1 x remote control
- 1 x battery
- 1 x user manual

**2 x EUROLITE LED WF-40 Water Effect**

- 1 x light effect
- 1 x power cord
- 1 x user manual

**1 x EUROLITE DMX LED Color Chief Controller**

- 1 x controller
- 1 x user manual
- 1 x external mains adapter