

EUROLITE Set 4x LED BAR-12 QCL RGBA Bar + Case

4x spotlight bar with 12 x 4 W 4in1 LED (RGBA) including flightcase

Art. No.: 20000460

GTIN: 4026397642162



Features:

- 12 LEDs 4 W high-power 4in1 RGBA (homogenous color mix)
- Color change adjustable; Dimmer electronic; color blend stepless
- Strobe effect
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional)
- Flicker-free
- With a beam angle of 17°
- With mounting bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; decoration; mobile djs / entertainer; party room; restaurants, bars and hotels; advertisement/Shop window
- Silent operation
- Application possibility: Suspended; wall mounting
- <p>ROADINGER Flightcase EC-B252 4x LED BAR-252 RGB
- <h2 class="featureSatz">Carrying case</h2>High-quality workmanship with plywood multi-layer glued 7 mm, black, laminated
- Interior with foam padding
- Aluminum profile frames 30mm with rounded edges
- Rugged carrying handle
- 3 chrome tip-over locks
- 2 high-quality butterfly locks
- For further information about this product, please refer to the Data Sheet under "Downloads"

Logistic

EAN / GTIN: 4026397642162

Weight: 26,60 kg

Length: 1.30 m

Width: 0.50 m

Height: 0.30 m

Bulky product

Technical specifications:

Weight: 22.50 kg

EUROLITE LED BAR-12 QCL RGBA Bar

| | |
|--------------------------|--|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 24 W |
| Protection class: | Protection class I |
| Power connection: | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided) |
| Power output: | 1 x IEC connector (F) mounting version |
| Lamp type: | LED lamp |
| LED type: | 12 x 4 W high-power 4in1 RGBA (homogenous color mix) |
| Flash rate: | 0 - 20 Hz |
| DMX channels: | 2; 4; 5; 6; 9 |
| DMX input: | 3-pin XLR (M) mounting version |
| DMX output: | 3-pin XLR (F) mounting version |
| Cooling: | Passive convection cooling |
| Control: | Stand-alone; DMX; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional) |
| Fixtures available for: | LED PC-Control 512; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; Light J; Colorchief |
| Projection: | Flicker-free |
| Beam angle (1/2 peak): | 17° |
| Housing color: | Black |
| Attachment system: | Mounting bracket |
| Display type: | 4 digit 7-segment LED display |
| Material: | Aluminum casting; metal; plastic |
| Dimensions: | Length: 110 cm Depth: 6.5 cm Height: 10 cm |
| Weight: | 2.90 kg |
| Noise classification: | Class 0 (no noise at all) |
| Photobiological safety: | Risk Group 0 |
| Diameter mounting holes: | 1 x Ø20mm; 1 x Ø10mm; 1 x Ø8mm; 2 x Ø7mm |
| Material: | Metal, 2 mm |
| Cable construction: | H05VV-F |
| Cable length: | Approx. 1.2 m |

| | |
|------------------|--|
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |

ROADINGER Flightcase EC-B252 4x LED BAR-252 RGB

| | |
|--------------------------|--|
| Maximum load: | 25 kg |
| Aluminum profile frames: | 30 mm |
| Carrying handle: | 1 pc/pcs |
| Stop hinge: | 3 pc/pcs |
| Lock: | Butterfly lock: 2 pc/pcs |
| Material: | Plywood multi-layer glued, 7 mm |
| Color: | Black, laminated |
| Inside dimensions: | 108 cm x 44 cm x 7.5 cm |
| Device compartment: | 108 cm x 6.5 cm x 7.5 cm |
| Dimensions: | Width: 117 cm Depth: 48 cm Height: 17 cm |
| Weight: | 10.90 kg |

Scope of delivery:

- 1 x light effect
- 2 x mounting bracket
- 1 x power cord
- 2 x knurled screw
- 2 x washer
- 1 x user manual