

## EUROLITE Set 12x LED BAR-12 QCL RGBW Bar + Case L

12x spotlight bar with 12 x 4 W 4in1 LED (RGBW) including PRO flightcase

Art. No.: 20000463

GTIN: 4026397642193



### Features:

- 12 LEDs 4 W high-power 4in1 RGBW (homogenous color mix)
- Color change adjustable; Dimmer electronic; color blend stepless
- Strobe effect
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional)
- Flicker-free
- With a beam angle of 17°
- With mounting bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; decoration; mobile djs / entertainer; party room; restaurants, bars and hotels; advertisement/Shop window
- Silent operation
- Application possibility: Suspended; wall mounting
- <p>ROADINGER Flightcase 12x LED Bar with wheels
- <h2 class="featureSatz">Trunk case with castors, PRO version</h2>Universal modular system for LED bars up to 1 m length
- 3 stackable units accommodate 4 LED bars each
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Removable cover
- Aluminum profile frames 20mm with rounded edges
- 6 hinged, chromium plated case handles
- 12 high-quality butterfly locks
- 4 x castors with 2 locking brakes

### Logistic

EAN / GTIN: 4026397642193

Weight: 79,05 kg

Length: 1.20 m

Width: 0.80 m

Height: 0.90 m

Bulky product

- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

## Technical specifications:

### EUROLITE LED BAR-12 QCL RGBW Bar

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	24 W
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Fuse:	5 x 20 mm, T 0.5 A fuse replaceable
Lamp type:	LED lamp
LED type:	12 x 4 W high-power 4in1 RGBW (homogenous color mix)
Flash rate:	0.5 - 24 Hz
DMX channels:	2; 4; 5; 6; 9
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional)
Fixtures available for:	LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; Light J; Colorchief
Projection:	Flicker-free
Beam angle (1/2 peak):	17°
Beam angle (1/10 peak):	33°
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Dimensions:	Length: 110 cm Depth: 6.5 cm Height: 10 cm
Weight:	2.85 kg
Noise classification:	Class 0 (no noise at all)
Photobiological safety:	Risk Group 0
Cable construction:	3 x 0.75 mm <sup>2</sup> H05RN-F
Diameter mounting holes:	1 x Ø20mm; 1 x Ø11mm; 1 x Ø8mm; 2 x Ø6mm
Material:	Metal
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

**ROADINGER Flightcase 12x LED Bar with wheels**

Maximum load:	150 kg
Removable covers:	1 pc/pcs
Aluminum profile frames:	20 mm
Case handle:	6 pc/pcs
Lock:	Butterfly lock: 12 pc/pcs
Transport aid:	4 x castors with 2 locking brakes
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Compartment dimensions:	113 cm x 8.5 cm x 9 cm
Inside dimensions:	113 cm x 40.5 cm x 16 cm
Dimensions:	Width: 119 cm Depth: 44 cm Height: 84 cm
Weight:	34.70 kg

**Scope of delivery:**

- 1 x light effect
- 1 x power cord
- 2 x mounting bracket
- 2 x knurled screw
- 2 x washer
- 1 x user manual