

EUROLITE Set 4x AKKU Bar-6 Glow QCL + Case with charging function

Art. No.: 20000547

4x tiltable battery-powered LED bar and mood light with 4in1 LEDs including PRO flightcase

GTIN:



List price: 1783.81 €

incl. 19% VAT.

Features:

Logistic

EUROLITE AKKU Bar-6 Glow QCL Flex QuickDMX

Tiltable battery-powered LED bar and mood light with 4in1 LEDs and QuickDMX

- 100° tiltable bar with 6 high-power 8 W RGBW LEDs (4in1) and removable frost filter
- Mood light with milky front screen provides a pleasantly soft light with 30 SMD RGBW LEDs (4in1)
- Integrated QuickDMX transceiver for wireless DMX control
- Cordless, flexible and versatile
- Battery operation up to 13h depending on program used
- Integrated automatic charging of the battery and status indicator
- 30 powerful LEDs 0,25 W SMD 5050 4in1 QCL RGBW (homogenous color mix)
- 6 powerful LEDs 8 W SMD 9080 4in1 QCL RGBW (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; Dimmer speed (step response) adjustable
- Strobe effect
- Integrated show programs
- Direct color selection for 30 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; QuickDMX; IR remote control; sound to light via microphone; master/slave function
- Preprogrammed in LED PC-Control 512; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Colorchief
- Flicker-free
- With a beam angle of 15°
- Multicolor LCD display
- With a KENSINGTON LOCK theft protection

- For application areas such as: Wedding/gala/events; mobile use; mobile djs / entertainer; small rental
- Silent operation
- Application possibility: Standing; suspended; on stand

Package contents

- 1 x device, 1 x user manual, 1 x power cord, 1 x frost filter, 1 x remote control, 1 x battery, 1 x omega bracket, 4 x knurled screw, 4 x washer, 1 x declaration of conformity

ROADINGER Flightcase 4x AKKU BAR-6 Glow QCL Flex QuickDMX with charging function

Trunk case with castors

- With accessory compartment
- With 4 device compartments
- High-quality workmanship with plywood multi-layer glued 9 mm, black, laminated
- Interior with foam padding
- Aluminum profile frames 25mm with rounded edges
- 4 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- 4 x castors with 2 locking brakes
- 4 x built-in stacking trays in the cover

Package contents

- 1 x case, 1 x user manual, 1 x power cord

Technical specifications:

Weight: 27,55 kg

EUROLITE AKKU Bar-6 Glow QCL Flex QuickDMX

Power supply:	100-240 V AC, 50/60 Hz
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Battery/battery pack Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Battery pack type:	1 x lithium ion 11,1 V, 10400 mAh, 115,44 Wh
Battery pack:	Battery operation up to 13h depending on program used Recharging time 4h
Lamp type:	LED lamp
LED type:	30 x 0,25 W SMD 5050 4in1 QCL RGBW (homogenous color mix) 6 x 8 W SMD 9080 4in1 QCL RGBW (homogenous color mix)
DMX channels:	3; 7; 8; 9; 11
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; QuickDMX; IR remote control; sound to light via microphone; master/slave function

Preprogrammed in:	LED PC-Control 512; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Colorchief
Projection:	Flicker-free
Carrier frequency:	2,4 GHz
Beam angle:	15°
Beam angle (1/2 peak):	15°
Beam angle (1/10 peak):	30°
Housing color:	Black
Display type:	Multicolor LCD display
Theft protection:	KENSINGTON LOCK
Dimensions:	Length: 41,1 cm Depth: 9,5 cm Height: 10,5 cm
Weight:	2,80 kg
Noise classification:	Class 0 (no noise at all)
Remote control	
Battery:	1 x button cell 3.0 V CR2032 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 4x AKKU BAR-6 Glow QCL Flex QuickDMX with charging function

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	Max. 1150 W
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	P-Con (gray), mounting version
Device fuse:	5 x 20 mm, T 5 A fuse replaceable
Aluminum profile frames:	25 mm
Case handle:	4 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Transport aid:	4 x castors with 2 locking brakes 4 x built-in stacking trays in the cover
Material:	Plywood multi-layer glued, 9 mm
Color:	Black, laminated
Device compartment:	10,5 cm x 45 cm x 17 cm
Accessory compartment:	11 cm x 45 cm x 17 cm
Inside dimensions:	69,5 cm x 45 cm x 17 cm
Dimensions:	Width: 73,5 cm Depth: 49,5 cm Height: 35 cm
Weight:	16,35 kg