

EUROLITE Set 4x AKKU Bar-6 Glow QCL + Case with charging function

4x tiltable battery-powered LED bar and mood light with 4in1 LEDs including PRO flightcase

Art. No.: 2000547

GTIN: 4026397653007



Features:

- 100° tiltable bar with 6 high-power 8 W RGBW LEDs (4in1) and removable frost filter
 - Mood light with milky front screen provides a pleasantly soft light with 30 SMD RGBW LEDs (4in1)
 - Integrated QuickDMX transceiver for wireless DMX control
 - Cordless, flexible and versatile
 - Battery operation up to 13h depending on program used
 - Integrated automatic charging of the battery and status indicator
 - 30 LEDs 0.25 W SMD 5050 4in1 RGBW (homogenous color mix)
 - 6 LEDs 8 W SMD 9080 4in1 RGBW (homogenous color mix)
 - Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; Dimmer speed (step response) adjustable
 - Atmospheric effect
 - Integrated show programs
 - Direct color selection for 30 preset colors
 - The device is cooled by passive convection cooling
 - Control via stand-alone; DMX; QuickDMX; IR remote control; sound to light via microphone; master/slave function
 - Flicker-free
 - With a beam angle of 15°
 - Multicolor LCD display
 - With a KENSINGTON LOCK theft protection
 - For application areas such as: Clubs/dancing school; decoration; wedding/gala/events; mobile djs / entertainer; party room; restaurants, bars and hotels; advertisement/Shop window
 - Silent operation
 - Application possibility: Standing; suspended; on stand
- knurled screw**

Logistic

EAN / GTIN: 4026397653007

Weight: 31,00 kg

Length: 0.60 m

Width: 0.80 m

Height: 1.00 m

Bulky product

- M6 thread
- <p>ROADINGER Flightcase 4x AKKU BAR-6 Glow QCL Flex QuickDMX with charging function
- <h2 class="featureSatz">Trunk case with castors</h2>With accessory compartment
- With 4 device compartments
- High-quality workmanship with plywood multi-layer glued 9 mm, black, laminated
- Interior with foam padding
- Aluminum profile frames 25mm with rounded edges
- 4 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks with shut-off function
- 4 x castors with 2 locking brakes
- 4 x built-in stacking trays in the cover

Technical specifications:

Weight: 27.55 kg

EUROLITE AKKU Bar-6 Glow QCL Flex QuickDMX

Power supply:	100-240 V AC, 50/60 Hz
Protection class:	Protection class I
Power connection:	Battery/battery pack Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Battery pack type:	1 x lithium ion 11.1 V, 10400 mAh, 115.44 Wh
Battery pack:	Battery operation up to 13h depending on program used Recharging time 4h
Lamp type:	LED lamp
LED type:	30 x 0.25 W SMD 5050 4in1 RGBW (homogenous color mix) 6 x 8 W SMD 9080 4in1 RGBW (homogenous color mix)
DMX channels:	3; 7; 8; 9; 11
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; QuickDMX; IR remote control; sound to light via microphone; master/slave function
Fixtures available for:	LED PC-Control 512; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Colorchief
Projection:	Flicker-free
Carrier frequency:	2.4 GHz
Beam angle (1/2 peak):	15°
Beam angle (1/10 peak):	30°
Housing color:	Black
Display type:	Multicolor LCD display
Material:	Plastic; metal

Theft protection:	KENSINGTON LOCK
Dimensions:	Length: 41.1 cm Depth: 9.5 cm Height: 10.5 cm
Weight:	2.80 kg
Noise classification:	Class 0 (no noise at all)
Cable construction:	3 x 1.0 mm ² H05VV-F
Cable length:	Approx. 1.2 m
Diameter mounting holes:	2 x Ø4mm
Material:	Plastic, 2 mm
Color:	Semi-transparent
Dimensions:	Length: 33.5 cm Width: 3.9 cm
Battery:	1 x button cell 3.0 V CR2032 lithium manganese built-in
Diameter mounting holes:	1 x Ø11mm; 2 x Ø6mm
Material:	Metal, 2 mm
Color:	Black
Dimensions:	Length: 11.7 cm Width: 2.5 cm Height: 2.7 cm
Weight:	0.048 kg
Material:	Metal
Color:	Black
Thread:	M6 thread x 11 mm
Diameter mounting holes:	Ø10mm
Material:	Metal, 0.5 mm
Dimensions:	Diameter: Ø 1.2 cm
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 4x AKKU BAR-6 Glow QCL Flex QuickDMX with charging function

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	Max. 1150 W
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	P-Con (gray), mounting version
Device fuse:	5 x 20 mm, T 5 A fuse replaceable
Aluminum profile frames:	25 mm
Case handle:	4 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs with shut-off function
Transport aid:	4 x castors with 2 locking brakes 4 x built-in stacking trays in the cover
Material:	Plywood multi-layer glued, 9 mm

Color:	Black, laminated
Device compartment:	10.5 cm x 45 cm x 17 cm
Accessory compartment:	11 cm x 45 cm x 17 cm
Inside dimensions:	69.5 cm x 45 cm x 17 cm
Dimensions:	Width: 73.5 cm Depth: 49.5 cm Height: 37.5 cm
Weight:	16.60 kg
Cable construction:	3 x 1.0 mm ² H05VV-F
Cable length:	1.2 m detachable

Scope of delivery:

4 x EUROLITE AKKU Bar-6 Glow QCL Flex QuickDMX

- 1 x device
- 1 x power cord
- 1 x frost filter
- 1 x remote control
- 1 x battery
- 1 x omega bracket
- 4 x knurled screw
- 4 x washer
- 1 x user manual
- 1 x declaration of conformity

1 x ROADINGER Flightcase 4x AKKU BAR-6 Glow QCL Flex QuickDMX with charging function

- 1 x case
- 1 x power cord
- 4 x castors
- 16 x screw
- 1 x key
- 1 x user manual