



Features:

- Flexible LED strip for decorative lighting
- Can be cut into segments of variable size
- Self-adhesive rear side
- Supplied on a plastic reel
- 150 LEDs SMD 5050 3in1 R/G/B (homogenous color mix)
- Control via system controller
- Suitable for outdoor use
- For application areas such as: Trade fair and shop fitting; clubs/dancing school; installation; restaurants, bars and hotels
- Silent operation
- <p>EUROLITE LED Strip RGB RF Controller
- <h2 class="featureSatz">3-channel LED controller with wireless remote control for RGB LED strips 12-24V</h2>For controlling RGB LED strips 12-24 V
- Color selection via touch-sensitive color wheel
- RJ45 jacks for serial connection
- Dimmer electronic; program speed adjustable
- 10 integrated show programs
- Control via wireless remote control
- Operating range up to 20m
- <p>EUROLITE LED Strip Wall Panel for RGB RF Controller
- <h2 class="featureSatz">Wireless wall dimmer for RGB LED strips</h2>For controlling RGB LED strips 12-24 V
- Color wheel selection
- Terminals for connecting the power supply (100-240 V)
- Program speed adjustable; Dimmer electronic
- 10 integrated show programs

Logistic

- Operating range up to 20m
- Flush mounting
- Finery housing (optional)
- <p>EUROLITE Electr. LED Transformer, 24V, 2A
- <h2 class="featureSatz">Stabilized LED power supply unit DC 24 V, 2 A</h2>Especially for LED installations
- Input voltage AC 100-240 V

Technical specifications:

Weight: 0.74 kg

EUROLITE LED IP Strip 150 5m RGB 24V

Power supply:	24V DC
Power consumption:	30 W
IP classification:	IP65
Protection class:	Protection class III
Power connection:	Fixed supply cord with open wires
Cable length:	Approx. 0.15 m
Lamp type:	LED lamp
LED type:	150 x SMD 5050 3in1 R/G/B (homogenous color mix)
Control:	System controller
Standing/fixation:	Self adhesive
Lamps/meter:	30 pc/pcs
Power/meter:	7.2 W
Lamps/tube:	150 pc/pcs
Lamp distance:	33 mm
Cutting mark:	17 cm
Luminous flux (Lumen) per meter:	300 lm/m
Housing color:	White
Dimensions:	Length: 500 cm Width: 1 cm Height: 0.2 cm
Weight:	0.18 kg
Noise classification:	Class 0 (no noise at all)
Energy efficiency class (A - G):	G

EUROLITE LED Strip RGB RF Controller

Power supply:	12/24V DC
Power consumption:	Max. 360 W 12 V DC Max. 720 W 24 V DC 120 W 12 V DC per channel 240 W 24 V DC per channel

Output current:	Max. 3 x 10 A per channel
Power connection:	Mains input via screw terminal
Power output:	4 x screw terminal
Battery:	Micro (AAA) (not included)
Control:	Wireless remote control
Range:	Range up to 20m
Carrier frequency:	433.920 MHz
Connections:	Signal via 2 x RJ-45 (F) mounting version Screw terminal
Dimensions:	Length: 9 cm Width: 9 cm Height: 2.4 cm
Weight:	0.29 kg
Dimensions:	Height: 2.2 cm

EUROLITE LED Strip Wall Panel for RGB RF Controller

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	Max. 1 W
Power connection:	Mains input via screw terminal
Range:	Range up to 20m
Carrier frequency:	433.920 MHz
Housing design:	Flush mounting Finery housing (optional)
Dimensions:	Length: 8.6 cm Width: 8.6 cm Depth: 3.4 cm
Weight:	0.13 kg

EUROLITE Electr. LED Transformer, 24V, 2A

Power supply:	100-240 V AC, 50/60 Hz
Protection class:	Protection class II
Power connection:	Mains input via screw terminal
Power output:	Screw terminal
Housing color:	White matte
Controls:	Overload; short-circuit; overheat
Output:	24 V DC, stabilized; 2 A;
Material:	Plastic
Dimensions:	Length: 18 cm Width: 4 cm Height: 2.5 cm
Weight:	0.14 kg

Scope of delivery:

1 x EUROLITE LED IP Strip 150 5m RGB 24V

- 1 x illuminant
- 1 x user manual

1 x EUROLITE LED Strip RGB RF Controller

- 1 x controller
- 1 x transmitter
- 1 x user manual
- 1 x declaration of conformity

1 x EUROLITE LED Strip Wall Panel for RGB RF Controller

- 1 x remote control
- 1 x user manual
- 1 x declaration of conformity

1 x EUROLITE Electr. LED Transformer, 24V, 2A

- 1 x external mains adapter