

## OMNITRONIC Set WAMS-65BT + Bodypack transmitter incl. headset + Battery No.: 20000567

Portable 6.5" PA with matching battery incl. pocket transmitter with headset microphone

GTIN: 4026397607208



### Features:

- Portable all-in-one PA system with 40 watts output power
- 4-channel mixer
- 2-way bass-reflex system
- SD card slot and USB port
- 1 microphone input (XLR) with adjustable reverb effect
- UHF receiver unit and matching wireless microphone
- Power-efficient and battery-saving class D amplifier
- Tone control and master control
- Integrated automatic charging of the battery
- The device is cooled by passive convection cooling
- UHF 863 - 865 MHz License-free and approved in Europe
- Black metal grille
- Rugged carrying handle
- For application areas such as: Theater; mobile use; wedding/gala/events; product presentations and lectures

#### **battery pack**

- Battery pack must be ordered separately
- Cordless, flexible and versatile
- Battery operation up to 4h

#### **audio player**

- Control via Bluetooth; IR remote control
- Bluetooth: operating range up to 10m
- 2.4 GHz license-free worldwide
- 4 digit 7-segment LED display

#### **microphone**

- Polar pattern: Cardioid

### Logistic

EAN / GTIN: 4026397607208

Weight: 6,50 kg

Length: 0.46 m

Width: 0.36 m

Height: 0.27 m

- Operating range up to 30m  
**remote control**
- Operating range up to 10m
- <p>OMNITRONIC WAMS-65BT Bodypack Transmitter incl. Headset
- <h2 class="featureSatz">Bodypack transmitter with headset microphone</h2>LED indicator for battery capacity
- With gooseneck-microphone boom for exact positioning of the microphone capsule
- One-sided cable run
- Operating range up to 50m with line-of-sight

## Technical specifications:

---

Weight: 5.34 kg

---

### OMNITRONIC WAMS-65BT Wireless PA System

Power supply:	100-240 V AC, 50/60 Hz Or 12V DC
Power consumption:	60 W
Protection class:	Protection class I
Output power:	40 W RMS
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided) Battery/battery pack (not included)
Frequency range:	62 - 18000 Hz
THD:	<0.5 % at 1 kHz
Cooling:	Passive convection cooling
Frequency band:	UHF 863 - 865 MHz
Carrier frequency:	865 MHz
Frequency stability:	± 0.005 %
Frequency selection:	Fixed frequencies
Housing color:	Black
Attachment system:	Flange: Ø 35mm
Circuitry:	Class D
Control elements:	Echo effect control, audio player
Status LED:	Power, peak, ON AIR, signal, charge status indicator
Connections:	Input: microphone via 1 x 3-pin XLR Input: line via 1 x stereo RCA Output: line via 1 x 6.3 mm plug (unbal.)
Channels:	Microphone channel: 1 x mono via XLR, channel control via rotary dial Input channel: 1 x stereo via RCA, channel control via rotary dial Input channel: 1 x stereo via audio player, channel control via rotary dial Input channel: 1 x mono via radio, channel control via rotary dial

Master output: 1 x mono, channel control via rotary dial, tone control EQ

Speaker:	1 x woofer 6.5" 1 x tweeter 1"
Type of speaker:	Compact cabinet speaker; wireless PA system
Type of construction:	Vented
Carrying handle:	1 pc/pcs
Material:	ABS Acrylonitrile butadiene styrene
Color:	Black
Dimensions:	Width: 23.5 cm Depth: 22 cm Height: 35 cm
Weight:	4.15 kg
Power supply:	3V DC
Power connection:	Battery/battery pack
Capsule type:	Dynamic
Polar pattern:	Cardioid
Battery:	2 x Mignon (AA) (not included)
Range:	Range up to 30m
RF power output:	10 mW
Modulation:	FM
Switch:	On/off/mute switch
Material:	Plastic
Dimensions:	Length: 26 cm Diameter: Ø 4 cm
Weight:	0.115 kg
Control:	Bluetooth; IR remote control
Bluetooth device name:	Omnitronic
Audio player:	USB + SD + Bluetooth
Range:	Bluetooth: range up to 10m
Frequency band:	2.4 GHz
Display type:	4 digit 7-segment LED display
Music format:	MP3, WAV
Available storage media:	USB devices/SD cards max. 32GB (FAT 32)
Power supply:	3V DC
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Range:	Range up to 10m
Battery pack type:	1 x lead 12 V, 2900 mAh,
Battery pack:	Battery operation up to 4h Recharging time 4h

#### **OMNITRONIC WAMS-65BT Bodypack Transmitter incl. Headset**

Type:	Bodypack with microphone
Battery:	2 x Mignon (AA) (not included)

Frequency range:	40 - 18000 Hz
S/N ratio:	>105 dB
THD:	<0.5 % at 1 kHz
Range:	Range up to 50m with line-of-sight
Carrier frequency:	865 MHz
RF power output:	10 mW
Modulation:	F3F
Frequency selection:	Fixed frequencies
Connections:	1 x 3.5 mm jack (mono) mounting version screwable
Material:	Plastic
Dimensions:	Width: 6.4 cm Depth: 3.6 cm Height: 10 cm
Weight:	0.09 kg
Capsule type:	Condenser
Color:	Black
Weight:	0.023 kg

#### **Akku 12V/2900mAh WAMS-05 / WAMS-65**

Weight:	1.094 kg
---------	----------

#### **Scope of delivery:**

##### **1 x OMNITRONIC WAMS-65BT Wireless PA System**

- 1 x device
- 1 x power cord
- 1 x microphone
- 1 x remote control
- 1 x user manual
- 1 x declaration of conformity

##### **1 x OMNITRONIC WAMS-65BT Bodypack Transmitter incl. Headset**

- 1 x transmitter
- 1 x microphone
- 1 x declaration of conformity
- 1 x user manual

##### **1 x Akku 12V/2900mAh WAMS-05 / WAMS-65**

- 1 x device