

EUROLITE Set 4x LED CBB-4 COB RGB Bar + Case

4x LED light effect bar with RGB color mixing and IR remote control incl. PRO flightcase

Art. No.: 20000575

GTIN:



The article is no longer in our assortment.

Features:

EUROLITE LED CBB-4 COB RGB Bar

LED light effect bar with RGB color mixing, incl. IR remote control

- 4 powerful LEDs 23 W COB (chip-on-board) 3in1 TCL RGB (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect
- Integrated show programs
- Direct color selection for 19 preset colors
- The device is cooled by low-noise cooling fan
- Control via stand-alone; DMX; IR remote control; sound to light via microphone; master/slave function
- Preprogrammed in Light´J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
- Flicker-free
- With a beam angle of 39°
- With mounting bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; stage; theater; mobile djs / entertainer
- Application possibility: Standing; suspended; on stand

Package contents

- 1 x spotlight, 1 x power cord, 1 x remote control, 1 x battery, 1 x user manual

Logistic

ROADINGER Flightcase 4x LED CBB-4

Trunk case, PRO version

- With accessory compartment
- With 4 device compartments
- High-quality workmanship with birch multiplex 7 mm, black, laminated
- Interior with foam padding
- Aluminum profile frames 25mm with rounded edges
- Hinged, chromium plated case handle
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight:	17,44 kg
---------	----------

EUROLITE LED CBB-4 COB RGB Bar

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	70 W
IP classification:	IP20
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Fuse:	T 1 A fuse replaceable
Lamp type:	LED lamp
LED type:	4 x 23 W COB (chip-on-board) 3in1 TCL RGB (homogenous color mix)
Flash rate:	0,3 - 23 Hz
DMX channels:	3; 5; 12; 15; 19
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	1 x low-noise cooling fan
Control:	Stand-alone; DMX; IR remote control; sound to light via microphone; master/slave function
Preprogrammed in:	Light´J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
Projection:	Flicker-free
Beam angle:	39°
Beam angle (1/2 peak):	39°
Beam angle (1/10 peak):	70°
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Dimensions:	Length: 46 cm

	Depth: 16 cm Height: 16 cm
Weight:	3,97 kg
Noise classification:	Class 2 (slight noise)
Mounting bracket	
Diameter mounting holes:	3 x Ø11mm; 4 x Ø8mm
Material:	Metal, 2,5 mm
Power cord	
Cable construction:	3 x 0,75 mm² H05VV-F
Cable length:	Approx. 1,1 m
Remote control	
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 4x LED CBB-4

Maximum load:	25 kg
Aluminum profile frames:	25 mm
Case handle:	1 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm; birch multiplex
Color:	Black, laminated; dark brown, laminated
Device compartment:	46,5 cm x 11,5 cm x 17 cm
Accessory compartment:	48 cm x 8 cm x 17 cm
Inside dimensions:	54 cm x 48 cm x 17 cm
Dimensions:	Width: 68 cm Depth: 53 cm Height: 27 cm
Weight:	9,55 kg