



Features:

EUROLITE LED TMH-X10 Moving-Head Beam

Beam spotlight with 150 W LED, color wheel, gobos and rotating 8-facet prism

- Equipped with a white 150 W COB LED
- Lightbeam with 4° radiation angle
- Positioning within 540° PAN and 280° TILT
- Exact positioning via 16 bit PAN/TILT movement resolution
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Macros
- Rotating 8-facet prism
- The prism rotates in both directions and at different speeds
- Frost-filter
- Strobe effect with variable speed
- Internal programs
- Dimmer
- Motorized focus
- Control board with LC display and four operating buttons for adjusting the DMX-starting address, PAN/TILT reverse, reset
- Switch-mode power supply for operation between 100 and 240 volts
- P-Con terminals for power linking up to 8 units
- 1 LED 150 W COB (chip-on-board) color wheel
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Gobo wheel with static gobos; prism 8-fold; frost filter; focus motor-driven
- Gobo effect
- Color wheel with 8 dichroic filters plus open
rainbow effect with adjustable speed in both directions

Logistic

- Gobo wheel with static gobos, 8 gobos and open
shake effect
- The device is cooled by cooling fan
- Control via stand-alone; sound to light via microphone
- Fixtures available for Light´J; LED PC-Control 512; Light Captain
- Flicker-free
- With a beam angle of 4°

ROADINGER Flightcase 4x LED TMH-X10

Trunk case with castors, PRO version

- With 4 device compartment
- With accessory compartment
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 25mm with rounded edges
- 4 hinged, chromium plated case handles
- 2 high-quality butterfly locks
- 4 x castors with 2 locking brakes
- Branded hardware
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight:	79.20 kg
---------	----------

EUROLITE LED TMH-X10 Moving-Head Beam

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	175 W
IP classification:	IP20
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x P-Con (gray), mounting version
Lamp type:	LED lamp
LED type:	1 x 150 W COB (chip-on-board) color wheel
Max. TILT movement:	280° exact positioning (16 bit resolution) auto position correction (feedback)
Max. PAN movement:	540° exact positioning (16 bit resolution) auto position correction (feedback)
Flash rate:	0 - 20 Hz
Equipment:	Gobo wheel with static gobos; prism 8-fold; frost filter; focus motor-driven
Color generation:	Color wheel with 8 dichroic filters plus open Rainbow effect with adjustable speed in both directions
Gobos:	Gobo wheel with static gobos, 8 gobos and open Shake effect
DMX channels:	15
DMX input:	3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Cooling fan

Control:	Stand-alone; sound to light via microphone
Fixtures available for:	Light J; LED PC-Control 512; Light Captain
Projection:	Flicker-free
Beam angle (1/2 peak):	4°
Illuminance in Lux (lx):	Cold white (CW) 6m: 21752 lx
Housing color:	Black
Dimensions:	Width: 23.5 cm Depth: 32.5 cm Height: 40 cm
Weight:	11.10 kg
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 4x LED TMH-X10

Maximum load:	100 kg
Aluminum profile frames:	25 mm
Case handle:	4 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Transport aid:	4 x castors with 2 locking brakes
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm; birch multiplex
Color:	Dark brown, laminated
Device compartment:	51 cm x 21 cm x 41 cm
Middle compartment:	10.5 cm x 63 cm x 46.5 cm
Inside dimensions:	112.5 cm x 63 cm x 46.5 cm
Dimensions:	Width: 120 cm Depth: 74 cm Height: 67 cm
Weight:	34.80 kg

Scope of delivery: