

EUROLITE Set 4x LED SLS-6 TCL Spot + Case TDV-1

4x flat spotlight with 6 x 8 W 3in1 LED with RGB including case

Art. No.: 2000632

GTIN: 4026397663587



Features:

- Slim design for space-saving applications
- DMX and power terminals intelligently designed for easy wiring
- 6 LEDs 8 W high-power 3in1 TCL RGB (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect
- 2 integrated show programs
- Direct color selection for 16 preset colors
- The device is cooled by cooling fan
- Control via stand-alone; DMX; sound to light via microphone; master/slave function
- Fixtures available for EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; LED PC-Control 512; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
- Flicker-free
- With a beam angle of 16°
- With mounting bracket
- 4 digit 7-segment LED display
- Rubber feet
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; decoration; mobile djs / entertainer; party room; restaurants, bars and hotels
- Application possibility: Standing; suspended; on stand
- <p>ROADINGER TDV-1 Universal Case Pick
- <h2 class="featureSatz">Universal case with flexible foam dividers</h2>With dividers
- High-quality workmanship with plastic 3 mm, black, imprinted
- Interior with foam padding
- Aluminum profile frames 12mm with rounded edges

Logistic

EAN / GTIN: 4026397663587

Weight: 10,00 kg

Length: 0.82 m

Width: 0.41 m

Height: 0.52 m

- Rugged carrying handle
- 3 chrome tip-over locks
- 2 high-quality spring locks with shut-off function
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight: 8.09 kg

EUROLITE LED SLS-6 TCL Spot

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	15 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug included
Power output:	1 x IEC connector (F) mounting version
Fuse:	5 x 20 mm, T 0.5 A fuse replaceable
Lamp type:	LED lamp
LED type:	6 x 8 W high-power 3in1 TCL RGB (homogenous color mix)
Flash rate:	0.5 - 23 Hz
DMX channels:	2; 3; 4; 5; 7
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	1 x cooling fan
Control:	Stand-alone; DMX; sound to light via microphone; master/slave function
Fixtures available for:	EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; LED PC-Control 512; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
Projection:	Flicker-free
Beam angle:	16°
Beam angle (1/2 peak):	16°
Beam angle (1/10 peak):	30°
Housing color:	Black matte
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Transport aid:	Rubber feet
Material:	Plastic; ABS Acrylonitrile butadiene styrene
Dimensions:	Width: 22 cm Depth: 11 cm Height: 21 cm

Weight:	1.16 kg
Noise classification:	Class 2 (slight noise)
Photobiological safety:	Risk Group 0
Cable construction:	3 x 0.75 mm ² H05VV-F
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER TDV-1 Universal Case Pick

Maximum load:	25 kg
Aluminum profile frames:	12 mm
Carrying handle:	1 pc/pcs
Stop hinge:	3 pc/pcs
Lock:	Spring lock: 2 pc/pcs with shut-off function
Material:	Plastic, 3 mm
Color:	Black, imprinted
Inside dimensions:	52 cm x 28.5 cm x 20 cm
Dimensions:	Width: 54 cm Depth: 31 cm Height: 26 cm
Weight:	3.45 kg

Scope of delivery:

4 x EUROLITE LED SLS-6 TCL Spot

1 x spotlight
1 x power cord
1 x user manual

1 x ROADINGER TDV-1 Universal Case Pick

1 x case