

EUROLITE Set 4x LED TL-4 Trusslight + Soft Bag

4x variable truss light and uplight with bright 4 x 8 W RGB+UV LED incl. soft bag

Art. No.: 20000636

GTIN:







List price: 565.25 €

incl. 19% VAT.

Features: Logistic

EUROLITE LED TL-4 QCL RGB+UV Trusslight

Variable truss light and uplight with bright 4 x 8 W RGB+UV LED

- Compact and bright
- Perfect for ALUTRUSS 4 point system QUADLOCK
- Folding foot adjustable in 5 steps for flexible placement
- 4 powerful LEDs 8 W high-power 4in1 QCL RGB/UV (homogenous color mix)
- Color change adjustable; Dimmer electronic; color blend stepless
- Strobe effect
- Integrated show programs
- Direct color selection for 18 preset colors
- The device is cooled by passive convection cooling
- Control via DMX; sound to light via microphone; IR remote control; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); stand-alone
- Preprogrammed in LED PC-Control 512; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
- With a beam angle of 13°
- Monochrome 4 digit 7-segment LED display
- Rubber fee
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; wedding/gala/events; stage; mobile djs / entertainer
- Silent operation
- Application possibility: Standing; suspended

Package contents

1 x spotlight, 1 x power cord, 1 x remote control, 1 x user manual

EUROLITE SB-4 Soft Bag L

Black soft bag for up to 4 devices, 320 x 320 x 200 mm

- Practical transport bag offers enough space for several lighting effects and accessories
- With dividers
- With 2 Outside pockets
- With 4 device compartments
- High-quality workmanship with nylon , black, water repellent
- Interior with foam padding
cover with foam padding
- 2 carrying straps

Package contents

- 1 x bag

Technical specifications:

Weight: 6,76 kg

EUROLITE LED TL-4 QCL RGB+UV Trusslight

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	15 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
LED type:	4 x 8 W high-power 4in1 QCL RGB/UV (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	3; 4; 8
DMX input:	1 x USB, type A
	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	DMX; sound to light via microphone; IR remote control; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); stand-alone
Preprogrammed in:	LED PC-Control 512; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
Beam angle:	13°
Beam angle (1/2 peak):	13°
Beam angle (1/10 peak):	30°
Housing color:	Black
Attachment system:	M10 thread
Display type:	Monochrome 4 digit 7-segment LED display
Transport aid:	Rubber feet

Dimensions:	Length: 15,5 cm
	Width: 14,5 cm
	Height: 13,0 cm
Weight:	1,56 kg
Noise classification:	Class 0 (no noise at all)
Photobiological safety:	Risk Group 0
Power cord	
Cable construction:	3 x 0,75 mm² H05VV-F
Cable length:	Approx. 1,1 m
Color:	Black
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE SB-4 Soft Bag L

Maximum load:	25 kg
Carrying strap:	2 pc/pcs
Material:	Nylon
Color:	Black, water repellent
Compartment dimensions:	15 cm x 15 cm x 20 cm
Inside dimensions:	31 cm x 34 cm x 20 cm
Dimensions:	Width: 32 cm
	Depth: 41 cm
	Height: 20 cm
Weight:	0,52 kg