

EUROLITE Set 6x LED TL-4 Trusslight + Case

6x variable truss light and uplight with bright 4 x 8 W RGB+UV LED incl. case

Art. No.: 20000637

GTIN:



List price: 831.81 €

incl. 19% VAT.

Features:

EUROLITE LED TL-4 QCL RGB+UV Trusslight

Variable truss light and uplight with bright 4 x 8 W RGB+UV LED

- Compact and bright
- Perfect for ALUTRUSS 4 point system QUADLOCK
- Folding foot adjustable in 5 steps for flexible placement
- 4 powerful LEDs 8 W high-power 4in1 QCL RGB/UV (homogenous color mix)
- Color change adjustable; Dimmer electronic; color blend stepless
- Strobe effect
- Integrated show programs
- Direct color selection for 18 preset colors
- The device is cooled by passive convection cooling
- Control via DMX; sound to light via microphone; IR remote control; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); stand-alone
- Preprogrammed in LED PC-Control 512; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
- With a beam angle of 13°
- Monochrome 4 digit 7-segment LED display
- Rubber feet
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; wedding/gala/events; stage; mobile djs / entertainer
- Silent operation
- Application possibility: Standing; suspended

Package contents

- 1 x spotlight, 1 x power cord, 1 x remote control, 1 x user manual

Logistic

ROADINGER Universal Case Pick TDV-1

Universal case with flexible foam dividers

- With dividers
- High-quality workmanship with plastic 3 mm, black, imprinted
- Interior with foam padding
- Aluminum profile frames 12mm with rounded edges
- Rugged carrying handle
- 3 chrome tip-over locks
- 2 high-quality spring locks with shut-off function
- For further information about this product, please refer to the Data Sheet under "Downloads"

Package contents

- 1 x case

Technical specifications:

Weight:	12,81 kg
---------	----------

EUROLITE LED TL-4 QCL RGB+UV Trusslight

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	15 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
LED type:	4 x 8 W high-power 4in1 QCL RGB/UV (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	3; 4; 8
DMX input:	1 x USB, type A 1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	DMX; sound to light via microphone; IR remote control; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); stand-alone
Preprogrammed in:	LED PC-Control 512; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
Beam angle:	13°
Beam angle (1/2 peak):	13°
Beam angle (1/10 peak):	30°
Housing color:	Black
Attachment system:	M10 thread
Display type:	Monochrome 4 digit 7-segment LED display
Transport aid:	Rubber feet

Dimensions:	Length: 15,5 cm Width: 14,5 cm Height: 13,0 cm
Weight:	1,56 kg
Noise classification:	Class 0 (no noise at all)
Photobiological safety:	Risk Group 0
Power cord	
Cable construction:	3 x 0,75 mm² H05VV-F
Cable length:	Approx. 1,1 m
Color:	Black
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Universal Case Pick TDV-1

Maximum load:	25 kg
Aluminum profile frames:	12 mm
Carrying handle:	1 pc/pcs
Stop hinge:	3 pc/pcs
Lock:	Spring lock: 2 pc/pcs with shut-off function
Material:	Plastic, 3 mm
Color:	Black, imprinted
Inside dimensions:	52 cm x 28,5 cm x 20 cm
Dimensions:	Width: 54 cm Depth: 31 cm Height: 26 cm
Weight:	3,45 kg