

OMNITRONIC Set TRM-202MK3 + Case

2-channel rotary mixer with 3-band frequency isolator for DJs including PRO flightcase

Art. No.: 2000666

GTIN: 4026397591743



Features:

- Classic rotary mixer with 2 input channels and integrated 3-band frequency isolator for DJs
- Gain control, 2-way equalizer (highs/low) and phono/line switching per channel
- Dedicated boost and kill cut
- Kill cut feature allows DJs to completely remove low, mid and high frequencies for amazing mixing
- Classic ALPS potentiometers (Blue Velvet RK27)
- High-grade components ensure long life and excellent sound quality
- DJ microphone input with separate level control
- Prefader listening to input channels and the master output via adjustable headphones output, with cue mix/split function
- 12-digit stereo LED level meter and master level control
- Booth output with separate level control
- Outputs: master and booth (XLR/RCA L/R), record (stereo RCA)
- Desktop console housing
- For application areas such as: Clubs/dancing school; mobile use; mobile djs / entertainer; homerecording and studios
- <p>ROADINGER Flightcase TRM-202 MK3
- <h2 class="featureSatz">Hood case, PRO version</h2>High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 25mm with rounded edges
- Rugged carrying handle
- 2 high-quality butterfly locks
- Branded hardware
- Made in Europe

Logistic

EAN / GTIN: 4026397591743

Weight: 6,50 kg

Length: 0.61 m

Width: 0.31 m

Height: 0.40 m

Technical specifications:

Weight: 5.88 kg

OMNITRONIC TRM-202MK3 2-channel Rotary Mixer

| | |
|--------------------|---|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 6.5 W |
| Protection class: | Protection class I |
| Power connection: | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided) |
| Frequency range: | 20 - 20000 Hz microphone 20 - 20000 Hz line 40 - 18000 Hz phono |
| S/N ratio: | >77 dB phono >80 dB microphone >85 dB line |
| THD: | Line <0.03 % at 1 kHz Phono <0.1 % at 1 kHz |
| Gain: | Microphone 44 dB Line 20 dB Phono 60 dB to +75 dB |
| Isolators: | Master Gain: - ? bis +9 Low/mid 300 Hz, 18db/oct , Butterworth Mid/high 4000 Hz, 18db/oct , Butterworth |
| Housing color: | Black |
| Control elements: | Power switch, source selector, crossfader, cue mix split function, tone control |
| Status LED: | Power, master level meter, channel source, CUE, microphone |
| Connections: | Input: line via 2 x stereo RCA Input: line/phono via 2 x stereo RCA Input: microphone via 1 x 3-pin XLR Output: headphones via 1 x 6.3 mm jack socket (stereo) mounting version Output: rec. via 1 x stereo RCA Output: booth via 2 x 3-pin XLR Output: booth via 1 x stereo RCA Output: master via 2 x 3-pin XLR Output: master via 1 x stereo RCA |
| Channels: | Input channel: 2 x stereo with line-line/phono switch via RCA, channel control via rotary, 2-band tone control EQ, CUE switch, phono gain rotary, source selector Microphone channel: 1 x mono via XLR, channel control via rotary dial, ON AIR switch Booth output: 1 x stereo via XLR or RCA, channel control via rotary dial |

Master output: 1 x stereo via XLR or RCA,
channel control via rotary dial

Headphones output: 1 x stereo via jack, channel
control via rotary dial, cue mix split function

| | |
|-----------------|---|
| Max. level: | Output: +22 dBu |
| Material: | Metal |
| Housing design: | Desktop console housing |
| Dimensions: | Width: 19 cm Depth: 25 cm Height: 10.7 cm |
| Weight: | 2.68 kg |

ROADINGER Flightcase TRM-202 MK3

| | |
|--------------------------|---|
| Maximum load: | 25 kg |
| Aluminum profile frames: | 25 mm |
| Carrying handle: | 1 pc/pcs |
| Lock: | Butterfly lock: 2 pc/pcs |
| Use of brands: | Branded hardware |
| Material: | Birch multiplex, 7 mm |
| Color: | Dark brown, laminated |
| Dimensions: | Width: 24 cm Depth: 38 cm Height: 18 cm |
| Weight: | 3.20 kg |

Scope of delivery:

1 x device
1 x power cord
1 x user manual