

EUROLITE Set LED IP PAR 12x9W SCL Spot + 2x Diffuser Cover (15x60° and 40°) 20000673

Weather-proof spotlight with 12 7in1-LEDs and RGBA/CW/WW+UV color mixing incl. 2x frost filters

GTIN: 4026397362343



Features:

- 12 LEDs 9 W COB (chip-on-board) 7in1 RGB/CW/WW/A/UV (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect
- Direct color selection for 28 preset colors
- The device is cooled by passive convection cooling
- Control via DMX; IR remote control; stand-alone
- Flicker-free
- With a beam angle of 15°
- With double bracket
- LCD display
- Mains input and output for power linking up to 8 units
- Suitable for outdoor use IP65
- With pressure compensation membrane
- For application areas such as: Architecture; stage; clubs/dancing school; wedding/gala/events; theater; rental; video and photography
- Silent operation
- Application possibility: Standing; suspended; on stand

Logistic

EAN / GTIN: 4026397362343
Weight: 6,60 kg
Length: 0.41 m
Width: 0.31 m
Height: 0.28 m

Technical specifications:

Weight: 5.43 kg

EUROLITE LED IP PAR 12x9W SCL Spot

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	75 W
IP classification:	IP65
Protection class:	Protection class I
Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug
Power output:	IP T-Con (F) mounting version
Lamp type:	LED lamp
LED type:	12 x 9 W COB (chip-on-board) 7in1 RGB/CW/WW/A/UV (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	3; 5; 7; 9; 13
DMX input:	3-pin XLR (M) mounting version IP
DMX output:	3-pin XLR (F) mounting version IP
Cooling:	Passive convection cooling
Control:	DMX; IR remote control; stand-alone
Fixtures available for:	LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3
Projection:	Flicker-free
Beam angle (1/2 peak):	15°
Beam angle (1/10 peak):	29°
Housing color:	Black
Attachment system:	Double bracket
Display type:	LCD display
Material:	Aluminum casting
Dimensions:	Width: 28.5 cm Depth: 15.3 cm Height: 31.35 cm
Weight:	5.20 kg
Noise classification:	Class 0 (no noise at all)
Photobiological safety:	Risk Group 0
Diameter mounting holes:	3 x Ø11mm
Material:	Metal, 2.5 mm
Cable construction:	3 x 1.0 mm ² H05RN-F
Cable length:	Approx. 1.2 m
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE Diffuser Cover 15x60° for IP PAR-12

Dimensions:	Height: 0.7 cm
-------------	----------------

Diameter: Ø 22.20 cm

Weight: 0.11 kg

EUROLITE Diffuser Cover 40° for IP PAR-12

Dimensions: Height: 0.65 cm
Diameter: Ø 22.20 cm

Weight: 0.12 kg

Scope of delivery:

1 x EUROLITE LED IP PAR 12x9W SCL Spot

- 1 x device
- 1 x power cord
- 1 x remote control
- 1 x battery
- 1 x user manual

1 x EUROLITE Diffuser Cover 15x60° for IP PAR-12

- 1 x beamshaper

1 x EUROLITE Diffuser Cover 40° for IP PAR-12

- 1 x frost filter