

EUROLITE Set 4x Multiflood Pro IP RGBW Wash/Frost + Case

4x bright LED outdoor spot with wireless DMX receiver incl. PRO flightcase

Art. No.: 2000677

GTIN: 4026397360929



Features:

- Washlight and strobe
- Suitable for external use (IP65)
- With integrated wireless receiver for WDMX operation (Wireless Solution - made in Sweden)
- 36 high-power 15 W RGBW LEDs (4in1)
- 16° standard beam angle
- 2 frost filters (25° and 45°) for a softer light with larger beam angles, included in delivery
- Flicker-free projection
- Direct color selection for 20 preset colors
- Stepless RGBW color blend
- Dimmer speed (step response) adjustable
- Addressing and setting via control panel with LED screen and four operating buttons
- Swivel mounting bracket with locking possibility
- Hanging installation via quick-lock Omega holders
- Additional rubber feet protect the device when positioned on the ground
- IP T-Con terminals for power linking up to 8 units
- 36 LEDs 15 W high-power 4in1 RGBW (homogenous color mix)
- The device is cooled by cooling fan
- Control via W-DMX by wireless solution; sound to light via microphone; master/slave function; DMX; stand-alone
- With a beam angle of 16°
- Suitable for outdoor use IP65
- <p>ROADINGER Flightcase 4x Multiflood Pro
- <h2 class="featureSatz">Trunk case with castors, HIGHLINE version</h2>With 4 device compartments
- High-quality workmanship with birch multiplex 9.8 mm, black, laminated
- Interior with foam padding

Logistic

EAN / GTIN: 4026397360929

- Cover with foam padding
- Aluminum profile frames 30mm with rounded edges
- 4 hinged, chromium plated case handles
- 4 chrome tip-over locks
- 2 high-quality butterfly locks
- 4 x castors with 2 locking brakes
- Branded hardware
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight: 83.55 kg

EUROLITE Multiflood Pro IP RGBW Wash/Frost

| | |
|-------------------------|---|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 215 W |
| IP classification: | IP65 |
| Protection class: | Protection class I |
| Lamp type: | LED lamp |
| LED type: | 36 x 15 W high-power 4in1 RGBW (homogenous color mix) |
| Flash rate: | 0 - 20 Hz |
| DMX channels: | 4; 5; 8 |
| DMX input: | 1 x 3-pin XLR (M) mounting version IP |
| DMX output: | 1 x 3-pin XLR (F) mounting version IP |
| Cooling: | Cooling fan |
| Control: | W-DMX by wireless solution; sound to light via microphone; master/slave function; DMX; stand-alone |
| Fixtures available for: | Light J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain |
| Carrier frequency: | 2.4 GHz |
| Beam angle (1/2 peak): | 16° 25° 45° |
| Beam angle (1/10 peak): | 35° |
| Housing color: | Black |
| Dimensions: | Length: 16 cm Width: 49 cm Height: 32 cm |
| Weight: | 12.05 kg |
| Noise classification: | Class 3 (clearly perceptible sounds) |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |

ROADINGER Flightcase 4x Multiflood Pro

| | |
|--------------------------|--|
| Maximum load: | 100 kg |
| Aluminum profile frames: | 30 mm |
| Case handle: | 4 pc/pcs |
| Stop hinge: | 4 pc/pcs |
| Lock: | Butterfly lock: 2 pc/pcs |
| Transport aid: | 4 x castors with 2 locking brakes |
| Use of brands: | Branded hardware |
| Material: | Birch multiplex, 9.8 mm; birch multiplex |
| Color: | Black, laminated; dark brown, laminated |
| Device compartment: | 21.5 cm x 55.5 cm x 28 cm |
| Accessory compartment: | 11.5 cm x 53.5 cm x 28 cm |
| Inside dimensions: | 105.5 cm x 56 cm x 37 cm |
| Dimensions: | Width: 110 cm Depth: 61 cm Height: 53 cm |
| Weight: | 35.35 kg |

Scope of delivery:

- 1 x spotlight
- 1 x user manual
- 1 x declaration of conformity
- 1 x power cord
- 1 x XLR cable
- 1 x omega bracket
- 2 x frost filter
- 1 x plug (male)