

EUROLITE Set 4x LED 7C-12 Silent Slim Spot + Case

4x inaudible 7in1 PAR spotlight in a space-saving design including PRO flightcase

Art. No.: 2000682

GTIN: 4026397360981



Features:

- 12 LEDs 9 W high-power 7in1 RGB/CW/WW/A/UV (homogenous color mix)
- Flat version requires minimal space when mounting
- With a beam angle of 15°
- Silent operation
- Very high color rendering index (CRI)
- Flicker-free
- Control via DMX; stand-alone; IR remote control; master/slave function; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Color blend stepless; Dimmer electronic
- Strobe effect
- Direct color selection for 27 preset colors
- Integrated show programs
- With double bracket
- Mains input and output for power linking up to 8 units
- The device is cooled by passive convection cooling
- For application areas such as: Stage; clubs/dancing school; wedding/gala/events; mobile djs / entertainer; party room; restaurants, bars and hotels; theater; video and photography; advertisement/Shop window
- Application possibility: Standing; suspended; on stand
- <p>ROADINGER Flightcase 4x LED 4/7C-12 Silent Slim Spot
- <h2 class="featureSatz">Trunk case, PRO version</h2>High-quality workmanship with birch multiplex , dark brown, laminated
- Interior with foam padding
- 2 hinged, chromium plated case handles
- 2 chrome tip-over locks

Logistic

EAN / GTIN: 4026397360981

Weight: 27,50 kg

Length: 1.20 m

Width: 0.60 m

Height: 0.60 m

Bulky product

- 2 high-quality butterfly locks
- Branded hardware
- Made in Europe

Technical specifications:

Weight: 25.32 kg

EUROLITE LED 7C-12 Silent Slim Spot

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	60 W
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x P-Con (gray), mounting version
Fuse:	5 x 20 mm, T 1 A fuse replaceable
Lamp type:	LED lamp
LED type:	12 x 9 W high-power 7in1 RGB/CW/WW/A/UV (homogenous color mix)
Flash rate:	0.5 - 24 Hz
DMX channels:	3; 4-1; 4-2; 4-3; 4-4; 5; 6; 7; 9; 12
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	DMX; stand-alone; IR remote control; master/slave function; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Fixtures available for:	LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3
Projection:	Flicker-free
Beam angle (1/2 peak):	15°
Beam angle (1/10 peak):	33°
Color rendering index (CRI):	92 Ra
Housing color:	Black
Attachment system:	Double bracket
Display type:	4 digit 7-segment LED display
USB port:	Type A
Dimensions:	Width: 28 cm Depth: 12 cm Height: 29.5 cm
Weight:	3.58 kg
Noise classification:	Class 0 (no noise at all)
Photobiological safety:	Risk Group 0

Cable construction:	3 x 1.0 mm ² H05VV-F
Cable length:	Approx. 1.2 m
Diameter mounting holes:	3 x Ø11mm; 2 x Ø11mm
Material:	Metal, 3 mm
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 4x LED 4/7C-12 Silent Slim Spot

Maximum load:	50 kg
Case handle:	2 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Use of brands:	Branded hardware
Material:	Birch multiplex
Color:	Dark brown, laminated
Device compartment:	29.5 cm x 13.5 cm x 27 cm
Accessory compartment:	63 cm x 10.5 cm x 27 cm
Inside dimensions:	63 cm x 42 cm x 27 cm
Dimensions:	Width: 67 cm Depth: 46 cm Height: 37 cm
Weight:	11.00 kg

Scope of delivery:

- 1 x light effect
- 1 x power cord
- 1 x remote control
- 1 x battery
- 1 x user manual