

EUROLITE Set 4x LED 4C-12 Silent Slim Spot + Case

4x inaudible 4in1 spotlight with RGBW color mixture including PRO flightcase

Art. No.: 20000683 GTIN: 4026397360998







List price: 1522.01 €

incl. 19% VAT.

Features:

EUROLITE LED 4C-12 Silent Slim Spot

Silent 4in1 LED spotlight with RGBW color mixture

- Flat version requires minimal space when mounting
- 12 powerful LEDs 8 W high-power 4in1 QCL RGBW (homogenous color mix)
- Color blend stepless; Dimmer stepless
- Strobe effect
- Integrated show programs
- Direct color selection for 19 preset colors
- The device is cooled by passive convection cooling
- Control via DMX; IR remote control; stand-alone; QuickDMX via USB (optional); sound to light via microphone; master/slave function
- Preprogrammed in LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; Light 'J; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
- With a beam angle of 16°
- With double bracket
- Monochrome 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- Silent operation
- For application areas such as: Clubs/dancing school; wedding/gala/events; stage; theater; mobile djs / entertainer
- Application possibility: Standing; suspended; on stand

Package contents

- 1 x spotlight, 1 x power cord, 1 x remote control, 1 x user manual

Logistic

EAN / GTIN: 4026397360998

Weight: 27,10 kg Length: 1.20 m Width: 0.60 m Heigth: 0.60 m Bulky product

ROADINGER Flightcase 4x LED 4/7C-12 Silent Slim Spot

Trunk case, PRO version

- High-quality workmanship with birch multiplex , dark brown, laminated
- Interior with foam padding
- 2 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- Branded hardware
- Made in Europe

Technical specifications:

Weight: 25,00 kg

EUROLITE LED 4C-12 Silent Slim Spot

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	55 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	P-Con (gray), mounting version
Lamp type:	LED lamp
LED type:	12 x 8 W high-power 4in1 QCL RGBW (homogenous color mix)
Flash rate:	1 - 20 Hz
DMX channels:	3; 4; 5; 6; 9
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	DMX; IR remote control; stand-alone; QuickDMX via USB (optional); sound to light via microphone; master/slave function
Preprogrammed in:	LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; Light 'J; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
Beam angle:	16°
Beam angle (1/2 peak):	16°
Beam angle (1/10 peak):	35°
Color temperature:	6500K
Housing color:	Black matte
Attachment system:	Double bracket
Display type:	Monochrome 4 digit 7-segment LED display

Material:	Aluminum casting; metal
Dimensions:	Width: 28,5 cm
	Depth: 10,5 cm
	Height: 29,5 cm
Weight:	3,50 kg
Noise classification:	Class 0 (no noise at all)
Photobiological safety:	Risk Group 0
Power cord	
Cable construction:	3 x 1,0 mm² H05VV-F
Cable length:	Approx. 1,2 m
Mounting bracket	
Diameter mounting holes:	3 x Ø11mm
Material:	Metal, 3 mm
Remote control	
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 4x LED 4/7C-12 Silent Slim Spot

Maximum load:	50 kg
Case handle:	2 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Use of brands:	Branded hardware
Material:	Birch multiplex
Color:	Dark brown, laminated
Device compartment:	29,5 cm x 13,5 cm x 27 cm
Accessory compartment:	63 cm x 10,5 cm x 27 cm
Inside dimensions:	63 cm x 42 cm x 27 cm
Dimensions:	Width: 67 cm
	Depth: 46 cm
	Height: 37 cm
Weight:	11,00 kg