

EUROLITE Set 2x LED TMH-X4 Moving Head Wash Zoom + EU Case

2x washlight with 19 intense 15 W LEDs (4in1) and motorized zoom incl. PRO flightcase

Art. No.: 2000684

GTIN: 4026397361438



Features:

- Positioning within
- <p>EUROLITE LED TMH-X4 Moving Head Wash Zoom
- <h2 class="featureSatz">Washlight with 19 x 15 W LEDs, 4in1 QCL RGBW color mixing and motorized zoom</h2>19 LEDs 15 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix)
3 segments controlled separately
- Positioning within 540° PAN, 270° TILT
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Zoom motor driven
- Color blend stepless; color change adjustable; Dimmer electronic
- Strobe effect
- Integrated show programs
- The device is cooled by temperature-controlled fan at the head; cooling fan at the base
- Control via stand-alone; DMX; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Fixtures available for Light'J; LED PC-Control 512; EASY SHOW 1; Light Captain; GDTF (GrandMA3)
- Flicker-free
- With a beam angle of 1° - 40°
- Multicolor LCD display
- Mains input and output for power linking up to 8 units
- For application areas such as: Stage; clubs/dancing school; wedding/gala/events; mobile djs / entertainer; restaurants, bars and hotels; rental
- Application possibility: Standing; suspended
- <p>ROADINGER Flightcase PRO 2x LED TMH-X4

Logistic

EAN / GTIN: 4026397361438

Weight: 30,50 kg

Length: 0.60 m

Width: 0.60 m

Height: 1.20 m

Bulky product

- <h2 class="featureSatz">Trunk case, PRO version</h2>For optimal security
- With 1 accessory compartment
- High-quality workmanship with birch multiplex 7 mm, black, laminated
- Interior with foam padding
- Aluminum profile frames 30mm with rounded edges
- 2 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- Branded hardware
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight: 28.64 kg

EUROLITE LED TMH-X4 Moving Head Wash Zoom

| | |
|-------------------------|---|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 225 W |
| IP classification: | IP20 |
| Power connection: | Mains input via P-Con (blue), mounting version power supply cord with safety plug |
| Power output: | P-Con (gray), mounting version |
| Fuse: | 5 x 20 mm, T 2 A fuse replaceable |
| Lamp type: | LED lamp |
| LED type: | 19 x 15 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix) |
| Max. TILT movement: | 270° exact positioning (16 bit resolution) auto position correction (feedback) |
| Max. PAN movement: | 540° exact positioning (16 bit resolution) auto position correction (feedback) |
| Flash rate: | 1.5 - 25 Hz |
| Equipment: | Zoom motor driven |
| DMX channels: | 16; 24 |
| DMX input: | 3-pin XLR (M) mounting version |
| DMX output: | 3-pin XLR (F) mounting version |
| Cooling: | Temperature-controlled fan at the head Cooling fan at the base |
| Control: | Stand-alone; DMX; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional) |
| Fixtures available for: | Light J; LED PC-Control 512; EASY SHOW 1; Light Captain; GDTF (GrandMA3) |
| Projection: | Flicker-free |
| PWM frequency: | 4400 Hz |
| Beam angle: | 1° - 40° |
| Beam angle (1/2 peak): | 1 - 25° |

| | |
|--------------------------|--|
| Beam angle (1/10 peak): | 8 - 40° |
| Illuminance in Lux (lx): | Narrow red (R) 3m: 2779 lx, 6m: 763 lx Narrow green (G) 3m: 7893 lx, 6m: 1841 lx Narrow blue (B) 3m: 1468 lx, 6m: 390 lx Narrow cold white (CW) 3m: 9558 lx, 6m: 2468 lx Narrow all 3m: 19553 lx, 6m: 5001 lx Wide red (R) 3m: 272 lx, 6m: 73 lx Wide green (G) 3m: 583 lx, 6m: 160 lx Wide blue (B) 3m: 117 lx, 6m: 34 lx Wide cold white (CW) 3m: 740 lx, 6m: 211 lx Wide all 3m: 1568 lx, 6m: 439 lx |
| Housing color: | Black |
| Display type: | Multicolor LCD display |
| Dimensions: | Width: 30.5 cm Depth: 20.0 cm Height: 40.0 cm |
| Weight: | 8.62 kg |
| Noise classification: | Class 3 (clearly perceptible sounds) |
| Photobiological safety: | Risk Group 0 |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |

ROADINGER Flightcase PRO 2x LED TMH-X4

| | |
|--------------------------|---|
| Maximum load: | 50 kg |
| Aluminum profile frames: | 30 mm |
| Case handle: | 2 pc/pcs |
| Stop hinge: | 2 pc/pcs |
| Lock: | Butterfly lock: 2 pc/pcs |
| Use of brands: | Branded hardware |
| Material: | Birch multiplex, 7 mm; birch multiplex |
| Color: | Black, laminated; dark brown, laminated |
| Inside dimensions: | 58 cm x 33.5 cm |
| Device compartment: | 24 cm x 23 cm x 33.5 cm |
| Middle compartment: | 10 cm x |
| Dimensions: | Width: 72 cm Depth: 46 cm Height: 41 cm |
| Weight: | 11.40 kg |

Scope of delivery:

1 x moving light
1 x user manual
1 x power cord
2 x omega bracket