

## EUROLITE Set PAR-16 Spot sil + GU-10 230V COB 5W LED 1800-3000K dim2warm

PAR-16 housing with GU-10 socket including LED lamp with modern dim-to-warm-feature

GTIN: 4026397361582



**List price: 35.58 €**  
incl. 19% VAT.

### Features:

#### EUROLITE PAR-16 Spot GU-10 silver

PAR-16 housing with GU10 socket (with plug + cable)

- Mini-spot for GU-10 lamp
- Control via plug and play
- For PAR 16

#### Package contents

- 1 x spotlight, 1 x filter frame, 1 x user manual

### Logistic

EAN / GTIN: 4026397361582

Weight: 0,50 kg

Length: 0.17 m

Width: 0.10 m

Height: 0.10 m

#### OMNILUX GU-10 230V COB 5W LED 1800-3000K dim2warm

LED lamp with modern dim-to-warm feature

- Dimming behavior comparable with incandescent and halogen lamps (dim-to-warm)
- Changes the light color from 3000 K (warm white) to 1800 K (extra warm white) when dimming
- Creates particularly cosy atmospheres
- Easy lamp replacement
- Energy-saving
- Dimmable
- Easy installation
- With a beam angle of 24°
- Variable color temperature 1800 K - 3000 K
- Very high color rendering index (CRI)

## Technical specifications:

|                                  |         |
|----------------------------------|---------|
| Weight:                          | 0,32 kg |
| Energy efficiency class (A - G): | F       |

### EUROLITE PAR-16 Spot GU-10 silver

|                          |   |
|--------------------------|---|
| Power supply:            | 230 V AC, 50 Hz                                       |
| Power consumption:       | Max. 75 W   |
| IP classification:       | IP20  |
| Protection class:        | Protection class I                                    |
| Power connection:        | Fixed power supply cord with safety plug              |
| Cable construction:      | 3 x 0,75 mm² H05SS-F                                  |
| Cable length:            | Approx. 0,4 m   |
| Base:                    | GU10  |
| Lamp type:               | Selectable  |
| Color generation:        | Via color filter frame                                |
| Control:                 | Plug and play   |
| Construction:            | PAR-16  |
| Housing color:           | Silver  |
| Material:                | Aluminum, 1 mm  |
| Slot for spot length:    | 8 cm x 8 cm   |
| Dimensions:              | Length: 17 cm<br>Width: 11 cm<br>Height: 13 cm        |
| Weight:                  | 0,28 kg   |
| Mounting bracket         |   |
| Diameter mounting holes: | 2 x Ø10mm   |
| Material:                | Aluminum, 3 mm  |
| Filter frame             |   |
| Shape:                   | Octagonal   |
| Material:                | Aluminum  |
| Dimensions:              | Length: 7,7 cm<br>Width: 7,7 cm<br>Diameter: Ø 5,3 cm |
| Weight:                  | 0,01 kg   |

### OMNILUX GU-10 230V COB 5W LED 1800-3000K dim2warm

|                    |      |
|--------------------|------|
| Operating voltage: | 230  |
| Nominal wattage:   | 5 W  |
| Base:              | GU10 |

|                                  |  |
|----------------------------------|--|
| Lamp type:                       | LED lamp; reflector lamp                   |
| Lamp specification:              | Dimmable                                   |
| Measurand (Pst LM):              | 0,0  |
| Setup:                           | Easy installation                          |
| Beam angle:                      | 24°  |
| Beam angle (1/2 peak):           | 24°  |
| Beam angle (1/10 peak):          | 60°  |
| Color of light:                  | White                                      |
| Color temperature:               | 1800K - 3000K adjustable                   |
| Color rendering index (CRI):     | 90 Ra                                      |
| Luminous flux maintenance:       | 13   |
| MacAdam Color consistency:       | 3  |
| Operating temperature max.:      | 40° C                                      |
| Operating temperature min.:      | 20° C                                      |
| Lamp life:                       | 15000 h                                    |
| Luminous flux:                   | 400 lm                                     |
| Luminous flux maintenance:       | 0,97                                       |
| Wavelength:                      | 640 nm                                     |
| Material:                        | Aluminum casting                           |
| Dimensions:                      | Width: 5 cm<br>Depth: 5 cm<br>Height: 5 cm |
| Weight:                          | 0,04 kg                                    |
| Energy efficiency class (A - G): | F  |
| EPREL-Nr:                        | 960770                                     |