



Features:

EUROLITE PAR-38 Spot bk

PAR-38 housing with E27 socket (with plug + cable)

- Heat-resistant fixing screw
- Precise light output
- Strong cable tension relief
- Control via plug and play
- With mounting bracket
- For PAR 38
- For application areas such as: Clubs/dancing school; decoration; restaurants, bars and hotels; video and photography; advertisement/Shop window
- Silent operation

OMNILUX PAR-38 230V COB 18W E-27 LED 1800k-3000k dim2warm

PAR-38 LED lamp with modern dim-to-warm feature

- Dimming behavior comparable with incandescent and halogen lamps (dim-to-warm)
- Changes the light color from 3000 K (warm white) to 1800 K (extra warm white) when dimming
- Creates particularly cosy atmospheres
- Easy lamp replacement
- Energy-saving
- Dimmable
- Easy installation
- Variable color temperature 1800 K - 3000 K
- Very high color rendering index (CRI)

Logistic

EAN / GTIN: 4026397366785

Weight: 9,00 kg

Length: 0.70 m

Width: 0.27 m

Height: 0.52 m

EUROLITE EDX-4 DMX RDM LED Dimmer Pack

4-channel dimmer for LED lights with 230 V operation

- Trailing edge dimmer with 4 channels
- Max. channel load 200 watts
- Independent DMX addressing per channel possible
- Dimmer or switch operation
- 4 channel faders for control on the device
- Note: Only suitable for LED - not for conventional light bulbs
- 16 integrated show programs
- Control via RDM; stand-alone; sound to light via microphone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- With rigging points
- LCD display
- For application areas such as: Trade fair and shop fitting; theater; rental; video and photography; restaurants, bars and hotels
- Silent operation
- Application possibility: Wall mounting

Technical specifications:

| | |
|----------------------------------|---------|
| Weight: | 6.86 kg |
| Energy efficiency class (A - G): | F |

EUROLITE PAR-38 Spot bk

| | |
|-----------------------|---|
| Power supply: | 230 V AC, 50 Hz |
| Power consumption: | Max. 85 W |
| IP classification: | IP20 |
| Protection class: | Protection class I |
| Power connection: | Fixed power supply cord with safety plug |
| Cable construction: | 3 x 1.0 mm ² H05SS-F |
| Cable length: | Approx. 0.9 m |
| Base: | E27 |
| Lamp type: | Selectable |
| Color generation: | Via color filter frame |
| Control: | Plug and play |
| Construction: | PAR-38 |
| Housing color: | Black |
| Attachment system: | Mounting bracket |
| Material: | Aluminum; metal |
| Slot for spot length: | 17.2 cm x 17.2 cm |
| Dimensions: | Length: 21.5 cm Width: 19 cm Depth: 19 cm |
| Weight: | 0.70 kg |
| Noise classification: | Class 0 (no noise at all) |

| | |
|--------------------------|--|
| Diameter mounting holes: | 2 x Ø12mm |
| Material: | Metal, 2 mm |
| Diameter mounting holes: | 2 x Ø8mm |
| Material: | Metal, 1 mm |
| Dimensions: | Length: 17 cm Width: 17 cm Diameter: Ø 14 cm |
| Weight: | 0.12 kg |

OMNILUX PAR-38 230V COB 18W E-27 LED 1800k-3000k dim2warm

| | |
|----------------------------------|--------------------------|
| Operating voltage: | 230, 220 - 240 V |
| Nominal wattage: | 18 W |
| Base: | E27 |
| Lamp type: | LED lamp; reflector lamp |
| Lamp specification: | Dimmable |
| Beam angle: | 38° |
| Setup: | Easy installation |
| Color of light: | White |
| Color temperature: | 1800K - 3000K adjustable |
| Color rendering index (CRI): | 96 Ra |
| Construction: | PAR-38 |
| Operating temperature max.: | 40° C |
| Operating temperature min.: | 20° C |
| Lamp life: | 15000 h |
| Luminous flux: | 1440 lm |
| Wavelength: | 630 nm |
| Weight: | 0.38 kg |
| Energy efficiency class (A - G): | F |
| EPREL-Nr: | 963434 |

EUROLITE EDX-4 DMX RDM LED Dimmer Pack

| | |
|--------------------------------|---|
| Power supply: | 230 V AC, 50 Hz |
| Output power: | Max. 200 W Max. 800 W |
| Power connection: | Mains input via P-Con (blue), mounting version power supply cord with safety plug |
| Power output: | 4 x safety contact (F), hinged lid mounting version fused 1 x P-Con (gray), mounting version Bypass |
| Device fuse: | 5 x 20 mm, F 6 A fuse replaceable |
| Power output fuse per channel: | 5 x 20 mm, T 1 A fuse replaceable |
| DMX channels: | 1; 4; 6 |
| DMX input: | 3-pin XLR (M) |
| DMX output: | 3-pin XLR (F) |

| | |
|-----------------------|---|
| Control: | RDM; stand-alone; sound to light via microphone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional) |
| Control channels: | 4 |
| Flying points: | 2 x M10 thread |
| Display type: | LCD display |
| Status LED: | Channel level meter |
| Color: | Black |
| Dimensions: | Width: 21 cm Depth: 29 cm Height: 9 cm |
| Weight: | 2.53 kg |
| Noise classification: | Class 0 (no noise at all) |

Scope of delivery:

4 x EUROLITE PAR-38 Spot bk

- 1 x spotlight
- 1 x filter frame
- 1 x user manual

1 x EUROLITE EDX-4 DMX RDM LED Dimmer Pack

- 1 x device
- 1 x user manual
- 1 x power cord