

## FUTURELIGHT Set 2x EYE-7 HCL Zoom + Case

2x PRO washlight with 6in1 COB LEDs and motorized zoom including PRO flightcase

Art. No.: 20000723

GTIN: 4026397471861



**The article is no longer in our assortment.**

### Features:

#### FUTURELIGHT EYE-7 HCL Zoom LED Moving Head Wash

PRO washlight with 6in1 COB LEDs and motorized zoom

- Equipped with 7 x 17 W 6in1 LED in R/G/B/Amber/Lime/Cyan
- Variable PWM frequency (pulse-width modulation)
- Optional W-DMX receiver for wireless DMX Control
- Compact design
- 2 different LED segments, which can be controlled individually via DMX
- Exact positioning via 16-bit PAN/TILT movement resolution
- 16-bit resolution for high-resolution dimming
- Motorized zoom with 2-36° beam angle
- Color presets
- Variable color temperature
- Built-in programs
- Stepless color blend
- Strobe effect with adjustable speed
- Random strobe effect
- Automatic position correction
- PAN angle switchable between 540° and 630°
- ESDC function (Easy Service Data Check) with battery-buffered control board for operation time readouts etc. (the Li-Ion battery 3.7V, AAA, 10440 is not included)
- Control panel with LC display for easy configuration
- Stand-alone, master/slave and DMX mode
- The scenes can be modified via the Control Board or via an external controller and loaded into the memory
- Number of scenes can be changed individually
- Software upload by optional accessories via DMX link

### Logistic

EAN / GTIN: 4026397471861

Weight: 28,00 kg

Length: 1.20 m

Width: 0.60 m

Height: 0.60 m

Bulky product

- 7 powerful LEDs 17 W high-power 6in1 HCL RGBALC (homogenous color mix)
  - PAN angle switchable between 540° and 630°
  - Auto position correction (feedback)
  - Exact positioning (16 bit resolution)
  - Zoom motor driven
  - Strobe effect
  - The device is cooled by temperature-controlled fan
  - Control via stand-alone; DMX; RDM; W-DMX by wireless solution upgradeable; master/slave function; sound to light via microphone
  - Preprogrammed in LED PC-Control 512; Light Captain; Light`J
  - Flicker-free
  - With a beam angle of 2° - 36°
  - Built with NEUTRIK connector
- Package contents**
- 1 x moving light, 1 x power cord, 1 x user manual, 1 x declaration of conformity, 1 x mounting bracket, 1 x XLR cable

**ROADINGER Flightcase 2x EYE-7 RGBW Zoom**

Trunk case, PRO version

- With 2 device compartments
- With accessory compartment
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 30mm with rounded edges
- 2 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 1 high-quality butterfly lock
- Made in Germany
- For further information about this product, please refer to the Data Sheet under "Downloads"

**Technical specifications:**

|         |          |
|---------|----------|
| Weight: | 25,20 kg |
|---------|----------|

**FUTURELIGHT EYE-7 HCL Zoom LED Moving Head Wash**

|                     |                                                                                      |
|---------------------|--------------------------------------------------------------------------------------|
| Power supply:       | 100-240 V AC, 50/60 Hz                                                               |
| Power consumption:  | 130 W                                                                                |
| IP classification:  | IP20                                                                                 |
| Power connection:   | Mains input via PowerCON (blue), mounting version power supply cord with safety plug |
| Power output:       | 1 x PowerCON (gray), mounting version                                                |
| Fuse:               | 5 x 20 mm, T 3,15 A fuse replaceable                                                 |
| Lamp type:          | LED lamp                                                                             |
| LED type:           | 7 x 17 W high-power 6in1 HCL RGBALC (homogenous color mix)                           |
| Max. TILT movement: | 270° exact positioning (16 bit resolution) auto position correction (feedback)       |
| Max. PAN movement:  | 540°, 630° exact positioning (16 bit resolution) auto position correction (feedback) |
| Flash rate:         | 1 - 18 Hz                                                                            |
| Equipment:          | Zoom motor driven                                                                    |

|                          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
|--------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| DMX channels:            | 16; 19; 20; 33                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| DMX input:               | 1 x 3-pin XLR (M) mounting version                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| DMX output:              | 1 x 3-pin XLR (F) mounting version                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Cooling:                 | Temperature-controlled fan                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Control:                 | Stand-alone; DMX; RDM; W-DMX by wireless solution upgradeable; master/slave function; sound to light via microphone                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Preprogrammed in:        | LED PC-Control 512; Light Captain; Light´J                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Projection:              | Flicker-free                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Beam angle:              | 2° - 36°                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Beam angle (1/2 peak):   | 2 - 15°                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Beam angle (1/10 peak):  | 7 - 36°                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Illuminance in Lux (lx): | <p>Narrow red (R) 1m: 7036 lx, 3m: 1003 lx, 6m: 248 lx</p> <p>Narrow green (G) 1m: 14473 lx, 3m: 2193 lx, 6m: 548 lx</p> <p>Narrow blue (B) 1m: 2461 lx, 3m: 478 lx, 6m: 122 lx</p> <p>Narrow amber (A) 1m: 27460 lx, 3m: 4256 lx, 6m: 1066 lx</p> <p>Narrow lime 1m: 44659 lx, 3m: 6773 lx, 6m: 1705 lx</p> <p>Narrow cyan 1m: 6274 lx, 3m: 1011 lx, 6m: 251 lx</p> <p>Narrow all 3m: 14976 lx, 6m: 3744 lx</p> <p>Wide red (R) 1m: 787 lx, 3m: 95 lx, 6m: 25 lx</p> <p>Wide green (G) 1m: 1716 lx, 3m: 215 lx, 6m: 58 lx</p> <p>Wide blue (B) 1m: 392 lx, 3m: 51 lx, 6m: 14 lx</p> <p>Wide amber (A) 1m: 3202 lx, 3m: 388 lx, 6m: 104 lx</p> <p>Wide lime 1m: 4793 lx, 3m: 594 lx, 6m: 160 lx</p> <p>Wide cyan 1m: 839 lx, 3m: 103 lx, 6m: 28 lx</p> <p>Wide all 1m: 11196 lx, 3m: 1365 lx, 6m: 362 lx</p> |
| Housing color:           | Black                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Use of brands:           | Built with NEUTRIK connector                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Dimensions:              | <p>Width: 24,9 cm</p> <p>Depth: 17,9 cm</p> <p>Height: 34,7 cm</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Weight:                  | 7,30 kg                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Noise classification:    | Class 3 (clearly perceptible sounds)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Special product:         | Not designed for household room illumination                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Intended use:            | Show effect lighting                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |

#### ROADINGER Flightcase 2x EYE-7 RGBW Zoom

|                          |                          |
|--------------------------|--------------------------|
| Maximum load:            | 50 kg                    |
| Aluminum profile frames: | 30 mm                    |
| Case handle:             | 2 pc/pcs                 |
| Stop hinge:              | 2 pc/pcs                 |
| Lock:                    | Butterfly lock: 1 pc/pcs |
| Material:                | Birch multiplex, 7 mm    |

|                        |                                                 |
|------------------------|-------------------------------------------------|
| Color:                 | Dark brown, laminated                           |
| Accessory compartment: | 45,5 cm x                                       |
| Device compartment:    | 18 cm x 25 cm x 22 cm                           |
| Inside dimensions:     | 45,5 cm x                                       |
| Dimensions:            | Width: 49,5 cm<br>Depth: 44 cm<br>Height: 47 cm |
| Weight:                | 10,60 kg                                        |