

EUROLITE Set 4x LED PIX-12 QCL Bar + Case

4x LED bar with 12 x 4 W RGBW LED including PRO flightcase

Art. No.: 20000739

GTIN: 4026397681529



The article is no longer in our assortment.

Features:

EUROLITE LED PIX-12 QCL Bar

LED light bar with 12 x 4 W RGBW LED, pixel control and IR remote control

- 12 powerful LEDs high-power 4in1 QCL RGBW (homogenous color mix)
LEDs controlled separately
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect
- 5 integrated show programs
- Direct color selection for 18 preset colors
- The device is cooled by cooling fan
- Control via stand-alone; IR remote control; DMX; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Preprogrammed in LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain
- With a beam angle of 18°
- With mounting bracket
- Mains input and output for power linking up to 8 units

Package contents

- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x remote control, 1 x battery

Logistic

EAN / GTIN: 4026397681529

Weight: 39,10 kg

Length: 1.10 m

Width: 0.00 m

Height: 0.00 m

Bulky product

ROADINGER Flightcase 4x PIX-12

Trunk case, PRO version

- For optimal security
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated

- Interior with foam padding
- Aluminum profile frames 30mm with rounded edges
- 2 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- Branded hardware

Technical specifications:

Weight:	36,40 kg
---------	----------

EUROLITE LED PIX-12 QCL Bar

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	45 W
IP classification:	IP20
Protection class:	Protection class I
Lamp type:	LED lamp
LED type:	12 x high-power 4in1 QCL RGBW (homogenous color mix)
DMX channels:	3; 4; 15; 52; 2
DMX input:	3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; IR remote control; DMX; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Preprogrammed in:	LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain
Beam angle:	18°
Beam angle (1/2 peak):	18°
Beam angle (1/10 peak):	36°
Housing color:	Black
Attachment system:	Mounting bracket
Dimensions:	Length: 100,0 cm Depth: 16,5 cm Height: 11,1 cm
Weight:	5,55 kg
Photobiological safety:	Risk Group 0
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 4x PIX-12

Maximum load:	50 kg
Aluminum profile frames:	30 mm
Case handle:	2 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm; birch multiplex
Color:	Dark brown, laminated
Device compartment:	100 cm x 8 cm x 21 cm
Dimensions:	Length: 105 cm Width: 55 cm Height: 24 cm
Weight:	14,20 kg