

## EUROLITE Set 4x LED TMH-S90 + Case

4x Led moving head spot including flightcase with wheels

Art. No.: 2000742

GTIN: 4026397681796



### Features:

- Positioning within
- <p>EUROLITE LED TMH-S90 Moving Head Spot
- <h2 class="featureSatz">LED moving head spot with color wheel, static and rotating gobo wheel, prism and focus</h2>Rotating 3-facet prism with variable speed
- 1 LED 90 W COB (chip-on-board) cold white (CW)
- Positioning within 540° PAN, 200° TILT
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Prism 3-fold; gobo wheel with rotating gobos; gobo wheel with static gobos; focus motor-driven; color wheel
- Dimmer electronic
- Color wheel with 7 dichroic filters plus open<BR>half colors selectable, Rainbow effect with adjustable speed in both directions
- Gobo wheel with static gobos, 7 gobos and open<BR>shake effect
- Gobo wheel with rotating gobos, 5 gobos, 1 multi color gobo and open<BR>shake effect
- Gobos changeable
- Slot-in gobo system for easy gobo replacement
- Integrated show programs
- The device is cooled by cooling fan
- Control via DMX; sound to light via microphone; stand-alone; master/slave function; QuickDMX via USB (optional); CRMX by LumenRadio via USB (optional); W-DMX by wireless solution via USB (optional)
- Flicker-free
- With a beam angle of 12°
- For application areas such as: Clubs/dancing school; wedding/gala/events; stage; mobile djs / entertainer; restaurants, bars and hotels

### Logistic

EAN / GTIN: 4026397681796

Weight: 50,00 kg

Length: 1.20 m

Width: 0.80 m

Height: 0.37 m

Bulky product

- Application possibility: Standing; suspended
- <p>ROADINGER Flightcase 4x TMH-S90/H90/B90
- <h2 class="featureSatz">Trunk case with castors</h2>For optimal security
- With 4 device compartments
- High-quality workmanship with plywood multi-layer glued 7 mm, black, laminated
- Interior with foam padding<BR>cover with foam padding
- Interior with foam padding<BR>cover with foam padding
- Aluminum profile frames 30mm with rounded edges
- 4 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- Castors

## Technical specifications:

---

Weight: 43.80 kg

---

### EUROLITE LED TMH-S90 Moving Head Spot

|                     |  |
|---------------------|--|
| Power supply:       | 100-240 V AC, 50/60 Hz   |
| Power consumption:  | 140 W  |
| Protection class:   | Protection class I   |
| Power connection:   | Mains input via P-Con (blue), mounting version power supply cord with safety plug  |
| Power output:       | P-Con (gray), mounting version   |
| Fuse:               | 5 x 20 mm, T 2 A   |
| Lamp type:          | LED lamp   |
| LED type:           | 1 x 90 W COB (chip-on-board) cold white (CW)   |
| Max. TILT movement: | 200° exact positioning (16 bit resolution) auto position correction (feedback)   |
| Max. PAN movement:  | 540° exact positioning (16 bit resolution) auto position correction (feedback)   |
| Flash rate:         | 1.5 - 15 Hz  |
| Equipment:          | Prism 3-fold; gobo wheel with rotating gobos; gobo wheel with static gobos; focus motor-driven; color wheel  |
| Color generation:   | Color wheel with 7 dichroic filters plus open Half colors selectable, Rainbow effect with adjustable speed in both directions  |
| Gobos:              | Gobo wheel with static gobos, 7 gobos and open Shake effect<br>Gobo wheel with rotating gobos, 5 gobos, 1 multi color gobo and open<br>Outside diameter 21.8mm<br>Image diameter 16mm<br>Shake effect<br>Gobos changeable<br>Slot-in gobo system for easy gobo replacement |
| DMX channels:       | 15   |
| DMX input:          | 3-pin XLR (M) mounting version   |
| DMX output:         | 3-pin XLR (F) mounting version   |

|                          |   |
|--------------------------|---|
| Cooling:                 | Cooling fan   |
| Control:                 | DMX; sound to light via microphone; stand-alone; master/slave function; QuickDMX via USB (optional); CRMX by LumenRadio via USB (optional); W-DMX by wireless solution via USB (optional) |
| Fixtures available for:  | EASY SHOW 1; Light Captain; EASY SHOW 3   |
| Projection:              | Flicker-free  |
| PWM frequency:           | 15600 Hz  |
| Beam angle (1/2 peak):   | 12°   |
| Illuminance in Lux (lx): | Cold white (CW) 1m: 52772 lx, 3m: 6198 lx, 6m: 1543 lx  |
| Housing color:           | Black   |
| Dimensions:              | Width: 25.0 cm<br>Depth: 20.5 cm<br>Height: 35.0 cm   |
| Weight:                  | 6.20 kg   |
| Noise classification:    | Class 3 (clearly perceptible sounds)  |
| Photobiological safety:  | Risk Group 0  |
| Special product:         | Not designed for household room illumination  |
| Intended use:            | Show effect lighting  |

#### **ROADINGER Flightcase 4x TMH-S90/H90/B90**

|                          |   |
|--------------------------|---|
| Maximum load:            | 100 kg  |
| Aluminum profile frames: | 30 mm   |
| Case handle:             | 4 pc/pcs                                      |
| Stop hinge:              | 2 pc/pcs                                      |
| Lock:                    | Butterfly lock: 2 pc/pcs                      |
| Transport aid:           | Castors                                       |
| Material:                | Plywood multi-layer glued, 7 mm               |
| Color:                   | Black, laminated                              |
| Device compartment:      | 26 cm x 20 cm x 37 cm                         |
| Accessory compartment:   | 26 cm x 9 cm x 37 cm                          |
| Dimensions:              | Width: 58 cm<br>Depth: 57 cm<br>Height: 54 cm |
| Weight:                  | 19.00 kg                                      |

#### **Scope of delivery:**

- 1 x moving light
- 1 x user manual
- 1 x power cord
- 1 x omega bracket
- 1 x safety eyelet