

## EUROLITE Set LED SLS-30 COB WW + Stand

LED floor spot with 30 W COB LED in WW including speaker stand and knob

Art. No.: 20000794

GTIN: 4026397687378



**List price: 136.85 €**

incl. 19% VAT.

### Features:

#### EUROLITE LED SLS-30 COB WW Floor

LED floor spot with 30 W COB LED in WW, incl. IR remote control

- DMX and power terminals intelligently designed for easy wiring
- 1 powerful LED 30 W COB (chip-on-board) warm white (WW)
- Dimmer electronic
- Strobe effect
- Integrated show programs
- The device is cooled by cooling fan
- Control via stand-alone; DMX; master/slave function; IR remote control; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Preprogrammed in Light´J; Light Captain; Colorchief
- Flicker-free
- With a beam angle of 18°
- Very high color rendering index (CRI)
- With double bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; stage; small rental
- Application possibility: Standing; suspended

#### Package contents

- 1 x spotlight, 1 x power cord, 1 x remote control, 1 x user manual

### Logistic

EAN / GTIN: 4026397687378

Weight: 4,00 kg

Length: 1.30 m

Width: 0.50 m

Height: 0.30 m

Bulky product

#### OMNITRONIC Speaker Stand BOB System

Speaker stand for BOB speakers, extendable up to 170 cm

- Tube diameter: Ø 30 mm
- Adjustable height
- Scratchproof and shockproof

#### Package contents

- 1 x stand, 1 x user manual

## Technical specifications:

Weight:	3,26 kg
---------	---------

### EUROLITE LED SLS-30 COB WW Floor

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	25 W
IP classification:	IP20
Protection class:	Protection class II
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug included
Power output:	Safety contact (F), mounting version
Device fuse:	T 1 A fuse replaceable
Lamp type:	LED lamp
LED type:	1 x 30 W COB (chip-on-board) warm white (WW)
Flash rate:	0 - 20 Hz
DMX channels:	1; 2; 4
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; DMX; master/slave function; IR remote control; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Preprogrammed in:	Light´J; Light Captain; Colorchief
Projection:	Flicker-free
Beam angle:	18°
Beam angle (1/2 peak):	18°
Beam angle (1/10 peak):	65°
Color temperature:	3000K
Color rendering index (CRI):	97 Ra
Housing color:	Black
Attachment system:	Double bracket
Display type:	4 digit 7-segment LED display
Material:	Plastic
Dimensions:	Width: 21,5 cm Depth: 12,7 cm

	Height: 22,85 cm
Weight:	1,10 kg
Noise classification:	Class 3 (clearly perceptible sounds); class 3 (clearly perceptible sounds)
Photobiological safety:	Risk Group 0
Mounting bracket	
Diameter mounting holes:	1 x Ø11mm; 2 x Ø10mm
Material:	Metal, 1,5 mm
Power cord	
Cable construction:	3 x 0,75 mm² H05VV-F
Cable length:	Approx. 1,2 m
Remote control	
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

#### **OMNITRONIC Speaker Stand BOB System**

Maximum carrying capacity:	14 kg
Height:	Maximum: 195 cm Minimum: 107 cm Adjustable in 6 steps with locking pin
Attachment system:	M10 thread
Type (general stands):	Speaker stand/manual
Material:	Steel
Color:	Black, painted; , scratchproof and shockproof
Main pipe diameter:	Ø 3 cm
Extension tube diameter:	Ø 2,5 cm
Weight:	2,15 kg