

## EUROLITE Set LED THA-20PC TRC + Stand

Fanless PC spot with 17 W white light LED incl. speaker stand

Art. No.: 20000797

GTIN: 4026397687408



**List price: 220.15 €**

incl. 19% VAT.

### Features:

#### EUROLITE LED THA-20PC TRC Theater Spot bk

Fanless PC spot with 17 W white light LED, color rendering index (CRI) >90

- New LED technology that simulates the color temperature curve of a halogen lamp when dimming
- Two additional frost filters provide a soft, homogeneous light
- 1 powerful LED 17 W COB (chip-on-board) Dim to warm (homogenous color mix)
- Dimmer electronic
- The device is cooled by passive convection cooling
- Control via stand-alone
- Flicker-free
- With a beam angle of 17°
- Very high color rendering index (CRI)
- With mounting bracket
- Rubber feet
- Silent operation
- For application areas such as: Trade fair and shop fitting; wedding/gala/events; video and photography; mobile use
- Application possibility: Suspended; on stand

#### Package contents

- 1 x spotlight, 1 x barndoor, 1 x filter frame, 2 x frost filter, 1 x ring, 2 x lamp clamping ring, 1 x user manual

### Logistic

EAN / GTIN: 4026397687408

Weight: 6,00 kg

Length: 1.20 m

Width: 0.60 m

Height: 0.60 m

Bulky product

#### OMNITRONIC Speaker Stand BOB System

Speaker stand for BOB speakers, extendable up to 170 cm

- Tube diameter: Ø 30 mm
- Adjustable height
- Scratchproof and shockproof

#### Package contents

- 1 x stand, 1 x user manual

## Technical specifications:

Weight:	4,39 kg
---------	---------

### EUROLITE LED THA-20PC TRC Theater Spot bk

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	22 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Fixed power supply cord with safety plug
Fuse:	5 x 20 mm, T 1 A fuse replaceable
LED type:	1 x 17 W COB (chip-on-board) Dim to warm (homogenous color mix)
Cooling:	Passive convection cooling
Control:	Stand-alone
Projection:	Flicker-free
Beam angle:	17°
Beam angle (1/2 peak):	17° Frost filter 19° Frost filter 26°
Beam angle (1/10 peak):	36° Frost filter 40° Frost filter 53°
Color temperature:	3000K
Color rendering index (CRI):	92 Ra
Illuminance in Lux (lx):	Warm white (WW) 3m: 727 lx, 6m: 188 lx
Housing color:	Black
Attachment system:	Mounting bracket
Transport aid:	Rubber feet
Material:	Aluminum casting
Slot for spot length:	10 cm x 10 cm
Dimensions:	Length: 21,5 cm Width: 14,5 cm Depth: 21 cm
Weight:	2,23 kg
Noise classification:	Class 0 (no noise at all)
Mounting bracket	
Diameter mounting holes:	1 x Ø10mm
Material:	Metal, 3 mm

Power cord	
Cable construction:	3 x 0,75 mm² H05VV-F
Cable length:	Approx. 1 m
Barndoor	
Material:	Aluminum, 1 mm; metal
Ring diameter:	Outside: 99 mm Inside: 80 mm
Filter frame	
Diameter mounting holes:	1 x Ø4mm
Material:	Aluminum, 0,8 mm
Color:	Black
Dimensions:	Width: 9,9 cm Height: 9,9 cm Diameter: Ø 8 cm
Frost filter	
Material:	Plastic
Color:	Semi-transparent
Dimensions:	Width: 0,2 cm Diameter: Ø 8 cm
Ring	
Material:	Aluminum, 1 mm
Color:	Gold
Dimensions:	Depth: 1,3 cm Diameter: Ø 8,2 cm
Lamp clamping ring	
Material:	Metal, 2 mm
Color:	Black
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

#### OMNITRONIC Speaker Stand BOB System

Maximum carrying capacity:	14 kg
Height:	Maximum: 195 cm Minimum: 107 cm Adjustable in 6 steps with locking pin
Attachment system:	M10 thread
Type (general stands):	Speaker stand/manual
Material:	Steel
Color:	Black, painted; , scratchproof and shockproof
Main pipe diameter:	Ø 3 cm
Extension tube diameter:	Ø 2,5 cm
Weight:	2,15 kg