

EUROLITE Set 2x LED CBB-2 COB WW Bar + Case

2x LED light effect bar with WW COB Leds including PRO flightcase

Art. No.: 20000810

GTIN: 4026397687972



Features:

- 2 LEDs 35 W COB (chip-on-board) warm white (WW)
- Dimmer electronic
- Strobe effect
- Integrated show programs
- The device is cooled by cooling fan
- Control via IR remote control; sound to light via microphone; DMX; stand-alone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Flicker-free
- With a beam angle of 37°
- Very high color rendering index (CRI)
- With mounting bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Stage; decoration; wedding/gala/events; restaurants, bars and hotels; Trade fair and shop fitting; video and photography
- Application possibility: Standing; suspended; on stand
- <p>ROADINGER Flightcase 2 x LED CBB-2 COB Bar
- <h2 class="featureSatz">Trunk case, PRO version</h2>For optimal security
- With accessory compartment
- High-quality workmanship with birch multiplex 6.5 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 20mm with rounded edges
- Hinged, chromium plated case handle
- 2 chrome tip-over locks
- 1 high-quality butterfly lock

Logistic

EAN / GTIN: 4026397687972

Weight: 12,00 kg

Length: 0.82 m

Width: 0.41 m

Height: 0.52 m

- Branded hardware

Technical specifications:

Weight:	9.75 kg
---------	---------

EUROLITE LED CBB-2 COB WW Bar

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	50 W
Lamp type:	LED lamp
LED type:	2 x 35 W COB (chip-on-board) warm white (WW)
Flash rate:	0 - 20 Hz
DMX channels:	2; 3; 5
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	IR remote control; sound to light via microphone; DMX; stand-alone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Fixtures available for:	LED PC-Control 512; Light Captain; Light´J; Colorchief
Projection:	Flicker-free
Beam angle (1/2 peak):	37°
Beam angle (1/10 peak):	70°
Color temperature:	2700K
Color rendering index (CRI):	91 Ra
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Dimensions:	Width: 15.5 cm Depth: 24 cm Height: 17.5 cm
Weight:	2.45 kg
Noise classification:	Class 2 (slight noise)
Photobiological safety:	Risk Group 0
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 2 x LED CBB-2 COB Bar

Maximum load:	25 kg
Aluminum profile frames:	20 mm
Case handle:	1 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 1 pc/pcs
Use of brands:	Branded hardware
Material:	Birch multiplex, 6.5 mm, laminated; birch multiplex, 7 mm
Color:	Dark brown, laminated
Device compartment:	12 cm x 26 cm x 19.5 cm
Middle compartment:	10.5 cm x 26 cm x 19.5 cm
Inside dimensions:	34.5 cm x 26 cm x 19.5 cm
Dimensions:	Width: 30 cm Depth: 41 cm Height: 30 cm
Weight:	4.85 kg

Scope of delivery:

1 x spotlight
 1 x user manual
 1 x power cord
 1 x remote control
 1 x battery