

EUROLITE Set DIY LED THA-40PC TRC + Multi adapter, 3 phases, black

DIY set for connection to 3-phase track systems

Art. No.: 2000831

GTIN: 4026397689327



Features:

- Silent operation
- Very high color rendering index (CRI)
- Flicker-free
- Control via stand-alone; rotary dial for brightness; Dimmer
- 1 LED 57 W COB (chip-on-board) warm white (WW)
- Dimmer electronic
- The device is cooled by passive convection cooling
- Rugged metal housing
- With mounting bracket
- For application areas such as: Decoration; Trade fair and shop fitting; restaurants, bars and hotels; video and photography; advertisement/Shop window
- <p>EUTRAC Multi adapter, 3 phases, black
- <h2 class="featureSatz">Multi adapter with data bus option</h2>For 3~ circuit track
- Prepared for data bus contacts (data bus contact with SELV safety chip, part no. 99-698-0)
- Screw termination, approved for 6 A inductive / 6 A ohmic up to 250 V
- With earth contact, circuit selection by turnkey switch and optional neutral position during operation
- Due to double mechanical locking perfect track fixing even when using heavy spotlights
- Maximum load up to 5 kg, or 10 kg when using retaining collar 99-066-x
- Made in Germany

Logistic

EAN / GTIN: 4026397689327

Weight: 3,50 kg

Length: 0.41 m

Width: 0.31 m

Height: 0.28 m

Technical specifications:

Weight: 3.88 kg

EUROLITE LED THA-40PC TRC Theater Spot bk

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 40 W

Protection class: Protection class I

Power connection: Fixed power supply cord with safety plug

Fuse: 5 x 20 mm, T 1 A fuse replaceable

Lamp type: LED lamp

LED type: 1 x 57 W COB (chip-on-board) warm white (WW)

Cooling: Passive convection cooling

Control: Stand-alone; rotary dial for brightness; Dimmer

Projection: Flicker-free

Beam angle (1/2 peak): 12 - 36°

Beam angle (1/10 peak): 18 - 47°

Color temperature: 3100K

Color rendering index (CRI): 92 Ra

Illuminance in Lux (lx):
Narrow 3m: 2008 lx, 6m: 514 lx
Wide 3m: 482 lx, 6m: 141 lx

Housing color: Black

Attachment system: Mounting bracket

Transport aid: Rubber feet

Material: Aluminum casting

Slot for spot length: 13.1 cm x 13.1 cm

Dimensions:
Length: 26 cm
Width: 20 cm
Depth: 25 cm

Weight: 3.82 kg

Noise classification: Class 0 (no noise at all)

Diameter mounting holes: 1 x Ø10mm; 2 x Ø6mm

Material: Metal, 3 mm

Cable construction: 3 x 0.75 mm² H05VV-F

Cable length: Approx. 1 m

Material: Aluminum, 1.5 mm; metal

Ring diameter:
Outside: 12.9 mm
Inside: 10.9 mm

Diameter mounting holes: 1 x Ø4mm

Shape: Octagonal

Material: Aluminum, 0.8 mm

Dimensions:
Width: 13 cm
Height: 13 cm
Diameter: Ø 10.5 cm

Special product: Not designed for household room illumination

Intended use: Show effect lighting

EUTRAC Multi adapter, 3 phases, black

Power connection:	Mains input via special connector recessed mounting
Power output:	Screw terminal
Weight:	0.05 kg

EUTRAC Retaining collar for multi adapter Ø10,5mm/ Ø13,5mm black

Weight:	0.01 kg
---------	---------

Scope of delivery:

1 x EUROLITE LED THA-40PC TRC Theater Spot bk

- 1 x spotlight
- 1 x barndoor
- 1 x filter frame
- 1 x user manual

1 x EUTRAC Retaining collar for multi adapter Ø10,5mm/ Ø13,5mm black

- 1 x screwing