



### Features:

#### EUROLITE AKKU Dot 1 RGB/WW QuickDMX bk

Battery-powered pinpoint with magnetic base, 15 W 4in1 LED, QuickDMX, frost filter and IR remote control

- Integrated QuickDMX transceiver for wireless DMX control
- Magnetic base affixes to metal surfaces
- Additional frost filter provides a wide, soft and homogeneous light
- Cordless, flexible and versatile
- Battery operation up to 18h depending on program used
- Integrated automatic charging of the battery and status indicator
- 1 LED 15 W SMD 9080 4in1 RGB/WW (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; white balance adjustable; Dimmer speed (step response) adjustable
- Strobe effect
- 36 integrated show programs
- Direct color selection for 15 preset colors
- The device is cooled by passive convection cooling
- Control via IR remote control; stand-alone; sound to light via microphone; QuickDMX; master/slave function; DMX
- Flicker-free
- With a beam angle of 9°
- With mounting bracket
- Monochrome OLED display
- With a KENSINGTON LOCK theft protection
- For application areas such as: Small rental; wedding/gala/events; mobile djs / entertainer
- Application possibility: Standing; suspended
- Silent operation

### Logistic

EAN / GTIN: 4026397689617

Weight: 14,00 kg

Length: 0.70 m

Width: 0.27 m

Height: 0.52 m

## ROADINGER Flightcase 4x AKKU Dot 1 RGB/WW QuickDMX

### Trunk case

- Cable bushing allows loading the devices inside
- With accessory compartment
- Interior with foam padding
- Aluminum profile frames 20mm with rounded edges
- Hinged, chromium plated case handle
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- Rubber feet

## Technical specifications:

---

Weight: 11.68 kg

---

## EUROLITE AKKU Dot 1 RGB/WW QuickDMX bk

|                         |   |
|-------------------------|---|
| Power supply:           | 100-240 V AC, 50/60 Hz<br>12.6V DC 200 mA   |
| Power consumption:      | 25 W  |
| Protection class:       | Protection class III  |
| Power connection:       | Battery/battery pack built-in<br>Mains input via coaxial power connector (M)<br>mounting version                                  |
| Battery pack type:      | 1 x lithium ion 11.1 V, 5200 mAh, 57.72 Wh  |
| Battery pack:           | Battery operation up to 18h depending on<br>program used<br>Recharging time 3.5h  |
| Lamp type:              | LED lamp  |
| LED type:               | 1 x 15 W SMD 9080 4in1 RGB/WW (homogenous<br>color mix)   |
| Flash rate:             | 1 - 23 Hz   |
| DMX channels:           | 3; 4; 6; 8; 11  |
| Cooling:                | Passive convection cooling  |
| Control:                | IR remote control; stand-alone; sound to light via<br>microphone; QuickDMX; master/slave function;<br>DMX                         |
| Fixtures available for: | LED EASY OPERATOR 4x4; LED EASY<br>OPERATOR 4x6; LED EASY OPERATOR<br>DELUXE; Light J; Light Captain; EASY SHOW 2;<br>EASY SHOW 3 |
| Projection:             | Flicker-free  |
| Carrier frequency:      | 2.4 GHz   |
| Beam angle (1/2 peak):  | 9°  |
| Beam angle (1/10 peak): | 18°   |
| Housing color:          | Black   |
| Attachment system:      | Mounting bracket  |

|                       |   |
|-----------------------|---|
| Display type:         | Monochrome OLED display                                 |
| Theft protection:     | KENSINGTON LOCK   |
| Dimensions:           | Width: 11.1 cm<br>Depth: 7.8 cm<br>Height: 17.5 cm      |
| Weight:               | 1.35 kg   |
| Noise classification: | Class 0 (no noise at all)                               |
| Battery:              | 1 x button cell 3.0 V CR2032 lithium manganese built-in |
| Special product:      | Not designed for household room illumination            |
| Intended use:         | Show effect lighting                                    |

#### **ROADINGER Flightcase 4x AKKU Dot 1 RGB/WW QuickDMX**

|                          |   |
|--------------------------|---|
| Aluminum profile frames: | 20 mm   |
| Case handle:             | 1 pc/pcs  |
| Stop hinge:              | 2 pc/pcs  |
| Lock:                    | Butterfly lock: 2 pc/pcs                        |
| Transport aid:           | Rubber feet                                     |
| Material:                | Birch multiplex                                 |
| Color:                   | Black; dark brown, laminated                    |
| Accessory compartment:   | 9.8 cm x 25.5 cm x 7 cm                         |
| Inside dimensions:       | 30.5 cm x 52 cm x 15 cm                         |
| Device compartment:      | 14.5 cm x 11.5 cm x 12 cm                       |
| Material thickness:      | 7 mm  |
| Dimensions:              | Width: 33.2 cm<br>Depth: 55 cm<br>Height: 22 cm |
| Weight:                  | 5.80 kg   |

#### **EUROLITE Charger 4x Akku Flat Light Series**

|                   |  |
|-------------------|--|
| Power supply:     | 100-240 V AC, 50/60 Hz<br>12.6V DC 6000 mA   |
| Power connection: | Mains input via C8 (M) "figure 8" mounting version power supply cord with Euro plug (provided) |
| Power output:     | 4 x coaxial power connector (F)  |
| Weight:           | 0.49 kg  |

#### **Scope of delivery:**

##### **4 x EUROLITE AKKU Dot 1 RGB/WW QuickDMX bk**

- 1 x spotlight
- 1 x user manual
- 1 x external mains adapter
- 1 x declaration of conformity
- 1 x frost filter
- 1 x remote control
- 1 x battery
- 1 x power cord

**1 x EUROLITE Charger 4x Akku Flat Light Series**

- 1 x charger
- 1 x power cord
- 1 x adapter cable