

EUROLITE Set 4x LED IP PAR 3x9W SCL Spot + Case

Art. No.: 20000845

GTIN: 4026397690613



List price: 1284.01 €

incl. 19% VAT.

Features:

EUROLITE LED IP PAR 3x9W SCL Spot

Weather-proof (IP65) spotlight with 3 x 9 W LED and 7in1 SCL RGB/CW/WW/A/UV color mixing

- 3 powerful LEDs 9 W 7in1 SCL RGB/CW/WW/A/UV (homogenous color mix)
- Direct color selection for 28 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; IR remote control; DMX
- Preprogrammed in Light´J; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3
- Flicker-free
- With a beam angle of 15°
- With double bracket
- LCD display
- Suitable for outdoor use IP65
- For application areas such as: Installation; stage; rental; architecture
- Silent operation
- Application possibility: On stand; suspended

Package contents

- 1 x device, 1 x user manual, 1 x power cord, 1 x remote control, 1 x battery

Logistic

EAN / GTIN: 4026397690613

Weight: 24,00 kg

Length: 1.20 m

Width: 0.60 m

Height: 0.60 m

Bulky product

ROADINGER Flightcase 4x LED IP PAR 3x8W QCL/3x9W SCL

Trunk case, PRO version

- High-quality workmanship with birch multiplex 6,5 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 25mm with rounded edges
- 2 hinged, chromium plated case handles

- 2 chrome tip-over locks
- 1 high-quality butterfly lock
- Branded hardware
- Made in Europe

Technical specifications:

Weight:	21,10 kg
---------	----------

EUROLITE LED IP PAR 3x9W SCL Spot

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	35 W
IP classification:	IP65
Protection class:	Protection class I
Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug (provided)
Power output:	IP T-Con (F) mounting version
LED type:	3 x 9 W 7in1 SCL RGB/CW/WW/A/UV (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	3; 5; 7; 9; 13
DMX input:	3-pin XLR (M) mounting version IP
DMX output:	3-pin XLR (F) mounting version IP
Cooling:	Passive convection cooling
Control:	Stand-alone; IR remote control; DMX
Preprogrammed in:	Light´J; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3
Projection:	Flicker-free
Beam angle:	15°
Beam angle (1/2 peak):	15°
Beam angle (1/10 peak):	30°
Housing color:	Black
Attachment system:	Double bracket
Display type:	LCD display
Dimensions:	Width: 21,5 cm Depth: 17,1 cm Height: 24,4 cm
Weight:	3,00 kg
Noise classification:	Class 0 (no noise at all)
Photobiological safety:	Risk Group 0
Remote control	
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in

Legal specifications

Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 4x LED IP PAR 3x8W QCL/3x9W SCL

Maximum load:	50 kg
Aluminum profile frames:	25 mm
Case handle:	2 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 1 pc/pcs
Use of brands:	Branded hardware
Material:	Birch multiplex, 6,5 mm
Color:	Dark brown, laminated
Inside dimensions:	48 cm x 47 cm x 28 cm
Device compartment:	17 cm x 22,5 cm x 27 cm
Accessory compartment:	11,5 cm x 46,5 cm x 28 cm
Dimensions:	Length: 53 cm Width: 52 cm Height: 33 cm
Weight:	9,10 kg