

# **EUROLITE Set LED SL-160 Search Light + Case with wheels**

Art. No.: 20000848 GTIN: 4026397690651







List price: 1962.31 €

incl. 19% VAT.

#### Features:

#### **EUROLITE LED SL-160 Search Light**

Follow spot with cold white 160 W LED for small to medium distances

- Comfortable control via control panel with buttons and faders
- 1 powerful LED 160 W COB (chip-on-board) cold white (CW)
- Focus manual; iris stepless
- Dimmer electronic; CTO correction filter adjustable
- Strobe effect
- Color wheel with 5 dichroic filters plus open
- The device is cooled by cooling fan
- Control via stand-alone
- With a beam angle of 10°
- With mounting bracket
- Suitable for a range of use from to 20 meters
- For application areas such as: Wedding/gala/events; stage; theater; rental
- Application possibility: Suspended; on stand

#### Package contents

- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x mounting bracket, 1 x hex key

#### ROADINGER Flightcase 1x LED SL-350/SL-160 with wheels

- , dark brown, laminated
- Interior with foam padding<BR>cover with foam padding
- Aluminum profile frames 25mm with rounded edges
- 4 hinged, chromium plated case handles

#### Logistic

EAN / GTIN: 4026397690651

Weight: 27,00 kg Length: 1.20 m Width: 0.80 m Heigth: 0.50 m Bulky product

- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- 4 x castors with 2 locking brakes
- Branded hardware

# **Technical specifications:**

Weight: 23,55 kg

## **EUROLITE LED SL-160 Search Light**

Power consumption:         230 W           IP classification:         IP20           Power connection:         Mains input via PowerCON (blue), mounting version power supply cord with safety plug (provided)           Lamp type:         LED lamp           LED type:         1 x 160 W COB (chip-on-board) cold white (CW)           Equipment:         Focus manual; iris stepless           Color generation:         Color wheel with 5 dichroic filters plus open           Cooling:         Cooling fan           Control:         Stand-alone           Beam angle:         10°           Beam angle (1/2 peak):         10°           Color temperature:         3200K; 4500K; 5600K           Housing color:         Black matte           Attachment system:         Mounting bracket           Material:         Aluminum casting; metal           Range of use:         - 20m           Dimensions:         Length: 60 cm Width: 27,5 cm Height: 31,5 cm           Weight:         9,85 kg           Noise classification:         Class 2 (slight noise)           Power cord         Class 2 (slight noise)           Cable length:         Approx. 1,4 m           Mounting bracket         Aluminum casting, 4 mm           Diameter mounting holes:         3 x Ø13mm; 2	Power supply:	100-240 V AC, 50/60 Hz
Power connection:  Mains input via PowerCON (blue), mounting version power supply cord with safety plug (provided)  Lamp type:  LED lamp  LED type:  1 x 160 W COB (chip-on-board) cold white (CW)  Equipment:  Focus manual; iris stepless  Color generation:  Color wheel with 5 dichroic filters plus open  Cooling:  Cooling fan  Control:  Stand-alone  Beam angle:  10°  Beam angle:  10°  Color temperature:  3200K; 4500K; 5600K  Housing color:  Black matte  Attachment system:  Mounting bracket  Material:  Aluminum casting; metal  Range of use:  - 20m  Dimensions:  Length: 60 cm Width: 27,5 cm Height: 31,5 cm  Weight:  9,85 kg  Noise classification:  Class 2 (slight noise)  Power cord  Cable construction:  3 x 1,5 mm² H05VV-F  Cable length:  Approx. 1,4 m  Mounting bracket  Diameter mounting holes:  3 x Ø13mm; 2 x Ø16mm  Material:  Aluminum casting, 4 mm  Color:  Black, matte  Hex key  Material:  Steel	Power consumption:	230 W
Lamp type:         LED lamp           LED type:         1 x 160 W COB (chip-on-board) cold white (CW)           Equipment:         Focus manual; iris stepless           Color generation:         Color wheel with 5 dichroic filters plus open           Cooling:         Cooling fan           Control:         Stand-alone           Beam angle:         10°           Beam angle (1/2 peak):         10°           Color temperature:         3200K; 4500K; 5600K           Housing color:         Black matte           Attachment system:         Mounting bracket           Material:         Aluminum casting; metal           Range of use:         - 20m           Dimensions:         Length: 60 cm           Width: 27,5 cm         Height: 31,5 cm           Weight:         9,85 kg           Noise classification:         Class 2 (slight noise)           Power cord         Cable construction:         3 x 1,5 mm² H05VV-F           Cable length:         Approx. 1,4 m           Mounting bracket         Diameter mounting holes:         3 x Ø13mm; 2 x Ø16mm           Material:         Aluminum casting, 4 mm           Color:         Black, matte           Hex key	IP classification:	IP20
LED type:         1 x 160 W COB (chip-on-board) cold white (CW)           Equipment:         Focus manual; iris stepless           Color generation:         Color wheel with 5 dichroic filters plus open           Cooling:         Cooling fan           Control:         Stand-alone           Beam angle:         10°           Beam angle (1/2 peak):         10°           Color temperature:         3200K; 4500K; 5600K           Housing color:         Black matte           Attachment system:         Mounting bracket           Material:         Aluminum casting; metal           Range of use:         - 20m           Dimensions:         Length: 60 cm           Width: 27,5 cm         Width: 27,5 cm           Height: 31,5 cm         Weight:           Weight:         9,85 kg           Noise classification:         Class 2 (slight noise)           Power cord         Cable construction:         3 x 1,5 mm² H05VV-F           Cable length:         Approx. 1,4 m           Mounting bracket         Diameter mounting holes:         3 x Ø13mm; 2 x Ø16mm           Material:         Aluminum casting, 4 mm           Color:         Black, matte	Power connection:	version power supply cord with safety plug
Equipment:  Color generation:  Cooling:  Cooling:  Cooling fan  Control:  Stand-alone  Beam angle:  10°  Beam angle:  10°  Color temperature:  3200K; 4500K; 5600K  Housing color:  Black matte  Attachment system:  Mounting bracket  Material:  Aluminum casting; metal  Range of use:  - 20m  Dimensions:  Length: 60 cm Width: 27,5 cm Height: 31,5 cm  Weight:  9,85 kg  Noise classification:  Class 2 (slight noise)  Power cord  Cable construction:  3 x 1,5 mm² H05VV-F  Cable length:  Approx. 1,4 m  Mounting bracket  Diameter mounting holes:  3 x Ø13mm; 2 x Ø16mm  Material:  Aluminum casting, 4 mm  Color:  Black, matte  Hex key  Material:  Steel	Lamp type:	LED lamp
Color generation:  Cooling: Cooling: Cooling fan  Control: Stand-alone  Beam angle: 10°  Beam angle (1/2 peak): 10°  Color temperature: 3200K; 4500K; 5600K  Housing color: Black matte  Attachment system: Mounting bracket  Material: Aluminum casting; metal  Range of use: -20m  Dimensions: Length: 60 cm Width: 27,5 cm Height: 31,5 cm  Weight: 9,85 kg  Noise classification: Class 2 (slight noise)  Power cord  Cable construction: 3 x 1,5 mm² H05VV-F  Cable length: Approx. 1,4 m  Mounting bracket  Diameter mounting holes: 3 x Ø13mm; 2 x Ø16mm  Material: Aluminum casting, 4 mm  Color: Black, matte  Steel	LED type:	1 x 160 W COB (chip-on-board) cold white (CW)
Cooling:         Cooling fan           Control:         Stand-alone           Beam angle:         10°           Beam angle (1/2 peak):         10°           Color temperature:         3200K; 4500K; 5600K           Housing color:         Black matte           Attachment system:         Mounting bracket           Material:         Aluminum casting; metal           Range of use:         - 20m           Dimensions:         Length: 60 cm Width: 27,5 cm Height: 31,5 cm           Weight:         9,85 kg           Noise classification:         Class 2 (slight noise)           Power cord         Cable construction:         3 x 1,5 mm² H05VV-F           Cable length:         Approx. 1,4 m           Mounting bracket         Diameter mounting holes:         3 x Ø13mm; 2 x Ø16mm           Material:         Aluminum casting, 4 mm           Color:         Black, matte           Hex key           Material:         Steel	Equipment:	Focus manual; iris stepless
Control:         Stand-alone           Beam angle:         10°           Beam angle (1/2 peak):         10°           Color temperature:         3200K; 4500K; 5600K           Housing color:         Black matte           Attachment system:         Mounting bracket           Material:         Aluminum casting; metal           Range of use:         - 20m           Dimensions:         Length: 60 cm           Width: 27,5 cm         Height: 31,5 cm           Weight:         9,85 kg           Noise classification:         Class 2 (slight noise)           Power cord         Cable construction:         3 x 1,5 mm² H05VV-F           Cable length:         Approx. 1,4 m           Mounting bracket         Diameter mounting holes:         3 x Ø13mm; 2 x Ø16mm           Material:         Aluminum casting, 4 mm           Color:         Black, matte           Hex key           Material:         Steel	Color generation:	Color wheel with 5 dichroic filters plus open
Beam angle   10°	Cooling:	Cooling fan
Beam angle (1/2 peak):  Color temperature:  3200K; 4500K; 5600K  Housing color:  Black matte  Attachment system:  Mounting bracket  Material:  Aluminum casting; metal  Range of use:  - 20m  Dimensions:  Length: 60 cm Width: 27,5 cm Height: 31,5 cm  Weight:  9,85 kg  Noise classification:  Class 2 (slight noise)  Power cord  Cable construction:  3 x 1,5 mm² H05VV-F  Cable length:  Approx. 1,4 m  Mounting bracket  Diameter mounting holes:  3 x Ø13mm; 2 x Ø16mm  Material:  Aluminum casting, 4 mm  Color:  Black, matte  Hex key  Material:  Steel	Control:	Stand-alone
Color temperature:  3200K; 4500K; 5600K  Housing color:  Black matte  Attachment system:  Mounting bracket  Material:  Aluminum casting; metal  Range of use:  -20m  Dimensions:  Length: 60 cm Width: 27,5 cm Height: 31,5 cm  Weight:  9,85 kg  Noise classification:  Class 2 (slight noise)  Power cord  Cable construction:  3 x 1,5 mm² H05VV-F  Cable length:  Approx. 1,4 m  Mounting bracket  Diameter mounting holes:  3 x Ø13mm; 2 x Ø16mm  Material:  Aluminum casting, 4 mm  Color:  Black, matte  Hex key  Material:  Steel	Beam angle:	10°
Housing color:  Attachment system:  Mounting bracket  Material:  Aluminum casting; metal  Range of use:  - 20m  Dimensions:  Length: 60 cm Width: 27,5 cm Height: 31,5 cm  Weight:  9,85 kg  Noise classification:  Class 2 (slight noise)  Power cord  Cable construction:  3 x 1,5 mm² H05VV-F  Cable length:  Approx. 1,4 m  Mounting bracket  Diameter mounting holes:  3 x Ø13mm; 2 x Ø16mm  Material:  Aluminum casting, 4 mm  Color:  Black, matte  Hex key  Material:  Steel	Beam angle (1/2 peak):	10°
Attachment system:  Material:  Aluminum casting; metal  Range of use:  - 20m  Dimensions:  Length: 60 cm Width: 27,5 cm Height: 31,5 cm  Weight:  9,85 kg  Noise classification:  Class 2 (slight noise)  Power cord  Cable construction:  3 x 1,5 mm² H05VV-F  Cable length:  Approx. 1,4 m  Mounting bracket  Diameter mounting holes:  3 x Ø13mm; 2 x Ø16mm  Material:  Aluminum casting, 4 mm  Color:  Black, matte  Hex key  Material:  Steel	Color temperature:	3200K; 4500K; 5600K
Material:  Range of use:  - 20m  Dimensions:  Length: 60 cm Width: 27,5 cm Height: 31,5 cm  Weight:  9,85 kg  Noise classification:  Class 2 (slight noise)  Power cord  Cable construction:  3 x 1,5 mm² H05VV-F  Cable length:  Approx. 1,4 m  Mounting bracket  Diameter mounting holes:  3 x Ø13mm; 2 x Ø16mm  Material:  Aluminum casting, 4 mm  Color:  Black, matte  Hex key  Material:  Steel	Housing color:	Black matte
Range of use:  - 20m  Dimensions:  Length: 60 cm Width: 27,5 cm Height: 31,5 cm  Weight:  9,85 kg  Noise classification:  Class 2 (slight noise)  Power cord  Cable construction:  3 x 1,5 mm² H05VV-F  Cable length:  Approx. 1,4 m  Mounting bracket  Diameter mounting holes:  3 x Ø13mm; 2 x Ø16mm  Material:  Aluminum casting, 4 mm  Color:  Black, matte  Hex key  Material:  Steel	Attachment system:	Mounting bracket
Dimensions:  Length: 60 cm Width: 27,5 cm Height: 31,5 cm  Weight:  9,85 kg  Noise classification:  Class 2 (slight noise)  Power cord  Cable construction:  3 x 1,5 mm² H05VV-F  Cable length:  Approx. 1,4 m  Mounting bracket  Diameter mounting holes:  3 x Ø13mm; 2 x Ø16mm  Material:  Aluminum casting, 4 mm  Color:  Black, matte  Hex key  Material:  Steel	Material:	Aluminum casting; metal
Width: 27,5 cm Height: 31,5 cm  Weight: 9,85 kg  Noise classification: Class 2 (slight noise)  Power cord  Cable construction: 3 x 1,5 mm² H05VV-F  Cable length: Approx. 1,4 m  Mounting bracket  Diameter mounting holes: 3 x Ø13mm; 2 x Ø16mm  Material: Aluminum casting, 4 mm  Color: Black, matte  Hex key  Material: Steel	Range of use:	- 20m
Noise classification:  Class 2 (slight noise)  Power cord  Cable construction:  3 x 1,5 mm² H05VV-F  Cable length:  Approx. 1,4 m  Mounting bracket  Diameter mounting holes:  3 x Ø13mm; 2 x Ø16mm  Material:  Aluminum casting, 4 mm  Color:  Black, matte  Hex key  Material:  Steel	Dimensions:	Width: 27,5 cm
Power cord  Cable construction: 3 x 1,5 mm² H05VV-F  Cable length: Approx. 1,4 m  Mounting bracket  Diameter mounting holes: 3 x Ø13mm; 2 x Ø16mm  Material: Aluminum casting, 4 mm  Color: Black, matte  Hex key  Material: Steel	Weight:	9,85 kg
Cable construction:  3 x 1,5 mm² H05VV-F  Cable length:  Approx. 1,4 m  Mounting bracket  Diameter mounting holes:  3 x Ø13mm; 2 x Ø16mm  Material:  Aluminum casting, 4 mm  Color:  Black, matte  Hex key  Material:  Steel	Noise classification:	Class 2 (slight noise)
Cable length:  Mounting bracket  Diameter mounting holes:  3 x Ø13mm; 2 x Ø16mm  Material:  Aluminum casting, 4 mm  Color:  Black, matte  Hex key  Material:  Steel	Power cord	
Mounting bracket  Diameter mounting holes: 3 x Ø13mm; 2 x Ø16mm  Material: Aluminum casting, 4 mm  Color: Black, matte  Hex key  Material: Steel	Cable construction:	3 x 1,5 mm² H05VV-F
Diameter mounting holes:  3 x Ø13mm; 2 x Ø16mm  Material:  Aluminum casting, 4 mm  Color:  Black, matte  Hex key  Material:  Steel	Cable length:	Approx. 1,4 m
Material:  Color:  Black, matte  Hex key  Material:  Steel	Mounting bracket	
Color: Black, matte  Hex key  Material: Steel	Diameter mounting holes:	3 x Ø13mm; 2 x Ø16mm
Hex key  Material: Steel	Material:	Aluminum casting, 4 mm
Material: Steel	Color:	Black, matte
	Hex key	
Color: Silver	Material:	Steel
	Color:	Silver

Dimensions:	Length: 8,5 cm
	Width: 0,6 cm
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

## ROADINGER Flightcase 1x LED SL-350/SL-160 with wheels

Maximum load:	50 kg
Aluminum profile frames:	25 mm
Case handle:	4 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Transport aid:	4 x castors with 2 locking brakes
Use of brands:	Branded hardware
Color:	Dark brown, laminated
Inside dimensions:	60 cm x 34 cm x 25,5 cm
Device compartment:	60 cm x 19 cm x 25,5 cm
Dimensions:	Length: 69,5 cm
	Width: 35,5 cm
	Height: 47 cm
Weight:	13,70 kg