



Features:

EUROLITE LED 7C-7 Silent Slim Spot

Silent 7in1 LED PAR spotlight in a space-saving design

- Flat version requires minimal space when mounting
- 7 LEDs 9 W high-power 7in1 RGB/CW/WW/A/UV (homogenous color mix)
- Color blend stepless; Dimmer electronic
- Strobe effect
- Integrated show programs
- Direct color selection for 27 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; IR remote control; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Fixtures available for LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3
- Flicker-free
- With a beam angle of 15°
- Very high color rendering index (CRI)
- With double bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Stage; clubs/dancing school; wedding/gala/events; mobile djs / entertainer; party room; restaurants, bars and hotels; theater; rental; advertisement/Shop window
- Silent operation
- Application possibility: Standing; suspended; on stand

Logistic

EAN / GTIN: 4026397691009

Weight: 21,00 kg

Length: 1.20 m

Width: 0.80 m

Height: 0.60 m

Bulky product

EUROLITE QuickDMX USB Wireless Transmitter/Receiver

Wireless miniature DMX transceiver 2.4 GHz, phantom powered

- User-friendly USB plug with swivel antenna
- Wireless DMX eliminates extensive cabling between DMX controller and the DMX-controlled units in lighting installations
- Due to GFSK modulation with 78 channels, interference-free operation also alongside other QuickDMX transceiver and wireless devices in the 2.4 GHz band (e.g. Wi-Fi and Bluetooth)
- LED indication for functions
- Transceiver, to be used as transmitter or receiver
- Requires 5 V phantom power for operation
- Can receive and process up to 512 DMX channels
- Can transmit up to 512 DMX channels
- Control via DMX; QuickDMX; plug and play
- Operating range up to 400m with line-of-sight
- Up to 6 transmitters can be operated in parallel without interference

ROADINGER Flightcase 4x SLS Size M

Trunk case, PRO version

- Individually adjustable and removable dividers for universal use
- With 4 device compartments
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 30mm with rounded edges
- Hinged, chromium plated case handle
- 2 chrome tip-over locks
- 1 high-quality butterfly lock
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight: 18.11 kg

EUROLITE LED 7C-7 Silent Slim Spot

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	45 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x P-Con (gray), mounting version
Fuse:	5 x 20 mm, T 1 A fuse replaceable
Lamp type:	LED lamp
LED type:	7 x 9 W high-power 7in1 RGB/CW/WW/A/UV (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	3; 4-1; 4-2; 4-3; 4-4; 5; 6; 7; 9; 12
DMX input:	1 x 3-pin XLR (M) mounting version

DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; IR remote control; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Fixtures available for:	LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3
Projection:	Flicker-free
Beam angle (1/2 peak):	15°
Beam angle (1/10 peak):	33°
Color rendering index (CRI):	92 Ra
Housing color:	Black matte
Attachment system:	Double bracket
Display type:	4 digit 7-segment LED display
USB port:	Type A
Material:	Aluminum casting; metal
Dimensions:	Width: 22 cm Depth: 11 cm Height: 25.5 cm
Weight:	2.60 kg
Noise classification:	Class 0 (no noise at all)
Photobiological safety:	Risk Group 0
Diameter mounting holes:	1 x Ø11mm
Material:	Metal, 2.5 mm
Cable construction:	3 x 1.0 mm ² H05VV-F
Cable length:	Approx. 1.2 m
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE QuickDMX USB Wireless Transmitter/Receiver

Power supply:	5V DC
IP classification:	IP20
Power connection:	Mains input via USB A (M) connectable version
DMX channels:	Input 512 Output 512
DMX output:	1 x USB, type A
Control:	DMX; QuickDMX; plug and play
Range:	Range up to 400m with line-of-sight
Carrier frequency:	2.4 GHz
Parallel mode:	Max. 6 transmitter
RF power output:	19 dBm
Modulation:	GFSK

Color:	Black
Dimensions:	Width: 8.6 cm Depth: 4 cm Height: 1.1 cm
Weight:	0.01 kg

ROADINGER Flightcase 4x SLS Size M

Maximum load:	25 kg
Aluminum profile frames:	30 mm
Case handle:	1 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 1 pc/pcs
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Compartment dimensions:	12 cm x 25 cm x 35.5 cm
Inside dimensions:	49.5 cm x 25 cm x 35.5 cm
Dimensions:	Width: 52.5 cm Depth: 28.5 cm Height: 44.5 cm
Weight:	7.65 kg

Scope of delivery:

4 x EUROLITE LED 7C-7 Silent Slim Spot

- 1 x light effect
- 1 x power cord
- 1 x remote control
- 1 x user manual

4 x EUROLITE QuickDMX USB Wireless Transmitter/Receiver

- 1 x device
- 1 x user manual
- 1 x declaration of conformity