

EUROLITE Set 2x LED KLS Laser Bar PRO + Easy Show + 2x M-4 Speaker System Stand

GTIN: 4026397693812



List price: 1486.31 €

incl. 19% VAT.

Features:

EUROLITE LED KLS Laser Bar PRO FX Light Set

Bar with 2 strong derbies and spots, white/UV strobe LEDs, laser (RG, 2M)

- Enhanced version with very high brightness and additional UV LEDs
 - Compact lightweight
 - Crossbar with integrated DMX control unit and stand sleeve
 - 2 laser diodes project hundreds of red and green laser beams
 - 2 rotating derbies for mirror ball effects
 - When fog is used, this effect becomes especially attractive
 - Laser; multi beam effect; flower effect; UV effect; strobe effect
 - 39 integrated show programs
 - The device is cooled by cooling fan
 - Control via stand-alone; DMX; IR remote control; sound to light via microphone; wireless footswitch; master/slave function
 - Preprogrammed in EASY SHOW 1; Light´J; LED PC-Control 512; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
 - With mounting bracket
 - Mains input and output for power linking up to 8 units
 - For application areas such as: Wedding/gala/events; mobile use; clubs/dancing school; mobile djs / entertainer; rental
 - Application possibility: On stand
- laser**
- Laser class 2M
 does not require additional protective measures or appointment of a laser safety officer
- spotlight**
- 6 powerful LEDs 6 W SMD 8072 3in1 TCL RGB (homogenous color mix)
 spots controlled separately

Logistic

EAN / GTIN: 4026397693812

Weight: 36,00 kg

Length: 1.20 m

Width: 0.80 m

Height: 1.50 m

Bulky product

- With a beam angle of 13°
light effect
- 6 powerful LEDs 2 W SMD 8072 R/G/B
 spots controlled separately
bar
- 4 powerful LEDs 2 W SMD 8072 2in1 BCL CW/UV (homogenous color mix)
 LEDs controlled separately
Package contents
- 1 x device, 1 x power cord, 1 x user manual, 1 x declaration of conformity, 1 x remote control, 1 x foot control, 2 x knurled screw, 2 x washer, 2 x mounting bracket, 2 x battery, 1 x bag

EUROLITE EASY Show

Programmed DMX controller for over 200 spotlights from EUROLITE

- Easy-to-use DMX controller and DMX recorder
- Designed for DMX beginners with 200 programmed fixtures
- DMX recording function for your own projects, ideal for installations or rental companies
- Ideal for colored LED spotlights, KLS systems, moving lights and lighting effects
- No programming required, simply connect your spotlights and get started
- All spotlights can be freely combined to a show
- Data storage on USB flash drives
- A list of all preset devices is available at www.steinigke.de
- Program speed adjustable; color fade adjustable; Dimmer
- Strobe effect
- 24 integrated show programs
- Direct color selection for 12 preset colors
- Preprogrammed 24 scenes/chases and 12 cues
- Control via DMX; sound to light via microphone; QuickDMX via USB (optional)
- Monochrome LCD display
- Desktop console housing
- For application areas such as: Clubs/dancing school; party room; mobile djs / entertainer; restaurants, bars and hotels; installation
- Silent operation
Package contents
- 1 x controller, 1 x user manual, 1 x external mains adapter, 2 x USB cable, 2 x mounting bracket, 4 x screw

OMNITRONIC M-4 Speaker-System Stand

Aluminum speaker stand, height adjustable 140-345 cm, maximum load 18 kg

- Durable aluminum version
- Tube diameter: Ø 35 mm
- Adjustable height
Package contents
- 1 x user manual

Technical specifications:

Weight:	27,95 kg
---------	----------

EUROLITE LED KLS Laser Bar PRO FX Light Set

Power supply:	100-240 V AC, 50/60 Hz
---------------	------------------------

Power consumption:	150 W
--------------------	-------

IP classification:	IP20
--------------------	------

Protection class:	Protection class I
-------------------	--------------------

Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Fuse:	5 x 20 mm, T 3,15 A
Lamp type:	LED lamp
DMX channels:	3; 5; 10; 28
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; DMX; IR remote control; sound to light via microphone; wireless footswitch; master/slave function
Preprogrammed in:	EASY SHOW 1; Light`J; LED PC-Control 512; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
Housing color:	Black
Attachment system:	2x mounting bracket
Dimensions:	Width: 1,030 cm Depth: 6,1 cm Height: 38,7 cm
Weight:	10,00 kg
Noise classification:	Class 2 (slight noise)
Power cord	
Cable length:	3 m
Remote control	
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Foot control	
Battery:	1 x 9.0 V E block 6F22 zinc carbon included
Laser	
Laser class:	2M
Laser color:	R/G
Laser module:	Red (R) 100 mW 650nm Green (G) 30 mW 532nm
Light effect	
LED type:	6 x 2 W SMD 8072 R/G/B
Flash rate:	0 - 30 Hz
Spotlight	
LED type:	6 x 6 W SMD 8072 3in1 TCL RGB (homogenous color mix)
Beam angle:	13°
Beam angle (1/2 peak):	13°
Beam angle (1/10 peak):	20°
Bar	
LED type:	4 x 2 W SMD 8072 2in1 BCL CW/UV (homogenous color mix)
Flash rate:	0 - 30 Hz

EUROLITE EASY Show

Power supply:	100-240 V AC, 50/60 Hz 5V DC 250 mA
Power consumption:	1,25 W
IP classification:	IP20
Power connection:	Mains input via USB C (W) mounting version power supply cord with AC adapter
Programs:	Preprogrammed 24 scenes/chases and 12 cues
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Control:	DMX; sound to light via microphone; QuickDMX via USB (optional)
Housing color:	Black
Display type:	Monochrome LCD display
Available storage media:	USB devices
Housing design:	Desktop console housing
Dimensions:	Width: 28,0 cm Depth: 14,5 cm Height: 6,0 cm
Weight:	1,35 kg
Noise classification:	Class 0 (no noise at all)

OMNITRONIC M-4 Speaker-System Stand

Maximum carrying capacity:	18 kg
Tube diameter sector:	38 - 35 mm
Height:	Maximum: 345 cm Minimum: 140 cm Adjustable in 10 steps with locking pin
Attachment system:	Ø 35mm
Type (general stands):	Speaker stand/manual
Material:	Aluminum
Color:	Black
Transport dimensions:	140 cm x 13,5 cm
Weight:	3,30 kg