



### Features:

#### EUROLITE LED IP PAR 7x8W QCL Spot

Weather-proof (IP65) spotlight with 7 x 8 W LED and 4in1 QCL RGBW color mixing

- 7 LEDs 8 W high-power 4in1 QCL RGBW (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect
- Direct color selection for 25 preset colors
- The device is cooled by passive convection cooling
- Control via DMX; stand-alone; IR remote control
- Fixtures available for LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
- Flicker-free
- With a beam angle of 15°
- With double bracket
- LCD display
- Mains input and output for power linking up to 8 units
- Suitable for outdoor use IP65
- With pressure compensation membrane
- For application areas such as: Architecture; stage; clubs/dancing school; wedding/gala/events; theater; rental; video and photography
- Silent operation
- Application possibility: Standing; suspended; on stand

### Logistic

EAN / GTIN: 4026397694178

Weight: 38,00 kg

Length: 1.20 m

Width: 0.80 m

Height: 0.50 m

Bulky product

#### ROADINGER Flightcase 4x LED IP PAR 7x8W QCL/7x9W SCL with wheels

Trunk case with castors, PRO version

- With 4 device compartments
- With 1 accessory compartment
- Interior with foam padding
- Aluminum profile frames 25mm with rounded edges
- 4 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- 4 x castors with 2 locking brakes
- 4 x built-in stacking trays in the cover
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

## Technical specifications:

---

Weight: 34.03 kg

---

### EUROLITE LED IP PAR 7x8W QCL Spot

|                         |  |
|-------------------------|--|
| Power supply:           | 100-240 V AC, 50/60 Hz   |
| Power consumption:      | 55 W   |
| IP classification:      | IP65   |
| Power connection:       | Mains input via IP T-Con (M) mounting version power supply cord with safety plug   |
| Power output:           | IP T-Con (F) mounting version  |
| Lamp type:              | LED lamp   |
| LED type:               | 7 x 8 W high-power 4in1 QCL RGBW (homogenous color mix)  |
| Flash rate:             | 0 - 20 Hz  |
| DMX channels:           | 3; 4; 5; 6; 10   |
| DMX input:              | 1 x 3-pin XLR (M) mounting version IP  |
| DMX output:             | 1 x 3-pin XLR (F) mounting version IP  |
| Cooling:                | Passive convection cooling   |
| Control:                | DMX; stand-alone; IR remote control  |
| Fixtures available for: | LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief |
| Projection:             | Flicker-free   |
| Beam angle:             | 15°  |
| Beam angle (1/2 peak):  | 15°  |
| Housing color:          | Black  |
| Attachment system:      | Double bracket   |
| Display type:           | LCD display  |
| Material:               | Aluminum casting   |
| Dimensions:             | Width: 25.5 cm<br>Depth: 15.3 cm<br>Height: 28.1 cm  |

---

|                          |   |
|--------------------------|---|
| Weight:                  | 4.07 kg   |
| Noise classification:    | Class 0 (no noise at all)                               |
| Photobiological safety:  | Risk Group 0  |
| Diameter mounting holes: | 3 x Ø11mm   |
| Material:                | Metal, 2.5 mm   |
| Cable construction:      | 3 x 1.0 mm <sup>2</sup> H05RN-F                         |
| Cable length:            | Approx. 1.2 m   |
| Battery:                 | 1 x button cell 3.0 V CR2025 lithium manganese built-in |
| Special product:         | Not designed for household room illumination            |
| Intended use:            | Show effect lighting                                    |

#### **ROADINGER Flightcase 4x LED IP PAR 7x8W QCL/7x9W SCL with wheels**

|                          |   |
|--------------------------|---|
| Maximum load:            | 100 kg  |
| Aluminum profile frames: | 25 mm   |
| Case handle:             | 4 pc/pcs  |
| Stop hinge:              | 2 pc/pcs  |
| Lock:                    | Butterfly lock: 2 pc/pcs  |
| Transport aid:           | 4 x castors with 2 locking brakes<br>4 x built-in stacking trays in the cover |
| Use of brands:           | Branded hardware  |
| Material:                | Birch multiplex   |
| Color:                   | Dark brown, laminated   |
| Device compartment:      | 21.5 cm x 22.5 cm x 29 cm   |
| Accessory compartment:   | 10 cm x 50 cm x 29 cm   |
| Inside dimensions:       | 53 cm x 50 cm x 29 cm   |
| Material thickness:      | 6.5 mm  |
| Dimensions:              | Width: 62.50 cm<br>Depth: 53.50 cm<br>Height: 51.50 cm                        |
| Weight:                  | 17.75 kg  |

#### **Scope of delivery:**

- 1 x light effect
- 1 x mounting bracket
- 1 x power cord
- 1 x remote control
- 1 x user manual