



Features:

EUROLITE LED IP PAR 7x9W SCL Spot

Weather-proof (IP65) spotlight with 7 x 9 W LED and 7in1 RGB/CW/WW/A/UV color mixing

- 7 LEDs 9 W high-power 7in1 RGB/CW/WW/A/UV (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect
- Direct color selection for 28 preset colors
- The device is cooled by passive convection cooling
- Control via DMX; stand-alone; IR remote control
- Flicker-free
- With a beam angle of 15°
- With double bracket
- LCD display
- Mains input and output for power linking up to 8 units
- Suitable for outdoor use IP65
- For application areas such as: Architecture; stage; clubs/dancing school; wedding/gala/events; theater; rental; video and photography
- Silent operation
- Application possibility: Standing; suspended; on stand

Logistic

EAN / GTIN: 4026397694185

Weight: 380,00 kg

Length: 1.20 m

Width: 0.80 m

Height: 0.50 m

Bulky product

ROADINGER Flightcase 4x LED IP PAR 7x8W QCL/7x9W SCL with wheels

Trunk case with castors, PRO version

- With 4 device compartments
- With 1 accessory compartment
- Interior with foam padding

- Aluminum profile frames 25mm with rounded edges
- 4 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- 4 x castors with 2 locking brakes
- 4 x built-in stacking trays in the cover
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight: 34.03 kg

EUROLITE LED IP PAR 7x9W SCL Spot

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	55 W
IP classification:	IP65
Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug
Power output:	IP T-Con (F) mounting version
Lamp type:	LED lamp
LED type:	7 x 9 W high-power 7in1 RGB/CW/WW/A/UV (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	3; 5; 7; 9; 13
DMX input:	1 x 3-pin XLR (M) mounting version IP
DMX output:	1 x 3-pin XLR (F) mounting version IP
Cooling:	Passive convection cooling
Control:	DMX; stand-alone; IR remote control
Fixtures available for:	LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3
Projection:	Flicker-free
Beam angle (1/2 peak):	15°
Housing color:	Black matte
Attachment system:	Double bracket
Display type:	LCD display
Material:	Aluminum casting
Dimensions:	Width: 25.5 cm Depth: 15.3 cm Height: 28.1 cm
Weight:	4.07 kg
Noise classification:	Class 0 (no noise at all)
Photobiological safety:	Risk Group 0
Diameter mounting holes:	3 x Ø11mm
Material:	Metal, 2.5 mm

Cable construction:	3 x 1.0 mm ² H05RN-F
Cable length:	Approx. 1.2 m
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 4x LED IP PAR 7x8W QCL/7x9W SCL with wheels

Maximum load:	100 kg
Aluminum profile frames:	25 mm
Case handle:	4 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Transport aid:	4 x castors with 2 locking brakes 4 x built-in stacking trays in the cover
Use of brands:	Branded hardware
Material:	Birch multiplex
Color:	Dark brown, laminated
Device compartment:	21.5 cm x 22.5 cm x 29 cm
Accessory compartment:	10 cm x 50 cm x 29 cm
Inside dimensions:	53 cm x 50 cm x 29 cm
Material thickness:	6.5 mm
Dimensions:	Width: 62.50 cm Depth: 53.50 cm Height: 51.50 cm
Weight:	17.75 kg

Scope of delivery:

1 x spotlight
1 x power cord
1 x remote control
1 x user manual