



The article is no longer in our assortment.

Features:

EUROLITE LED PIX-12 HCL Bar

LED bar (100cm) with 12 x 10 watt 6in1 HCL RGBWA/UV LED

- 12 powerful LEDs 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)
 LEDs controlled separately
- Color blend stepless; color change adjustable; Dimmer electronic
- Strobe effect; UV effect
- The device is cooled by cooling fan
- Control via stand-alone; DMX; sound to light via microphone; master/slave function; IR remote control
- Preprogrammed in Light´J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3
- Flicker-free
- With a beam angle of 20°
- With mounting bracket
- Mains input and output for power linking up to 8 units

Package contents

- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x remote control, 1 x battery

Logistic

EAN / GTIN: 4026397694963

Weight: 53,00 kg

Length: 1.20 m

Width: 0.80 m

Height: 0.80 m

Bulky product

ROADINGER Flightcase 4x LED IP T-PIX 8 QCL/T-PIX 12 HCL with wheels

Trunk case with castors, PRO version

- ,
- Interior with foam padding
- Aluminum profile frames 25mm with rounded edges
- 4 hinged, chromium plated case handles

- 3 chrome tip-over locks
- 2 high-quality butterfly locks
- 4 x castors with 2 locking brakes
- Branded hardware
- European engineering
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight:	45,60 kg
---------	----------

EUROLITE LED PIX-12 HCL Bar

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	60 W
IP classification:	IP20
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	IEC connector (F) mounting version
Fuse:	T 2 A fuse replaceable
Lamp type:	LED lamp
LED type:	12 x 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)
DMX channels:	4; 6; 16; 36; 74
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; DMX; sound to light via microphone; master/slave function; IR remote control
Preprogrammed in:	Light´J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3
Projection:	Flicker-free
Beam angle:	20°
Beam angle (1/2 peak):	20°
Beam angle (1/10 peak):	41°
Housing color:	Black
Attachment system:	Mounting bracket
Dimensions:	Length: 100 cm Depth: 11,5 cm Height: 16,5 cm
Weight:	5,20 kg
Photobiological safety:	Risk Group 0
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in

Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 4x LED IP T-PIX 8 QCL/T-PIX 12 HCL with wheels

Maximum load:	100 kg
Aluminum profile frames:	25 mm
Case handle:	4 pc/pcs
Stop hinge:	3 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Transport aid:	4 x castors with 2 locking brakes
Use of brands:	Branded hardware
Device compartment:	100 cm x 12 cm x 17 cm
Accessory compartment:	102 cm x 10,5 cm x 17 cm
Dimensions:	Length: 106 cm Width: 74 cm Height: 40 cm
Weight:	24,80 kg