



The article is no longer in our assortment.

Features:

EUROLITE LED Strip 300 5m RGBWW 24V

Flexible LED strip with RGB and warm white LEDs

- Flexible LED strip for decorative lighting
- High-grade components and a solid construction guarantee a long service life and excellent color rendering
- Can be cut into segments of variable size
- Self-adhesive rear side
- Supplied on a plastic reel
- Power cable, straight and flexible plug connectors available as accessories
- 300 powerful LEDs SMD 5050 4in1 QCL RGB/WW (homogenous color mix)
- Control via system controller
- Good color rendering index (CRI)
- For application areas such as: Trade fair and shop fitting; clubs/dancing school; installation; restaurants, bars and hotels
- Silent operation

Package contents

- 1 x illuminant, 1 x user manual

Logistic

EAN / GTIN: 4026397695007

Weight: 1,50 kg

Length: 0.30 m

Width: 0.22 m

Heigh: 0.21 m

EUROLITE LED Strip 4in1 Zone RF Controller

4-channel wireless LED controller with remote control for RGB/W and dual white

- User-friendly LED controller with 4 zones (4 x 6A) and remote control
- Controls single- and multi-colored (CW+WW, RGB, RGBW) LED strips (12-24 V) as desired
- Innovative wireless technology allows multiple controllers to be controlled synchronously and asynchronously with just one remote control

- Synchronous color sequences even over several hours with multiple controllers and different LED types
- Excellent signal transmission with 2.4 GHz - no perceptible difference to a wired system
- All controllers communicate with each other and cover a large range
- No visible contact between remote control and controller required
- Any number of controllers possible in 4 zones
- Color selection via touch-sensitive color wheel
- Memory function saves last setting when switching off
- Program speed adjustable; Dimmer electronic
- 8 integrated show programs
- remote control**
- Operating range up to 20m
- Package contents**
- 1 x controller, 1 x remote control, 1 x user manual, 2 x battery, 1 x declaration of conformity, 1 x holder, 4 x screw

EUROLITE Electronic Transformer, 24V, 5A, IP67

Stabilized LED power supply unit DC 24 V, 5 A

- Input voltage AC 100-240 V
- Noise filter
- Suitable for outdoor use IP67

Package contents

- 1 x external mains adapter

Technical specifications:

| | |
|---------|---------|
| Weight: | 0,91 kg |
|---------|---------|

EUROLITE LED Strip 300 5m RGBWW 24V

| | |
|------------------------------|--|
| Power supply: | 24V DC |
| Power consumption: | 67 W |
| IP classification: | IP20 |
| Protection class: | Protection class III |
| Power connection: | Fixed supply cord with open wires |
| Cable length: | Approx. 0,15 m |
| LED type: | 300 x SMD 5050 4in1 QCL RGB/WW (homogenous color mix) |
| Control: | System controller |
| Standing/fixation: | Self adhesive |
| Color rendering index (CRI): | 82 Ra |
| Lamps/meter: | 60 pc/pcs |
| Power/meter: | 13,4 W |
| Lamps/tube: | 300 pc/pcs |
| Lamp distance: | 16 mm |
| Cutting mark: | 10 cm |
| Housing color: | White |
| Dimensions: | Length: 500 cm Width: 1,2 cm Height: 0,2 cm |

| | |
|----------------------------------|---------------------------|
| Weight: | 0,15 kg |
| Noise classification: | Class 0 (no noise at all) |
| Energy efficiency class (A - G): | G |

EUROLITE LED Strip 4in1 Zone RF Controller

| | |
|--------------------|---|
| Weight: | 0,19 kg |
| Power supply: | 12/24V DC |
| Power consumption: | Max. 576 W 24 V DC 144 W 24 V DC per channel Max. 288 W 12 V DC 72 W 12 V DC per channel |
| Output current: | Max. 4 x 6 A per channel |
| Power connection: | Via screw terminal |
| Power output: | Screw terminal |
| Carrier frequency: | 2,4 GHz |
| Dimensions: | Length: 16 cm Width: 4,6 cm Height: 2,5 cm |
| Weight: | 0,19 kg |
| Battery: | 2 x 1.5 V AAA Micro LR03 alkaline manganese included |
| Range: | Range up to 20m |
| Dimensions: | Length: 16,4 cm Width: 4,5 cm Height: 2,6 cm |
| Weight: | 0,1 kg |

EUROLITE Electronic Transformer, 24V, 5A, IP67

| | |
|--------------------|--|
| Power supply: | 100-240 V AC, 50/60 Hz |
| IP classification: | IP67 |
| Protection class: | Protection class II |
| Power connection: | Fixed supply cord with open wires |
| Cable length: | Approx. 0,2 m |
| Power output: | No connector/cable only |
| Housing color: | White matte |
| Controls: | Overload; short-circuit; overheat |
| Output: | 24 V DC, stabilized; 5 A; |
| Material: | Plastic |
| Dimensions: | Length: 20 cm Width: 5,2 cm Height: 3,7 cm |
| Weight: | 0,58 kg |