

EUROLITE Set Multiflood Pro IP RGBW Wash MK2 + Diffusor Cover 40° + Barndoor

GTIN: 4026397698664



List price: 1248.31 €

incl. 19% VAT.

Features:

EUROLITE Multiflood Pro IP RGBW Wash MK2

Bright outdoor spot with RGBW LEDs and W-DMX

- Integrated W-DMX transceiver for wireless DMX Control
- 36 powerful LEDs 8 W high-power 4in1 QCL RGBW (homogenous color mix)
4 segments controlled separately
- Wash effect; strobe effect
- Direct color selection for 27 preset colors
- The device is cooled by low-noise cooling fan
- Control via stand-alone; IR remote control; DMX; W-DMX by wireless solution; master/slave function; wired remote control
- Preprogrammed in Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Light´J; Colorchief
- With a beam angle of 14°
- With omega bracket
- OLED display
- Rubber feet
- Mains input and output for power linking up to 8 units
- Suitable for outdoor use
- For application areas such as: Installation; stage; rental; architecture
- Very quiet working noise
- Application possibility: Standing; suspended

Package contents

- 1 x device, 1 x user manual, 1 x power cord, 1 x remote control, 1 x battery, 1 x omega bracket

Logistic

EAN / GTIN: 4026397698664

Weight: 14,20 kg

Length: 0.00 m

Width: 0.00 m

Heigh: 0.00 m

EUROLITE Diffuser Cover 40° for Multiflood Pro IP RGBW Wash MK2

Frost filter provides a soft, homogeneous light

- To set different beam angles (from 14° to approx. 40° or 15 x 60°)
- Package contents**
- 1 x frost filter

EUROLITE Barndoors for Multiflood Pro IP RGBW Wash MK2**Package contents**

- 1 x barndoor, 14 x screw

Technical specifications:

Weight:	14,42 kg
---------	----------

EUROLITE Multiflood Pro IP RGBW Wash MK2

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	230 W
IP classification:	IP65
LED type:	36 x 8 W high-power 4in1 QCL RGBW (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	3; 4; 6; 9; 10; 16; 26
DMX input:	3-pin XLR (M) mounting version IP
DMX output:	3-pin XLR (F) mounting version IP
Cooling:	Low-noise cooling fan
Control:	Stand-alone; IR remote control; DMX; W-DMX by wireless solution; master/slave function; wired remote control
Preprogrammed in:	Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Light J; Colorchief
Carrier frequency:	2,4 GHz
Beam angle:	14°
Beam angle (1/2 peak):	14°
Beam angle (1/10 peak):	30
Housing color:	Black
Attachment system:	Omega bracket
Display type:	OLED display
Transport aid:	Rubber feet
Dimensions:	Length: 51,35 cm Depth: 18,10 cm Height: 33,90 cm
Weight:	12,75 kg
Noise classification:	Class 1 (very slight noise, suitable for noise-sensitive environments)

Remote control	
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE Diffuser Cover 40° for Multiflood Pro IP RGBW Wash MK2

Dimensions:	Length: 46,3 cm
	Width: 23,2 cm
	Depth: 0,6 cm
Weight:	0,37 kg

EUROLITE Barndoors for Multiflood Pro IP RGBW Wash MK2

Color:	Black
Dimensions:	Length: 50,0 cm
	Width: 27,0 cm
	Depth: 2,5 cm
Weight:	1,30 kg