



Features:

- Positioning within
- <p>EUROLITE LED TSL-1000 Scan MK2
- <h2 class="featureSatz">Scanner with 100 W LED, rotating gobos, 3-facet prism, color wheel and motorized focus</h2>Note: The macro programs of the predecessor model (no. 51786122) are not identical, therefore no synchronous master/slave operation is possible between these devices.
- 1 LED 100 W COB (chip-on-board) cold white (CW)
- Positioning within 160° PAN, 50° TILT
- Exact positioning (16 bit resolution)
- Focus motor-driven; color wheel; gobo wheel with rotating gobos; prism 3-fold
- Dimmer electronic
- Gobo effect; strobe effect
- Color wheel with 8 dichroic filters plus open
half colors selectable, Rainbow effect with adjustable speed in both directions
- Gobo wheel with rotating gobos, 7 gobos and open
shake effect
- Gobos changeable
- Slot-in gobo system for easy gobo replacement
- Integrated show programs
- The device is cooled by cooling fan
- Control via stand-alone; DMX; master/slave function; sound to light via microphone
- Flicker-free
- With a beam angle of 20°
- OLED display
- Rubber feet
- Mains input and output for power linking up to 8 units

Logistic

EAN / GTIN: 4026397705683

Weight: 25,00 kg

Length: 0.00 m

Width: 0.00 m

Heigh: 0.00 m

- For application areas such as: Clubs/dancing school; wedding/gala/events; mobile djs / entertainer; stage; restaurants, bars and hotels
- Application possibility: Standing; suspended; on stand
- safety eyelet**
- M6 thread
- <p>ROADINGER Flightcase 2x LED TSL-1000 with trolley function
- <h2 class="featureSatz">Trolley case, PRO version</h2>High-quality workmanship with birch multiplex 6.5 mm,
- Interior with foam padding
- Aluminum profile frames 25mm with rounded edges
- 3 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- Trolley
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight: 21.60 kg

EUROLITE LED TSL-1000 Scan MK2

| | |
|---------------------|---|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 110 W |
| Protection class: | Protection class I |
| Power connection: | Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided) |
| Power output: | P-Con (gray), mounting version |
| Fuse: | 5 x 20 mm, T 4 A fuse replaceable |
| Lamp type: | LED lamp |
| LED type: | 1 x 100 W COB (chip-on-board) cold white (CW) |
| Max. TILT movement: | 50° exact positioning (16 bit resolution) |
| Max. PAN movement: | 160° exact positioning (16 bit resolution) |
| Flash rate: | 1 - 25 Hz |
| Equipment: | Focus motor-driven; color wheel; gobo wheel with rotating gobos; prism 3-fold |
| Color generation: | Color wheel with 8 dichroic filters plus open Half colors selectable, Rainbow effect with adjustable speed in both directions |
| Gobos: | Gobo wheel with rotating gobos, 7 gobos and open Outside diameter 23.9mm Image diameter 18mm Shake effect Gobos changeable Slot-in gobo system for easy gobo replacement |
| DMX channels: | 10; 15 |
| DMX input: | 3-pin XLR (M) mounting version |
| DMX output: | 3-pin XLR (F) mounting version |

| | |
|--------------------------|--|
| Cooling: | Cooling fan |
| Control: | Stand-alone; DMX; master/slave function; sound to light via microphone |
| Fixtures available for: | Light´J; Light Captain; EASY SHOW 2; EASY SHOW 3 |
| Projection: | Flicker-free |
| Beam angle (1/2 peak): | 20° |
| Color temperature: | 8000K |
| Illuminance in Lux (lx): | Cold white (CW) 1m: 35679 lx, 3m: 4265 lx, 6m: 1055 lx |
| Housing color: | Black |
| Display type: | OLED display |
| Transport aid: | Rubber feet |
| Material: | Metal; plastic |
| Dimensions: | Width: 25.1 cm Depth: 14.1 cm Height: 37.7 cm |
| Weight: | 5.75 kg |
| Noise classification: | Class 2 (slight noise) |
| Cable construction: | 3 x 1.0 mm ² H05VV-F |
| Cable length: | Approx. 1.5 m |
| Diameter mounting holes: | 3 x Ø10mm |
| Material: | Metal, 3 mm |
| Material: | Metal |
| Ring diameter: | Outside: 23 mm Inside: 11 mm |
| Thread: | M6 thread |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |

ROADINGER Flightcase 2x LED TSL-1000 with trolley function

| | |
|--------------------------|---------------------------|
| Maximum load: | 25 kg |
| Aluminum profile frames: | 25 mm |
| Case handle: | 3 pc/pcs |
| Stop hinge: | 2 pc/pcs |
| Lock: | Butterfly lock: 2 pc/pcs |
| Transport aid: | Trolley |
| Use of brands: | Branded hardware |
| Material: | Birch multiplex, 6.5 mm |
| Accessory compartment: | 44 cm x 7 cm x 13 cm |
| Device compartment: | 36 cm x 25.5 cm x 13 cm |
| Inside dimensions: | 86.5 cm x 32.5 cm x 13 cm |
| Weight: | 10.10 kg |

Scope of delivery:

- 1 x light effect
- 1 x power cord
- 1 x safety eyelet
- 1 x user manual