

## EUROLITE Set 2x LED PLL-480 QCL Panel + Case

Art. No.: 20000932

GTIN: 4026397694598



**List price: 2021.81 €**

incl. 19% VAT.

### Features:

#### EUROLITE LED PLL-480 QCL Panel

DMX-controlled surface light with 480 4in1 RGBW LEDs

- Frost filter provides a soft, homogeneous light
- 4 barn doors to avoid blinding the audience and for protection during transport
- Slim, rugged metal housing
- Stand or truss installation
- 480 powerful LEDs SMD 5050 4in1 QCL RGBW (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; pulse-width modulation variable
- Strobe effect
- The device is cooled by passive convection cooling
- Control via DMX; stand-alone; master/slave function
- Preprogrammed in Light J; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3
- Flicker-free
- With a beam angle of 120°
- With mounting bracket
- LCD display
- Rugged carrying handle
- Mains input and output for power linking up to 8 units
- Silent operation
- For application areas such as: Video and photography; stage; theater; advertisement/Shop window
- Application possibility: Suspended; on stand

#### Package contents

- 1 x spotlight, 1 x power cord, 1 x plug (male), 1 x user manual

### Logistic

EAN / GTIN: 4026397694598

Weight: 41,00 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

ROADINGER Flightcase 2x LED PLL-480

- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Branded hardware

Technical specifications:

|         |          |
|---------|----------|
| Weight: | 37,50 kg |
|---------|----------|

EUROLITE LED PLL-480 QCL Panel

|                          |                                                                                                                                                                                                                                        |
|--------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Power supply:            | 100-240 V AC, 50/60 Hz                                                                                                                                                                                                                 |
| Power consumption:       | 205 W                                                                                                                                                                                                                                  |
| IP classification:       | IP20                                                                                                                                                                                                                                   |
| Protection class:        | Protection class I                                                                                                                                                                                                                     |
| Power connection:        | Mains input via P-Con (blue), mounting version<br>power supply cord with safety plug (provided)                                                                                                                                        |
| Power output:            | P-Con (gray), mounting version                                                                                                                                                                                                         |
| Fuse:                    | T 6,3 A fuse fix in power supply                                                                                                                                                                                                       |
| Lamp type:               | LED lamp                                                                                                                                                                                                                               |
| LED type:                | 480 x SMD 5050 4in1 QCL RGBW (homogenous<br>color mix)                                                                                                                                                                                 |
| Flash rate:              | 1 - 19 Hz                                                                                                                                                                                                                              |
| DMX channels:            | 6; 4                                                                                                                                                                                                                                   |
| DMX input:               | 3-pin XLR (M) mounting version                                                                                                                                                                                                         |
| DMX output:              | 3-pin XLR (F) mounting version                                                                                                                                                                                                         |
| Cooling:                 | Passive convection cooling                                                                                                                                                                                                             |
| Control:                 | DMX; stand-alone; master/slave function                                                                                                                                                                                                |
| Preprogrammed in:        | Light´J; Light Captain; EASY SHOW 1; EASY<br>SHOW 2; EASY SHOW 3                                                                                                                                                                       |
| Projection:              | Flicker-free                                                                                                                                                                                                                           |
| Beam angle:              | 120°                                                                                                                                                                                                                                   |
| Beam angle (1/2 peak):   | 120°                                                                                                                                                                                                                                   |
| Illuminance in Lux (lx): | Red (R) 1m: 438 lx, 3m: 61 lx, 6m: 18 lx<br>Green (G) 1m: 633 lx, 3m: 88 lx, 6m: 25 lx<br>Blue (B) 1m: 209 lx, 3m: 29 lx, 6m: 8 lx<br>Cold white (CW) 1m: 2130 lx, 3m: 296 lx, 6m: 87<br>lx<br>All 1m: 2696 lx, 3m: 380 lx, 6m: 112 lx |
| Lamp life:               | 50000 h                                                                                                                                                                                                                                |
| Luminous flux:           | 17103 lm                                                                                                                                                                                                                               |
| Housing color:           | Black                                                                                                                                                                                                                                  |
| Attachment system:       | Mounting bracket                                                                                                                                                                                                                       |
| Display type:            | LCD display                                                                                                                                                                                                                            |

|                                  |                                                 |
|----------------------------------|-------------------------------------------------|
| Carrying handle:                 | 1 pc/pcs                                        |
| Material:                        | Metal; aluminum casting                         |
| Dimensions:                      | Width: 64 cm<br>Depth: 13 cm<br>Height: 33,5 cm |
| Weight:                          | 12,60 kg                                        |
| Noise classification:            | Class 0 (no noise at all)                       |
| Energy efficiency class (A - G): | F                                               |
| EPREL-Nr:                        | 1243720                                         |
| Mounting bracket                 |                                                 |
| Diameter mounting holes:         | 3 x Ø12mm                                       |
| Material:                        | Metal, 3 mm                                     |
| Barndoor                         |                                                 |
| Material:                        | Metal, 1,5 mm                                   |

#### **ROADINGER Flightcase 2x LED PLL-480**

|                        |                                                |
|------------------------|------------------------------------------------|
| Maximum load:          | 50 kg                                          |
| Use of brands:         | Branded hardware                               |
| Material:              | Birch multiplex, 7 mm                          |
| Color:                 | Dark brown, laminated                          |
| Inside dimensions:     | 64 cm x 38,5 cm x 29 cm                        |
| Device compartment:    | 64 cm x 14 cm x 29 cm                          |
| Accessory compartment: | 64 cm x 10,5 cm x 29 cm                        |
| Dimensions:            | Length: 70 cm<br>Width: 47 cm<br>Height: 39 cm |
| Weight:                | 12,30 kg                                       |