



Features:

EUROLITE LED TMH-X4 Moving Head Wash Zoom wh

Washlight with 19 intense 15 W 4in1 LEDs, motorized zoom and white housing

- 19 LEDs 15 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix)
3 segments controlled separately
- Positioning within 630° PAN, 270° TILT
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Zoom motor driven
- Color blend stepless; color change adjustable; Dimmer electronic
- Strobe effect
- Integrated show programs
- The device is cooled by temperature-controlled fan at the head; cooling fan at the base
- Control via stand-alone; DMX; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Fixtures available for Light´J; LED PC-Control 512; EASY SHOW 1; Light Captain; GDTF (GrandMA3)
- Flicker-free
- With a beam angle of 1° - 40°
- Multicolor LCD display
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; wedding/gala/events; stage; mobile djs / entertainer; rental; restaurants, bars and hotels
- Application possibility: Standing; suspended

Logistic

EAN / GTIN: 4026397716382

Weight: 33,00 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

Bulky product

ROADINGER Flightcase PRO 2x LED TMH-X4

Trunk case, PRO version

- For optimal security
- With 1 accessory compartment
- High-quality workmanship with birch multiplex 7 mm, black, laminated
- Interior with foam padding
- Aluminum profile frames 30mm with rounded edges
- 2 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- Branded hardware
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight: 28.64 kg

EUROLITE LED TMH-X4 Moving Head Wash Zoom wh

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	225 W
IP classification:	IP20
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug
Power output:	P-Con (gray), mounting version
Fuse:	5 x 20 mm, T 2 A fuse replaceable
Lamp type:	LED lamp
LED type:	19 x 15 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix)
Max. TILT movement:	270° exact positioning (16 bit resolution) auto position correction (feedback)
Max. PAN movement:	630° exact positioning (16 bit resolution) auto position correction (feedback)
Equipment:	Zoom motor driven
DMX channels:	16; 24
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan at the head Cooling fan at the base
Control:	Stand-alone; DMX; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Fixtures available for:	Light J; LED PC-Control 512; EASY SHOW 1; Light Captain; GDTF (GrandMA3)
Projection:	Flicker-free
Beam angle:	1° - 40°

Beam angle (1/2 peak):	1 - 25°
Beam angle (1/10 peak):	8 - 40°
Illuminance in Lux (lx):	Narrow red (R) 3m: 2779 lx, 6m: 763 lx Narrow green (G) 3m: 7893 lx, 6m: 1841 lx Narrow blue (B) 3m: 1468 lx, 6m: 390 lx Narrow cold white (CW) 3m: 9558 lx, 6m: 2468 lx Narrow all 3m: 19553 lx, 6m: 5001 lx Wide red (R) 3m: 272 lx, 6m: 73 lx Wide green (G) 3m: 583 lx, 6m: 160 lx Wide blue (B) 3m: 117 lx, 6m: 34 lx Wide cold white (CW) 3m: 740 lx, 6m: 211 lx Wide all 3m: 1568 lx, 6m: 439 lx
Housing color:	White
Display type:	Multicolor LCD display
Dimensions:	Width: 30.5 cm Depth: 20.0 cm Height: 40.0 cm
Weight:	8.62 kg
Noise classification:	Class 3 (clearly perceptible sounds)
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase PRO 2x LED TMH-X4

Maximum load:	50 kg
Aluminum profile frames:	30 mm
Case handle:	2 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm; birch multiplex
Color:	Black, laminated; dark brown, laminated
Inside dimensions:	58 cm x 33.5 cm
Device compartment:	24 cm x 23 cm x 33.5 cm
Middle compartment:	10 cm x
Dimensions:	Width: 72 cm Depth: 46 cm Height: 41 cm
Weight:	11.40 kg

Scope of delivery:

1 x moving light
1 x user manual
1 x power cord
2 x omega bracket