



Features:

EUROLITE LED Silent Par 6 QCL floor bk

LED floor spot with RGB/WW color mixing

- 14350 lux at 1 m
- 6 LEDs 8 W 4in1 QCL RGB/WW (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; Dimmer speed (step response) adjustable
- Strobe effect
- Direct color selection for 25 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; QuickDMX via USB (optional); master/slave function; sound to light via microphone
- Fixtures available for Light´J; Light Captain; Colorchief
- Flicker-free
- With a beam angle of 16°
- With double bracket; with mounting bracket
- 4 digit 7-segment LED display
- For application areas such as: Stage; clubs/dancing school; decoration; wedding/gala/events; mobile djs / entertainer; party room; restaurants, bars and hotels; theater; advertisement/Shop window
- Silent operation
- Application possibility: Standing; suspended; on stand

Logistic

EAN / GTIN: 4026397728224

Weight: 20,00 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

ROADINGER Flightcase 4x SILENT PAR 6 QCL FLOOR

Trunk case, HIGHLINE version

- High-quality workmanship with birch multiplex 7 mm, black
- Interior with felt cover
cover with foam padding
- Aluminum profile frames 30mm with rounded edges
- 3 hinged, chromium plated case handles
- 4 x rubber feet
- Branded hardware
- Made in Europe

Technical specifications:

Weight: 17.20 kg

EUROLITE LED Silent Par 6 QCL floor bk

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	45 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug
Power output:	P-Con (gray), mounting version
Lamp type:	LED lamp
LED type:	6 x 8 W 4in1 QCL RGB/WW (homogenous color mix)
Flash rate:	1.5 - 30 Hz
DMX channels:	6; 11
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; QuickDMX via USB (optional); master/slave function; sound to light via microphone
Fixtures available for:	Light J; Light Captain; Colorchief
Projection:	Flicker-free
PWM frequency:	23500 Hz
Beam angle (1/2 peak):	16°
Beam angle (1/10 peak):	29°
Housing color:	Black
Attachment system:	Double bracket Mounting bracket
Display type:	4 digit 7-segment LED display
Dimensions:	Length: 14.3 cm Width: 17.7 cm Height: 21.1 cm
Weight:	2.15 kg
Noise classification:	Class 0 (no noise at all)
Cable construction:	3 x 1.0 mm ² H05VV-F

Cable length:	Approx. 1.2 m
Diameter mounting holes:	1 x Ø10mm
Material:	Metal, 1.5 mm
Cable length:	Approx. 2 m
Color:	Black
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 4x SILENT PAR 6 QCL FLOOR

Aluminum profile frames:	30 mm
Case handle:	3 pc/pcs
Transport aid:	4 x rubber feet
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm
Color:	Black
Device compartment:	15 cm x 14 cm x 20 cm
Accessory compartment:	11 cm x 30 cm x 21 cm
Inside dimensions:	44 cm x 30 cm x 21 cm
Dimensions:	Width: 48.5 cm Depth: 35 cm Height: 30 cm
Weight:	8.60 kg

Scope of delivery:

- 1 x spotlight
- 1 x power cord
- 1 x XLR cable
- 1 x user manual