



Features:

EUROLITE LED PIX-16 QCL Bar

LED light effect bar with 16 x 4 W RGBW LED (4in1), incl. IR remote control

- 16 LEDs 4 W COB (chip-on-board) 4in1 RGBW (homogenous color mix)
- Color animations with two adjustable colors
- Strobe effect
- 21 integrated show programs
- Direct color selection for 15 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; master/slave function; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); sound to light via microphone; IR remote control
- Flicker-free
- With a beam angle of 15°
- With mounting bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; decoration; wedding/gala/events; restaurants, bars and hotels; advertisement/Shop window
- Silent operation
- Application possibility: Suspended; wall mounting

EUROLITE SB-12 Soft Bag

Practical black soft bag for LED bars (1 m length), adjustable divider

- Ideal for 1 or 2 LED bars with 1 meter length

Logistic

EAN / GTIN: 4026397728415

Weight: 7,00 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

- Made of easy-care nylon
- With divider
- With 2 device compartments
- High-quality workmanship with textile , black
- Interior with foam padding
- 2 carrying straps
- 1 x shoulder strap

Technical specifications:

Weight: 5.38 kg

EUROLITE LED PIX-16 QCL Bar

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	70 W
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug
Power output:	P-Con (gray), mounting version
Fuse:	F 1 A fuse replaceable
Lamp type:	LED lamp
LED type:	16 x 4 W COB (chip-on-board) 4in1 RGBW (homogenous color mix)
DMX channels:	3; 4; 11; 21-1; 21-2; 64
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; master/slave function; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); sound to light via microphone; IR remote control
Fixtures available for:	Light J; Light Captain; Colorchief
Projection:	Flicker-free
Beam angle (1/2 peak):	15°
Beam angle (1/10 peak):	30°
Housing color:	Black
Attachment system:	2x mounting bracket
Display type:	4 digit 7-segment LED display
Dimensions:	Length: 108 cm Width: 6.5 cm Height: 8.5 cm
Weight:	2.39 kg
Noise classification:	Class 0 (no noise at all)
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in

Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE SB-12 Soft Bag

Maximum load:	20 kg
Carrying strap:	2 pc/pcs
Transport aid:	1 x shoulder strap
Material:	Textile
Color:	Black
Dimensions:	Width: 107 cm Depth: 17 cm Height: 18 cm
Weight:	0.60 kg

Scope of delivery:

- 1 x bar
- 1 x user manual
- 1 x power cord
- 1 x remote control
- 1 x battery
- 2 x mounting bracket
- 2 x screw
- 2 x washer