



List price: 355.81 €

incl. 19% VAT.

Features:

EUROLITE LED B-40 HCL Beam Effect MK2

LED beam effect with RGBWA+UV color mixing, incl. remote-control

- 5 powerful LEDs 10 W 6in1 HCL RGBWA/UV
 segments controlled separately
- Rotation speed adjustable; Dimmer electronic; color blend stepless
- Multi beam effect; strobe effect
- 8 integrated show programs
- The device is cooled by passive convection cooling
- Control via IR remote control; stand-alone; sound to light via microphone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); master/slave function
- Preprogrammed in Light´J; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
- With omega bracket
- Monochrome 4 digit 7-segment LED display
- For application areas such as: Clubs/dancing school; wedding/gala/events; mobile djs / entertainer; restaurants, bars and hotels
- Application possibility: Standing; suspended

Package contents

- 1 x light effect, 1 x power cord, 1 x omega bracket, 1 x remote control, 4 x screw, 4 x washer, 1 x user manual

Logistic

EAN / GTIN: 4026397728507

Weight: 7,00 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

EUROLITE SB-10 Soft Bag

Black soft bag with divider, 330 x 330 x 355 mm

- Practical transport bag offers enough space for several lighting effects and accessories
- With divider

- With Outside pocket
- High-quality workmanship with nylon , black, water repellent
- Interior with foam padding
- 2 Rugged carrying handles

Package contents

- 1 x bag

Technical specifications:

Weight:	4,69 kg
---------	---------

EUROLITE LED B-40 HCL Beam Effect MK2

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	56 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	IEC connector (F) mounting version
Fuse:	T 1,6 A fuse replaceable
Lamp type:	LED lamp
LED type:	5 x 10 W 6in1 HCL RGBWA/UV
Flash rate:	0 - 20 Hz
DMX channels:	3; 12; 23
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	IR remote control; stand-alone; sound to light via microphone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); master/slave function
Preprogrammed in:	Light´J; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
Housing color:	Black matte
Attachment system:	Omega bracket
Display type:	Monochrome 4 digit 7-segment LED display
Material:	Metal; plastic
Dimensions:	Length: 32,00 cm Width: 32,00 cm Height: 39,00 cm
Weight:	4,22 kg
Noise classification:	Class 2 (slight noise)
Power cord	
Cable construction:	3 x 1,0 mm² H05VV-F

Cable length:	Approx. 1,5 m
Omega bracket	
Diameter mounting holes:	1 x Ø13mm; 4 x Ø4mm
Material:	Metal, 3 mm
Remote control	
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE SB-10 Soft Bag

Maximum load:	25 kg
Carrying handle:	2 pc/pcs
Material:	Nylon
Color:	Black, water repellent
Dimensions:	Width: 33 cm Depth: 37 cm Height: 33 cm
Weight:	0,47 kg