



**List price: 3092.81 €**

incl. 19% VAT.

### Features:

#### EUROLITE LED PMB-8 COB QCL 30W Bar

LED light effect bar with RGBW color mixing, incl. IR remote control

- 8 powerful LEDs 30 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect
- Integrated show programs
- Direct color selection for 27 preset colors
- The device is cooled by low-noise cooling fan
- Control via stand-alone; IR remote control; DMX; master/slave function; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Preprogrammed in Light´J; Light Captain
- Flicker-free
- With a beam angle of 45°
- With mounting bracket
- LCD display
- Mains input and output for power linking up to 8 units
- For application areas such as: Wedding/gala/events; Trade fair and shop fitting; stage; theater; rental
- Very quiet working noise
- Application possibility: Standing; suspended; on stand

#### Package contents

- 1 x spotlight, 1 x power cord, 1 x remote control, 1 x battery, 1 x user manual

### Logistic

EAN / GTIN: 4026397527957

Weight: 67,00 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

Bulky product

ROADINGER Flightcase 4x LED PMB-8 COB QCL

Trunk case, PRO version

- High-quality workmanship with birch multiplex 9 mm, black, laminated
- Interior with foam padding
- Aluminum profile frames 30mm with rounded edges
- 4 hinged, chromium plated case handles
- 7 chrome tip-over locks
- 2 high-quality butterfly locks
- PENN Hardware
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

|         |          |
|---------|----------|
| Weight: | 58,80 kg |
|---------|----------|

EUROLITE LED PMB-8 COB QCL 30W Bar

|                         |   |
|-------------------------|---|
| Power supply:           | 100-240 V AC, 50/60 Hz  |
| Power consumption:      | 240 W   |
| IP classification:      | IP20  |
| Protection class:       | Protection class I  |
| Power connection:       | Mains input via P-Con (blue), mounting version<br>power supply cord with safety plug (provided)   |
| Power output:           | P-Con (gray), mounting version  |
| Fuse:                   | T 3 A fuse replaceable  |
| Lamp type:              | LED lamp  |
| LED type:               | 8 x 30 W COB (chip-on-board) 4in1 QCL RGBW<br>(homogenous color mix)  |
| Flash rate:             | 0 - 20 Hz   |
| DMX channels:           | 3; 4; 5; 6; 12; 32; 36  |
| DMX input:              | 3-pin XLR (M) mounting version  |
| DMX output:             | 3-pin XLR (F) mounting version  |
| Cooling:                | 2 x low-noise cooling fan   |
| Control:                | Stand-alone; IR remote control; DMX;<br>master/slave function; sound to light via<br>microphone; QuickDMX via USB (optional); W-<br>DMX by wireless solution via USB (optional);<br>CRMX by LumenRadio via USB (optional) |
| Preprogrammed in:       | Light´J; Light Captain  |
| Projection:             | Flicker-free  |
| Beam angle:             | 45°   |
| Beam angle (1/2 peak):  | 45°   |
| Beam angle (1/10 peak): | 74°   |
| Housing color:          | Black   |
| Attachment system:      | Mounting bracket  |
| Display type:           | LCD display   |

|                          |  |
|--------------------------|--|
| Material:                | Aluminum casting; metal  |
| Dimensions:              | Length: 98,0 cm<br>Depth: 16,3 cm<br>Height: 20,6 cm                   |
| Weight:                  | 8,65 kg  |
| Noise classification:    | Class 1 (very slight noise, suitable for noise-sensitive environments) |
| Photobiological safety:  | Risk Group 0   |
| Mounting bracket         |  |
| Diameter mounting holes: | 3 x Ø11mm; 3 x Ø10mm; 4 x Ø8mm; 2 x Ø6mm                               |
| Material:                | Metal, 2,5 mm  |
| Power cord               |  |
| Cable construction:      | 3 x 1,0 mm² H05VV-F  |
| Cable length:            | Approx. 1,2 m  |
| Remote control           |  |
| Battery:                 | Button cell 3.0 V CR2025 lithium manganese built-in                    |
| Legal specifications     |  |
| Special product:         | Not designed for household room illumination                           |
| Intended use:            | Show effect lighting   |

#### **ROADINGER Flightcase 4x LED PMB-8 COB QCL**

|                          |  |
|--------------------------|--|
| Maximum load:            | 100 kg   |
| Aluminum profile frames: | 30 mm  |
| Case handle:             | 4 pc/pcs   |
| Stop hinge:              | 7 pc/pcs   |
| Lock:                    | Butterfly lock: 2 pc/pcs                         |
| Use of brands:           | PENN Hardware                                    |
| Material:                | Birch multiplex, 9 mm                            |
| Color:                   | Black, laminated                                 |
| Device compartment:      | 99,5 cm x 12 cm x 26 cm                          |
| Accessory compartment:   | 10 cm x 71 cm x 28 cm                            |
| Dimensions:              | Width: 116 cm<br>Depth: 75 cm<br>Height: 32,5 cm |
| Weight:                  | 24,20 kg   |