



### Features:

#### EUROLITE LED TMH Bar S120 Moving Head Spots

LED lighting system with 4 individually controllable 30 W moving heads

- Crossbar with integrated DMX control unit and stand sleeve
- 4 LEDs 30 W COB (chip-on-board)
- Positioning within 540° PAN, 180° TILT
- Exact positioning (16 bit resolution)
- Gobo wheel with static gobos; focus manual; color wheel
- Dimmer electronic
- Strobe effect; beam effect
- Color wheel with 7 dichroic filters plus open-<BR>half colors selectable, Rainbow effect with adjustable speed
- Gobo wheel with static gobos, 7 gobos and open-<BR>shake effect
- The device is cooled by temperature-controlled fan
- Control via stand-alone; DMX; sound to light via microphone; master/slave function; QuickDMX via USB (optional); CRMX by LumenRadio via USB (optional); W-DMX by wireless solution via USB (optional)
- Fixtures available for Colorchief; Light´J; Light Captain
- Flicker-free
- With a beam angle of 13°
- With omega bracket
- 4 digit 7-segment LED display
- Rubber feet
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; wedding/gala/events; party room; mobile djs / entertainer; restaurants, bars and hotels
- Application possibility: Standing; suspended; on stand

### Logistic

EAN / GTIN: 4026397739435

Weight: 54,00 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

Bulky product

## ROADINGER Flightcase 2x LED TMH Bar-S120 with wheels

Trunk case with castors

- With 2 device compartments
- With 2 accessory compartments
- Interior with foam padding<BR>cover with foam padding
- Aluminum profile frames 30mm with rounded edges
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- 4 x castors with 2 locking brakes
- 4 x built-in stacking trays in the cover
- For further information about this product, please refer to the Data Sheet under "Downloads"

### Technical specifications:

---

Weight: 47.85 kg

---

### EUROLITE LED TMH Bar S120 Moving Head Spots

|                     |  |
|---------------------|--|
| Power supply:       | 100-240 V AC, 50/60 Hz   |
| Power consumption:  | 100 W  |
| IP classification:  | IP20   |
| Protection class:   | Protection class I   |
| Power connection:   | Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)               |
| Power output:       | P-Con (gray), mounting version   |
| Fuse:               | 5 x 20 mm, T 2 A fuse replaceable  |
| Lamp type:          | LED lamp   |
| LED type:           | 4 x 30 W COB (chip-on-board)   |
| Max. TILT movement: | 180° positioning; exact positioning (16 bit resolution)  |
| Max. PAN movement:  | 540° positioning; exact positioning (16 bit resolution)  |
| Flash rate:         | 2 - 14 Hz  |
| Equipment:          | Gobo wheel with static gobos; focus manual; color wheel  |
| Color generation:   | Color wheel with 7 dichroic filters plus open Half colors selectable, Rainbow effect with adjustable speed |
| Gobos:              | Gobo wheel with static gobos, 7 gobos and open Shake effect  |
| DMX channels:       | 3; 5; 9; 11; 17; 21; 30; 38  |
| DMX input:          | 3-pin XLR (M) mounting version   |
| DMX output:         | 3-pin XLR (F) mounting version   |
| Cooling:            | Temperature-controlled fan   |

|                          |   |
|--------------------------|---|
| Control:                 | Stand-alone; DMX; sound to light via microphone; master/slave function; QuickDMX via USB (optional); CRMX by LumenRadio via USB (optional); W-DMX by wireless solution via USB (optional) |
| Fixtures available for:  | Colorchief; Light´J; Light Captain  |
| Projection:              | Flicker-free  |
| PWM frequency:           | 11000 Hz  |
| Beam angle (1/2 peak):   | 13°   |
| Color temperature:       | 7300K   |
| Illuminance in Lux (lx): | Cold white (CW) 1m: 8899 lx, 3m: 856 lx, 6m: 205 lx   |
| Housing color:           | Black   |
| Attachment system:       | 2x omega bracket<br>Tube: Ø 35mm  |
| Display type:            | 4 digit 7-segment LED display   |
| Transport aid:           | Rubber feet   |
| Dimensions:              | Width: 100.0 cm<br>Depth: 17.5 cm<br>Height: 28.0 cm  |
| Weight:                  | 13.00 kg  |
| Noise classification:    | Class 3 (clearly perceptible sounds)  |
| Special product:         | Not designed for household room illumination  |
| Intended use:            | Show effect lighting  |

#### **ROADINGER Flightcase 2x LED TMH Bar-S120 with wheels**

|                          |   |
|--------------------------|---|
| Maximum load:            | 100 kg  |
| Aluminum profile frames: | 30 mm   |
| Stop hinge:              | 2 pc/pcs  |
| Lock:                    | Butterfly lock: 2 pc/pcs  |
| Transport aid:           | 4 x castors with 2 locking brakes<br>4 x built-in stacking trays in the cover |
| Material:                | Plywood multi-layer glued   |
| Color:                   | Black, laminated  |
| Device compartment:      | 100 cm x 14 cm x 30 cm  |
| Accessory compartment:   | 49.5 cm x 8 cm x 30 cm  |
| Inside dimensions:       | 100 cm x 40 cm x 30 cm  |
| Dimensions:              | Width: 106 cm<br>Depth: 45 cm<br>Height: 49 cm                                |
| Weight:                  | 21.85 kg  |

#### **Scope of delivery:**

1 x moving light  
1 x user manual  
1 x power cord  
2 x omega bracket  
2 x safety eyelet