

EUROLITE Set 4x AKKU Mini UP-4 QCL Spot MK2 + Soft bag

Art. No.: 20001031

GTIN: 4026397739510



List price: 534.31 €

incl. 19% VAT.

Features:

EUROLITE AKKU Mini UP-4 QCL Spot MK2

Mini battery-powered uplight with RGBW LEDs and IR remote control

- Cordless, flexible and versatile
- Battery operation up to 9h depending on program used
- Integrated automatic charging of the battery and status indicator
- 4 powerful LEDs 4 W 4in1 QCL RGBW (homogenous color mix)
- Color change adjustable; color fade adjustable; color blend stepless
- Strobe effect; uplight effect
- Direct color selection for 10 preset colors
- The device is cooled by passive convection cooling
- Control via IR remote control; stand-alone; sound to light via microphone
- Flicker-free
- With a beam angle of 18°
- 4 digit 7-segment LED display
- For application areas such as: Wedding/gala/events; mobile use; mobile djs / entertainer; small rental
- Silent operation
- Application possibility: Standing

Package contents

- 1 x device, 1 x user manual, 1 x remote control, 1 x battery, 1 x USB cable

Logistic

EAN / GTIN: 4026397739510

Weight: 4,50 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

EUROLITE Softbag for 4x AKKU Mini UP-4 QCL Spot MK2

Nylon transport bag

- With 4 device compartments

- With accessory compartment
- High-quality workmanship with nylon , black
- Interior with foam padding
- 2 carrying straps

Technical specifications:

Weight:	3,33 kg
---------	---------

EUROLITE AKKU Mini UP-4 QCL Spot MK2

Power supply:	5V
IP classification:	IP20
Protection class:	Protection class III
Power connection:	Battery/battery pack Mains input via USB C (W) mounting version
Battery pack type:	3 x lithium ion 3,6 V, 2600 mAh, 9,36 Wh
Battery pack:	Battery operation up to 9h depending on program used Recharging time 5h
Lamp type:	LED lamp
LED type:	4 x 4 W 4in1 QCL RGBW (homogenous color mix)
Flash rate:	1 - 28 Hz
Cooling:	Passive convection cooling
Control:	IR remote control; stand-alone; sound to light via microphone
Projection:	Flicker-free
PWM frequency:	15000 Hz
Beam angle:	18°
Beam angle (1/2 peak):	18°
Beam angle (1/10 peak):	38°
Housing color:	Black
Display type:	4 digit 7-segment LED display
Dimensions:	Length: 11 cm Width: 11 cm Height: 12 cm
Weight:	0,73 kg
Noise classification:	Class 0 (no noise at all)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE Softbag for 4x AKKU Mini UP-4 QCL Spot MK2

Carrying strap:	2 pc/pcs
-----------------	----------

Material:	Nylon, water repellent
Color:	Black
Device compartment:	11 cm x 11 cm x 8 cm
Dimensions:	Length: 35,5 cm Depth: 29 cm Height: 10 cm
Weight:	0,39 kg