



List price: 1605.31 €

incl. 19% VAT.

Features:

EUROLITE AKKU UP-4 QCL Spot QuickDMX MK2

Bright battery powered LED uplight with 10 W 4in1 LEDs and QuickDMX

- Integrated QuickDMX transceiver for wireless DMX control
- Cordless, flexible and versatile
- Battery operation up to 9h depending on program used
- Integrated automatic charging of the battery and status indicator
- 4 powerful LEDs 10 W SMD 5050 4in1 QCL RGBW (homogenous color mix)
- Dimmer electronic; Dimmer speed (step response) adjustable; color fade adjustable speed; color change adjustable speed; white balance adjustable; color blend adjustable; frost filter; color selection manual; program selection manual; pulse-width modulation; Energy-saving mode; Emergency lighting function in case of power failure
- Multi beam effect; spot effect; wash effect; strobe effect
- 36 integrated show programs
- Direct color selection for 15 preset colors
- The device is cooled by passive convection cooling
- Control via IR remote control; QuickDMX; DMX; stand-alone; sound to light via microphone; wireless Master/slave function; RDM
- Preprogrammed in Light Captain; Colorchief
- Flicker-free
- QuickDMX: operating range up to 600m in the open air
- Up to 6 transmitters can be operated in parallel without interference
- DMX fail mode (blackout; hold; static; full on)
- With a beam angle of 7°
- With bracket for floor use
- Monochrome OLED display
- Display of the remaining battery life for the current setting

Logistic

EAN / GTIN: 4026397710106

Weight: 19,00 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

- Charge status indicator
- Mains input and output for power linking up to 8 units
- With a KENSINGTON LOCK theft protection
- For application areas such as: Wedding/gala/events; mobile use; mobile djs / entertainer; rental
- Silent operation
- Application possibility: Standing; suspended
- 3 buttons on the remote control for saving your own settings

Package contents

- 1 x spotlight, 1 x user manual, 1 x declaration of conformity, 1 x power cord, 1 x remote control, 1 x battery, 1 x frost filter, 1 x knurled screw

ROADINGER Plastic Case for 4x AKKU UP-4 QCL Spot QuickDMX MK2

Carrying case

- With 4 device compartment
- High-quality workmanship with plastic , black
- Interior with foam padding
cover with foam padding
- Rugged carrying handle
- 4 high-quality spring locks with shut-off function
- 4 x plastic feet
- For application areas such as: Mobile use; rental; mobile djs / entertainer

Package contents

- 1 x case

Technical specifications:

| | |
|---------|----------|
| Weight: | 15,62 kg |
|---------|----------|

EUROLITE AKKU UP-4 QCL Spot QuickDMX MK2

| | |
|---------------------|---|
| Power supply: | 100-240 V AC, 50/60 Hz |
| IP classification: | IP20 |
| Protection class: | Protection class I |
| Power connection: | Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided) |
| Cable construction: | 3 x 1,0 mm² H05VV-F |
| Power output: | P-Con (gray), mounting version |
| Battery pack type: | 1 x lithium ion 14,8 V, 6600 mAh, 97,68 Wh |
| Battery pack: | Battery operation up to 9h depending on program used Recharging time 3h |
| Lamp type: | LED lamp |
| LED type: | 4 x 10 W SMD 5050 4in1 QCL RGBW (homogenous color mix) |
| Flash rate: | 27 Hz |
| DMX channels: | 3; 4; 6; 8; 11 |
| DMX input: | 3-pin XLR (M) mounting version |
| DMX output: | 3-pin XLR (F) mounting version |
| Cooling: | Passive convection cooling |
| Control: | IR remote control; QuickDMX; DMX; stand-alone; sound to light via microphone; wireless Master/slave function; RDM |

| | |
|-------------------------|---|
| Preprogrammed in: | Light Captain; Colorchief |
| Projection: | Flicker-free |
| PWM frequency: | 3000 Hz |
| Range: | QuickDMX: range up to 600m in the open air |
| Carrier frequency: | 2,4 GHz |
| Parallel mode: | Max. 6 transmitter |
| Modulation: | GFSK |
| DMX fail mode: | Blackout; hold; static; full on |
| Beam angle: | 7° |
| Beam angle (1/2 peak): | 7° Frost filter 20° |
| Beam angle (1/10 peak): | 18° Frost filter 42° |
| Attachment system: | Bracket for floor use |
| Display type: | Monochrome OLED display |
| Display: | Battery runtime calculation , charge status indicator |
| Material: | Metal, painted |
| Theft protection: | KENSINGTON LOCK |
| Dimensions: | Length: 15,4 cm Width: 13,3 cm Height: 15,8 cm |
| Weight: | 2,83 kg |
| Noise classification: | Class 0 (no noise at all) |
| Remote control | |
| Battery: | 1 x button cell 3.0 V CR2032 lithium manganese built-in |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |

ROADINGER Plastic Case for 4x AKKU UP-4 QCL Spot QuickDMX MK2

| | |
|------------------------|--|
| Maximum load: | 25 kg |
| Carrying handle: | 1 pc/pcs |
| Lock: | Spring lock: 4 pc/pcs with shut-off function |
| Transport aid: | 4 x plastic feet |
| Material: | Plastic |
| Color: | Black |
| Inside dimensions: | 49 cm x 36 cm x 13 cm |
| Device compartment: | 16 cm x 13,5 cm x 16 cm |
| Accessory compartment: | 8 cm x 30,5 cm x 16 cm |
| Dimensions: | Length: 55 cm Depth: 42,5 cm Height: 21 cm |
| Weight: | 4,30 kg |