



List price: 1426.81 €

incl. 19% VAT.

Features:

EUROLITE AKKU UP-4 QCL Spot QuickDMX MK2

Bright battery powered LED uplight with 10 W 4in1 LEDs and QuickDMX

- Integrated QuickDMX transceiver for wireless DMX control
- Cordless, flexible and versatile
- Battery operation up to 9h depending on program used
- Integrated automatic charging of the battery and status indicator
- 4 powerful LEDs 10 W SMD 5050 4in1 QCL RGBW (homogenous color mix)
- Dimmer electronic; Dimmer speed (step response) adjustable; color fade adjustable speed; color change adjustable speed; white balance adjustable; color blend adjustable; frost filter; color selection manual; program selection manual; pulse-width modulation; Energy-saving mode; Emergency lighting function in case of power failure
- Multi beam effect; spot effect; wash effect; strobe effect
- 36 integrated show programs
- Direct color selection for 15 preset colors
- The device is cooled by passive convection cooling
- Control via IR remote control; QuickDMX; DMX; stand-alone; sound to light via microphone; wireless Master/slave function; RDM
- Preprogrammed in Light Captain; Colorchief
- Flicker-free
- QuickDMX: operating range up to 600m in the open air
- Up to 6 transmitters can be operated in parallel without interference
- DMX fail mode (blackout; hold; static; full on)
- With a beam angle of 7°
- With bracket for floor use
- Monochrome OLED display
- Display of the remaining battery life for the current setting

Logistic

EAN / GTIN: 4026397603125

Weight: 14,00 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

- Charge status indicator
- Mains input and output for power linking up to 8 units
- With a KENSINGTON LOCK theft protection
- For application areas such as: Wedding/gala/events; mobile use; mobile djs / entertainer; rental
- Silent operation
- Application possibility: Standing; suspended
- 3 buttons on the remote control for saving your own settings

Package contents

- 1 x spotlight, 1 x user manual, 1 x declaration of conformity, 1 x power cord, 1 x remote control, 1 x battery, 1 x frost filter, 1 x knurled screw

EUROLITE SB-4 Soft Bag L

Black soft bag for up to 4 devices, 320 x 320 x 200 mm

- Practical transport bag offers enough space for several lighting effects and accessories
- With dividers
- With 2 Outside pockets
- With 4 device compartments
- High-quality workmanship with nylon , black, water repellent
- Interior with foam padding
cover with foam padding
- 2 carrying straps

Package contents

- 1 x bag

Technical specifications:

Weight:	12,93 kg
---------	----------

EUROLITE AKKU UP-4 QCL Spot QuickDMX MK2

Power supply:	100-240 V AC, 50/60 Hz
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Cable construction:	3 x 1,0 mm² H05VV-F
Power output:	P-Con (gray), mounting version
Battery pack type:	1 x lithium ion 14,8 V, 6600 mAh, 97,68 Wh
Battery pack:	Battery operation up to 9h depending on program used Recharging time 3h
Lamp type:	LED lamp
LED type:	4 x 10 W SMD 5050 4in1 QCL RGBW (homogenous color mix)
Flash rate:	27 Hz
DMX channels:	3; 4; 6; 8; 11
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	IR remote control; QuickDMX; DMX; stand-alone; sound to light via microphone; wireless Master/slave function; RDM

Preprogrammed in:	Light Captain; Colorchief
Projection:	Flicker-free
PWM frequency:	3000 Hz
Range:	QuickDMX: range up to 600m in the open air
Carrier frequency:	2,4 GHz
Parallel mode:	Max. 6 transmitter
Modulation:	GFSK
DMX fail mode:	Blackout; hold; static; full on
Beam angle:	7°
Beam angle (1/2 peak):	7° Frost filter 20°
Beam angle (1/10 peak):	18° Frost filter 42°
Attachment system:	Bracket for floor use
Display type:	Monochrome OLED display
Display:	Battery runtime calculation , charge status indicator
Material:	Metal, painted
Theft protection:	KENSINGTON LOCK
Dimensions:	Length: 15,4 cm Width: 13,3 cm Height: 15,8 cm
Weight:	2,83 kg
Noise classification:	Class 0 (no noise at all)
Remote control	
Battery:	1 x button cell 3.0 V CR2032 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE SB-4 Soft Bag L

Maximum load:	25 kg
Carrying strap:	2 pc/pcs
Material:	Nylon
Color:	Black, water repellent
Compartment dimensions:	15 cm x 15 cm x 20 cm
Inside dimensions:	31 cm x 34 cm x 20 cm
Dimensions:	Width: 32 cm Depth: 41 cm Height: 20 cm
Weight:	0,52 kg