



8x



Features:

EUROLITE AKKU IP Flat Light SMD bk

Flat IP65 spotlight in black with 81 x 0.2 W 4in1 QCL RGBW LED, QuickDMX transceiver

- Integrated QuickDMX transceiver for wireless DMX control
- Compact and bright
- Cordless, flexible and versatile
- Battery operation up to 16h depending on program used
- Integrated automatic charging of the battery and status indicator
- 81 LEDs 0.2 W SMD 5050 4in1 QCL RGBW (homogenous color mix)
- Dimmer speed (step response) adjustable; color selection manual; color change adjustable; color fade adjustable
- Strobe effect
- Direct color selection for 30 preset colors
- The device is cooled by passive convection cooling
- Control via master/slave function; IR remote control; QuickDMX; stand-alone; sound to light via microphone
- Fixtures available for Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Light´J; Colorchief
- Flicker-free
- LCD display
- Suitable for outdoor use IP65
- For application areas such as: Decoration; wedding/gala/events; mobile djs / entertainer; party room; restaurants, bars and hotels
- Silent operation
- Application possibility: Standing

Logistic

EAN / GTIN: 4026397748352

Weight: 24,00 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

ROADINGER Plastic Case for 8x AKKU Flat Light with Trolley

Trolley case

- Interior with foam padding
cover with foam padding
- 2 Rugged carrying handles
- 4 high-quality spring locks with shut-off function
- Trolley

Technical specifications:

Weight: 19.10 kg

EUROLITE AKKU IP Flat Light SMD bk

Power supply:	100-240 V AC, 50/60 Hz 12.6V DC 2500 mA
IP classification:	IP65
Protection class:	Protection class III
Power connection:	Mains input via coaxial power connector (M) mounting version power supply cord with Euro plug (provided) Battery/battery pack
Battery pack type:	2 x lithium ion 11.1 V, 2600 mAh, 28.86 Wh
Battery pack:	Battery operation up to 16h depending on program used Recharging time 4h
Lamp type:	LED lamp
LED type:	81 x 0.2 W SMD 5050 4in1 QCL RGBW (homogenous color mix)
Flash rate:	1 - 23 Hz
DMX channels:	3; 4; 6; 8; 10
Cooling:	Passive convection cooling
Control:	Master/slave function; IR remote control; QuickDMX; stand-alone; sound to light via microphone
Fixtures available for:	Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Light J; Colorchief
Projection:	Flicker-free
Carrier frequency:	2.4 GHz
Beam angle (1/10 peak):	120°
Housing color:	Black
Display type:	LCD display
Dimensions:	Length: 17.2 cm Width: 13.8 cm Depth: 6.4 cm
Weight:	1.60 kg
Noise classification:	Class 0 (no noise at all)

Battery:	1 x button cell 3.0 V CR2032 lithium manganese built-in
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Plastic Case for 8x AKKU Flat Light with Trolley

Maximum load:	50 kg
Carrying handle:	2 pc/pcs
Lock:	Spring lock: 4 pc/pcs with shut-off function
Transport aid:	Trolley
Material:	Plastic
Color:	Black
Inside dimensions:	49 cm x 36 cm x 16 cm
Device compartment:	17.8 cm x 6.5 cm x 14 cm
Accessory compartment:	7.8 cm x 32.7 cm x 18.5 cm
Dimensions:	Width: 55 cm Depth: 42 cm Height: 26 cm
Weight:	6.30 kg

Scope of delivery:

8 x EUROLITE AKKU IP Flat Light SMD bk

- 1 x device
- 1 x external mains adapter
- 2 x battery
- 1 x remote control
- 1 x user manual

1 x ROADINGER Plastic Case for 8x AKKU Flat Light with Trolley

- 1 x case