



8x



Features:

EUROLITE AKKU IP Flat Light 3 bk

Flat IP65 spotlight in black with 3 x 8 W 4in1 RGBW LED, QuickDMX transceiver

- Integrated QuickDMX transceiver for wireless DMX control
- Cordless, flexible and versatile
- Battery operation up to 16h depending on program used
- Integrated automatic charging of the battery and status indicator
- 3 LEDs 8 W SMD 9080 4in1 RGBW (homogenous color mix)
- Dimmer electronic; Dimmer speed (step response) adjustable; color blend stepless; color change adjustable; colors preset
- Strobe effect
- The device is cooled by passive convection cooling
- Control via master/slave function; IR remote control; QuickDMX; stand-alone; sound to light via microphone
- Fixtures available for Light´J; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Colorchief
- Flicker-free
- With a beam angle of 15°
- With mounting bracket
- LCD display
- Suitable for outdoor use IP65
- For application areas such as: Decoration; wedding/gala/events; mobile djs / entertainer; party room; restaurants, bars and hotels
- Silent operation
- Application possibility: Standing

Logistic

EAN / GTIN: 4026397748369

Weight: 24,00 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

ROADINGER Plastic Case for 8x AKKU Flat Light with Trolley

Trolley case

- Interior with foam padding
cover with foam padding
- 2 Rugged carrying handles
- 4 high-quality spring locks with shut-off function
- Trolley

Technical specifications:

Weight: 22.30 kg

EUROLITE AKKU IP Flat Light 3 bk

| | |
|-------------------------|--|
| Power supply: | 100-240 V AC, 50/60 Hz 12.6V DC 2500 mA |
| IP classification: | IP65 |
| Protection class: | Protection class III |
| Power connection: | Mains input via coaxial power connector (M) mounting version power supply cord with Euro plug (provided) Battery/battery pack |
| Battery pack type: | 2 x lithium ion 11.1 V, 2600 mAh, 28.86 Wh |
| Battery pack: | Battery operation up to 16h depending on program used Recharging time 4h |
| Lamp type: | LED lamp |
| LED type: | 3 x 8 W SMD 9080 4in1 RGBW (homogenous color mix) |
| Flash rate: | 1 - 23 Hz |
| DMX channels: | 3; 4; 6; 8; 10 |
| Cooling: | Passive convection cooling |
| Control: | Master/slave function; IR remote control; QuickDMX; stand-alone; sound to light via microphone |
| Fixtures available for: | Light J; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Colorchief |
| Projection: | Flicker-free |
| Carrier frequency: | 2.4 GHz |
| Beam angle (1/2 peak): | 15° |
| Beam angle (1/10 peak): | 33° |
| Housing color: | Black |
| Attachment system: | Mounting bracket |
| Display type: | LCD display |
| Dimensions: | Width: 17.2 cm Depth: 13.8 cm Height: 6.2 cm |

| | |
|-----------------------|---|
| Weight: | 1.61 kg |
| Noise classification: | Class 0 (no noise at all) |
| Battery: | 1 x button cell 3.0 V CR2032 lithium manganese built-in |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |

ROADINGER Plastic Case for 8x AKKU Flat Light with Trolley

| | |
|------------------------|---|
| Maximum load: | 50 kg |
| Carrying handle: | 2 pc/pcs |
| Lock: | Spring lock: 4 pc/pcs with shut-off function |
| Transport aid: | Trolley |
| Material: | Plastic |
| Color: | Black |
| Inside dimensions: | 49 cm x 36 cm x 16 cm |
| Device compartment: | 17.8 cm x 6.5 cm x 14 cm |
| Accessory compartment: | 7.8 cm x 32.7 cm x 18.5 cm |
| Dimensions: | Width: 55 cm Depth: 42 cm Height: 26 cm |
| Weight: | 6.30 kg |

Scope of delivery:

8 x EUROLITE AKKU IP Flat Light 3 bk

- 1 x device
- 1 x external mains adapter
- 1 x power cord
- 1 x remote control
- 1 x battery
- 1 x declaration of conformity
- 1 x user manual

1 x ROADINGER Plastic Case for 8x AKKU Flat Light with Trolley

- 1 x case